PATENT

Attorney Docket No.: CXU-339

5

UNITED STATES PATENT APPLICATION

10

15

ENTITLED

DESIGNS FOR WIDE BAND ANTENNAS WITH PARASITIC ELEMENTS AND
A METHOD TO OPTIMIZE THEIR DESIGN USING A GENETIC
ALGORITHM AND FAST INTEGRAL EQUATION TECHNIQUE

20

 \mathbf{BY}

CHALMERS BUTLER

25

AND

SHAWN ROGERS

PATENT

Attorney Docket No: CXU-339

UNITED STATES PATENT APPLICATION

TITLE:

5

15

20

25

30

Designs for Wide Band Antennas with Parasitic Elements and a Method to Optimize Their Design Using a Genetic Algorithm and Fast Integral Equation Technique

PRIORITY CLAIM

This application claims the benefit of previously filed U.S. Provisional

Application with the same titles and inventors as present, assigned USSN 60/215,434, filed on June 30,2000, and which is incorporated herein by reference.

INCORPORATION BY REFERENCE OF MATERIAL SUBMITTED ON <u>COMPACT DISC</u>

A computer program listing appendix that includes a genetic algorithm utilized in accordance with aspects of the presently disclosed technology is contained on a submitted compact disc. Each of two identical copies of such compact disc includes a file named "CXU-339 Genetic Algorithm", dated 04/04/2005 and having a size of 126 KB. The program listing contained in such file is hereby incorporated by reference for all purposes.

FIELD OF THE INVENTION

This technology provides a method (application) of an algorithm to facilitate the design of wideband operations of antennas, and the design of sleeve cage monopole and sleeve helix, units. The technology is of interest/commercial potential throughout the audio communications community.

Omnidirectional capabilities and enhanced wideband capabilities are two desirable features for the design of many antenna applications. Designing omnidirectional antennas with wideband capabilities requires rapid resolution of complex relationship among antenna components to yield an optimal system. The invention

comprises the use of a genetic algorithm with fitness values for design factors expressed in terms to yield optimum combinations of at least two types of antennas.

Cage antennas are optimized via a genetic algorithm (GA) for operation over a wide band with low voltage standing wave ratio (VSWR). Numerical results are compared to those of other dual band and broadband antennas from the literature. Measured results for one cage antenna are presented.

Genetic algorithms and an integral equation solver are employed to determine the position and lengths of parasitic wires around a cage antenna in order to minimize voltage standing wave ratio (VSWR) over a band. The cage is replaced by a normal mode quadrifilar helix for height reduction and the parasites are re-optimized. Measurements of the input characteristics of these optimized structures are presented along with data obtained from solving the electric field integral equation.

Genetic algorithms (Y. Rahmat-Samii and E. Michielssen, *Electromagnetic Optimizations by Genetic Algorithms*, New York: John Wiley and Sons, Inc., 1999) are used here in conjunction with an integral equation solution technique to determine the placement of the parasitic wires around a driven cage. The cage may be replaced by a quadrifilar helix operating in the normal mode in order to shorten the antenna. Measurements of these optimized structures are included for verification of the bandwidth improvements.

20

25

30

5

10

15

BACKGROUND OF THE INVENTION

Recent advances in modern mobile communication systems, especially those whichemploy which employ spread-spectrum techniques such as frequency hopping, require antennas whichhave which have omnidirectional radiation characteristics, are of low profile, and can be operated over operated over a very wide frequency range. The simple whip and the helical antenna operating inits in its normal mode appear to be attractive for this application because they naturally haveomnidirectional have omnidirectional characteristics and are mechanically simple. However, these structures are inherently narrow band and fall short of needs in this regard. Hence, additionalinvestigations additional investigations must be undertaken to develop

methods to meet the wide bandwidthrequirement bandwidth requirement of the communication systems.

5

10

15

20

25

30

BRIEF SUMMARY OF THE INVENTION

This invention comprises a method to design (produce) a product and the product(s) designed/produced as a result of the application of the method. The products are broadband, omnidimensional communications antennas, and the design procedure involves the coordinated, sequential application of two algorithms: a generally described "genetic algorithm that simulates population response to selection and a new algorithm that is a fast wire integral equation solver that generates optimal multiple antenna designs from ranges of data that limit the end product. Individual designs comprise a population of designs upon which specified selection by limiting the genetic algorithm ultimate identifies the optimum design(s) for specified conditions. Superior designs so identified can be regrouped and a new population of designs generated for further selection/refinement.

The products are the antenna designs and specifications derived as a product of the application of the method briefly described above. The antennas all are characterized generally as broad band and omni directional, two features of critical importance in antenna design. In addition, although much of the theory has been developed on monopole antennas, both the method and designs include both monopole and dipole designs. In addition, the designs include sleeve-cage and sleeve-helix designs as hereinbelow further described.

The cage monopole comprises four vertical, straight wires connected in parallel and driven from a common stalk at the ground plane. The parallel straight wires are joined by crosses made of brass (or other conductive) strips, the width of which is equal to the electrical equivalent of the wire radius. Compared to a single wire, this cage structure has a lower peak voltage standing wave ratio (VSWR) over the band. A structure with lower VSWR is amenable to improved bandwidth characteristics with the addition of parasitic elements.

Adding parasitic elements of equal height and distance from the center of the eage monopole creates a sleeve eage monopole. The sleeve eage monopole has a greater

bandwidth than its otherwise comparable antennas. Fitness values are determined by relative bandwidth, with greater fitness being associated with wider bandwidth defined by £2/f1, where £2 and £1 are respectively the largest and smallest frequencies between which VSWR is 3.5 or less. Speed of optimization is increased by interpolation of the impedance matrix.

The heart of the process is the solution of the equation governing total axial current. The executable algorithm linked to the genetic algorithm by the fast wire integral equation solver provides a rapid method of solving this equation for varied values and inputs. The basic theory and equations are incorporated completely herein. See, S.D. Rogers and C.M. Butler, "An efficient curved wire integral equation solution technique," submitted to *IEEE Trans. Antennas Propagat*.

Reduced height without loss of bandwidth or omni-directional capabilities is a desired feature of antenna designs for a plurality of applications. These include installations in vehicles and confined interior spaces. The helix structure yields shorter antennas than the traditional whip structure with otherwise comparable features. Height is a function of the pitch angle of the helix, such that a pitch angle of 42 degrees reduces height by 30 percent. The addition of parasitic elements reduces VSWR in a helix configuration in a magnitude similar to the reduction noted for the eage monopole design.

Many modern wireless communication systems require low-profile antennas. To meet this requirement, we consider the helical antenna operating in the normal mode. A normal mode helix and a straight wire antenna having approximately the same wire length exhibit similar input impedance and far field patterns. One drawback to the helix operating in the normal mode is that its bandwidth is too limited for many applications. To increase the bandwidth, we have considered several potential remedies, one of which is discussed herein. It is well known that adding additional parasitic straight wires on either side of a driven dipole antenna may increase the bandwidth of the dipole (J.L. Wong and H.E. King, AP-21, no. 5, 725-727, Sept. 1973). One must be especially eareful, however, to choose parasitic elements with the proper length and spacing. We use this basic idea to increase the bandwidth of the helical monopole. A structure similar to the sleeve dipole but applied to the helix has been used to design dual frequency antennas (P. Eratuuli, et. al., Electronics Letters, v. 32, no. 12, 1051-1052, June 1996).

The helix and its helical sleeve are both driven in the antenna of this reference. Several novel antenna structures are considered such as a driven helical antenna adjacent to parasitic helices and straight wires. Another candidate structure consists of a driven helix with helical parasites inside or outside of the driven element, which has the added benefit of conserving space. In any case, due to the large number of parameters in a helix, it is more difficult to design a broadband sleeve helical antenna than is the case for a sleeve dipole. It is not feasible to obtain optimum values of parameters by trial and error. Thus we employ a genetic algorithm routine (D.L. Carroll, A FORTRAN Genetic Algorithm Driver, http://www.staff.uiuc.edu/-carroll/ga.html) and efficient integral equation solution techniques to optimize the antenna system for bandwidth. Having an efficient numerical solution technique is necessary for this problem since the geometry of the antenna is redefined for each structure evaluated by the genetic algorithm. Since these antennas have a high degree of curvature, their solutions generally require a large number of unknowns for representing the geometry. An efficient solution technique which gets around this problem is used (S.D. Rogers and C.M. Butler, APS Symposium Digest, vol. I, 68-71, July 1997).

1) Commission B. B-2 Antennas

5

10

15

30

- 2) A genetic algorithm is used to optimize helical parasitic elements for a helical antenna.
- 3) This work is an extension to increasing the bandwidth of dipoles by use of parasites. This research could not have been completed in a time efficient manner without the development of an efficient integral equation solution technique for curved wires with reference below.
- S.D. Rogers and C.M. Butler, "Reduced Rank Matrices for Curved Wire Structures," Digest of IEEE APS Symposium, Montreal, Canada, vol. I, pp. 68-71, July 1997.

We have recently shown from numerical calculations that the bandwidth of a normal mode helix can be increased by the addition of close-by wire parasites (S.D. Rogers, J.C. Young, and C.M. Butler, "Bandwidth Enhanced Normal Mode Helical

Antennas," Digest 1998 USNC / URSI National Radio Science Meeting, Atlanta, GA., p. 293, June 1998). Agenetic algorithm and a fast integral equation solution technique are employed to determine the optimum distance and height of these parasites. In (H.E. King and J.L. Wong, "An Experimental Study of a Balun Fed Open Sleeve Dipole in Front of a Metallic Reflector," IEEE Trans. Antennas Propagat. (Commun.), vol. AP-20, pp. 201-204, March 1972) these parameters were determined experimentally when the driven element was a straight wire dipole. In a recent paper (H. Nakano, et. al., "Realization of Dual Frequency and Wide Band VSWR Performances Using Normal Mode Helical and Inverted F Antennas," IEEE Trans. Antennas Propagat., vol. AP-46, June 1998) a central parasitic straight cylinder was added inside a driven single wire helix to obtain dual frequency operation. We have found that even greater bandwidth, over that of a single driven wire, can be realized when the parasites are placed around "cage" monopoles having several parallel wires. Similar observations are made about a multifilament versus a single filament helix.

. 5

10

15

20

25

30

Bandwidth of vertically polarized wire antennas is often increased by adjustment of the antenna geometry. King and Wong reduce VSWR by placing parasitic wires around a driven element, creating the well-known open sleeve dipole (KING, H.E., and WONG, J.L.: 'An experimental study of a balun-fed open-sleeve dipole in front of a metallic reflector', *IEEE Trans. Antennas Propagat.*, March 1972, 20, (2), pp. 201-204). In (NAKANO, H., IKEDA, N., WU, Y., SUZUKI, R., MIMAKI, H., and YAMAUCHI, J.: 'Realization of dual-frequency and wide-band VSWR performances using normal-mode helical and inverted-F antennas', *IEEE Trans. Antennas Propagat.*, June 1998, 46, (6), pp. 788-793) the displacement of a parasitic monopole is varied inside a driven normal mode helical antenna in order to control its characteristics. Cage antennas can be made broadband when their dimensions are chosen judiciously. Genetic algorithms and integral equation solution techniques are employed here to optimize the dimensions of the cage antenna in order to create a structure with low VSWR over a wide band.

Recent advances in modern mobile communication systems, especially those which employ spread-spectrum techniques such as frequency hopping, require low-profile, broadband, omnidirectional (in azimuth) antennas. The simple whip and the helical antenna, operating in its normal mode, are potentially attractive for these

applications because they naturally have suitable radiation characteristics and are mechanically simple and rugged. However, these structures are inherently narrow band. Hence, additional measures are employed to meet the wide bandwidth requirement of communication systems. Antennas often are loaded with tuning circuits and are connected to radios through matching networks in order to improve overall bandwidth. Altering the antenna geometry is another method for modifying bandwidth properties. The sleeve monopole, in which the outer conductor of the coaxial feed line forms a "sleeve" around the base of the protruding center conductor, is known to have greater bandwidth than the conventional monopole and has been studied extensively (J. Taylor, "The sleeve antenna," doctoral dissertation, Cruft Lab., Harvard Univ., Cambridge, MA, 1950); (R.W.P. King, The Theory of Linear Antennas. Cambridge, MA: Harvard Univ Press, 1956); (A.J. Poggio and P.E. Mayes, "Pattern bandwidth optimization of the sleeve monopole antenna," IEEE Trans. Antennas Propagat. (Commun.), vol. AP-14, pp. 643-645, Sept. 1966); (Z. Shen and R. MacPhie, "Rigorous evaluation of the input impedance of a sleeve monopole by modal-expansion method," IEEE Trans. Antennas Propagat., vol. AP-44, pp. 1584-1591, Dec. 1996). A variation of this antenna is the open-sleeve dipole which has straight-wire parasites in place of the coaxial sleeve. The effects of the spacing and size of the parasitic elements on the VSWR are determined experimentally in (H.E. King and J.L. Wong, "An experimental study of a balun-fed open-sleeve dipole in front of a metallic reflector," IEEE Trans. Antennas Propagat. (Commun.), vol. AP-20, pp. 201-204, March 1972). In other papers, parasitie and driven elements of various sorts are combined in order to create dual band antennas. In (P. Eratuuli, et. al., "Dual frequency wire antennas," Electronics Letters, vol. 32, no. 12, pp. 1051-1052, June 6, 1996) the driven wire is a straight monopole or a helix surrounded by a parasitic helix. In (H. Nakano, et. al., "Realization of dual-frequency and wide-band VSWR performances using normal-mode helical and inverted-F antennas," IEEE Trans. Antennas Propagat., vol. AP-46, pp. 788-793, June 1998) the position of a straight-wire parasite inside a driven normal mode helical antenna is adjusted to control the VSWR over the band of operation. Another antenna, which can be made to have broadband properties if its dimensions are chosen judiciously, is the eage antenna (S.D. Rogers and C.M. Butler, "Cage antennas optimized for bandwidth," submitted to Electronics Letters, April 2000).

5

10

15

20

25

30

The cage is more amenable than a single straight wire to improvement in bandwidth when parasitic wires of appropriate size and spacing are added (S.D. Rogers and C.M. Butler, "The sleeve-cage monopole and sleeve helix for wideband operation," *Digest of APS Symposium*, Orlando Florida, vol. 2, pp. 1308-1311, July 1999).

5

10

20

30

We have found that the cage structure and multifilar helices are more amenable than single wire antennas to improvements in VSWR when parasitic wires are added. The helical configuration can be used to reduce the height of the antenna, but at the sacrifice of bandwidth. While the addition of the parasitic wires improves the overall bandwidth, the VSWR increases outside the design band. Fast integral equation solution techniques and optimization methods have been developed in the course of this work and have led to effective tools for designing broadband antennas.

Certain exemplary attributes of the invention may relate to a method to create optimum design specifications for omni-directional, wide band antennas comprising the steps of:

- (a) loading software including a genetic algorithm and an executable algorithm that is a fast wire equation solver into a computer;
 - (b) loading instructions into said computer specifying basic antenna design to be optimized;
 - (c) loading antenna design parameters and corresponding ranges of values for said parameters into said computer;
 - (d) specifying resolution of said parameters by loading number of bits per parameter into said computer;
 - (e) executing (operating) said genetic algorithm thereby generating a population of individual antenna designs each with a fitness value; and
- 25 (f) evaluating relative fitness of antenna designs produced and selecting superior designs for continued refinement.

The foregoing method may further comprise the following exemplary subroutines and algorithms for the software involved:

- (a) a first algorithm that allows different values for critical design elements to combined in all possible combinations and a fitness value for each design ultimately estimated;
- (b) a second algorithm that determines electronic current in an antenna by solving an

integral equation numerically;

5

10

15

20

25

30

(c) a computer program link that provides essential communication between said first algorithm and said second algorithm.

Certain exemplary attributes of the invention may further relate to the sleeve monopole antenna designs, the cage sleeve monopole antenna designs, and the sleeve dipole antenna designs produced following the foregoing methods. Those of ordinary skill in the art will appreciate that various modifications and variations may be practiced in particular embodiments of the subject invention in keeping with the broader principles of the invention disclosed herein. The disclosures of all the citations herein referenced are fully incorporated by reference to this disclosure.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

A full and enabling description of the presently disclosed subject matter, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which makes reference to the appended figures, in which:

- FIG. 1A is a perspective view of an exemplary cage monopole antenna embodiment in accordance with the presently disclosed technology;
- FIG. 1B is a graphical representation of the voltage standing wave ratio (VSWR) versus frequency for the exemplary cage monopole antenna of FIG. 1A;
- FIG. 1C is a graphical representation of the directivity versus frequency for the exemplary cage monopole antenna of FIG. 1A;
- FIG. 2A is a perspective view of an exemplary sleeve-cage monopole antenna embodiment in accordance with the presently disclosed technology;
- FIG. 2B is a graphical representation of the voltage standing wave ratio (VSWR) versus frequency for the exemplary sleeve-cage monopole antenna of FIG. 2A;
- FIG. 2C is a top view of an exemplary sleeve-cage monopole antenna embodiment in accordance with the presently disclosed technology;
- FIG. 2D is a graphical representation of the directivity versus frequency for the exemplary sleeve-cage monopole antenna of FIG. 2C;
- FIG. 3A is a perspective view of an exemplary quadrifilar helix antenna embodiment in accordance with the presently disclosed technology:

- FIG. 3B is a graphical representation of the voltage standing wave ratio (VSWR) versus frequency for the exemplary quadrifilar helix antenna of FIG. 3A;
- FIG. 3C is a graphical representation of the directivity versus frequency for the exemplary quadrifilar helix antenna of FIG. 3A;
- FIG. 4A is a perspective view of an exemplary sleeve helix antenna embodiment in accordance with the presently disclosed technology;
 - FIG. 4B is a graphical representation of the voltage standing wave ratio (VSWR) versus frequency for the exemplary sleeve helix antenna of FIG. 4A;
- FIG. 4C is a perspective view of an exemplary sleeve helix antenna embodiment

 in accordance with the presently disclosed technology;
 - FIG. 4D is a graphical representation of the directivity versus frequency for the exemplary sleeve helix antenna of FIG. 4C;
 - FIG. 5A is a graphical representation of VSWR versus frequency for a cage antenna optimized for VSWR < 2.0;
- FIG. 5B is a graphical representation of input impedance versus frequency for a cage antenna optimized for VSWR < 2.0;
 - FIG. 6A is a graphical representation of VSWR versus frequency for a cage antenna optimized for VSWR < 2.5;
- FIG. 6B is a graphical representation of directivity versus frequency for a cage
 antenna optimized for VSWR < 2.5;
 - FIG. 7A is a perspective view of an exemplary cage monopole antenna embodiment in accordance with the presently disclosed technology, having dimensions a = 0.814mm, d = 2.2cm, w = 3.256mm, $h_1 = 1.2$ cm, $h_2 = 16$ cm and $Z_0 = 50\Omega$;
 - FIG. 7B is a graphical representation of VSWR versus frequency for the exemplary cage monopole antenna of FIG. 7A;

25

- FIG. 7C is a graphical representation of the input impedance versus frequency for the exemplary cage monopole antenna of FIG. 7A;
- FIG. 7D is a graphical representation of the directivity versus frequency for the exemplary cage monopole antenna of FIG. 7A;
- FIG. 8A is a perspective view of an exemplary sleeve-cage monopole antenna embodiment in accordance with the presently disclosed technology, having dimensions a

= 0.814mm, d = 2.2cm, w = 3.256mm, $h_1 = 1.2$ cm, $h_2 = 16$ cm, r = 2.5cm, h = 4cm, and Z_0 $=50\Omega;$ FIG. 8B is a graphical representation of VSWR versus frequency for the exemplary sleeve-cage monopole antenna of FIG. 8A; FIG. 8C is a graphical representation of the input impedance versus frequency for 5 the exemplary sleeve-cage monopole antenna of FIG. 8A; FIG. 8D is a graphical representation of the directivity versus frequency for the exemplary sleeve-cage monopole antenna of FIG. 8A; FIG. 8E is a top view of the exemplary sleeve-cage monopole antenna of FIG. 8A; 10 FIG. 9A is a perspective view of an exemplary quadrifilar helical antenna embodiment in accordance with the presently disclosed technology, having dimensions a = 0.814mm, d = 2cm, w = 3.256mm, $h_1 = 0.91$ cm, $h_2 = 8.85$ cm, $Z_0 = 50\Omega$; FIG. 9B is a graphical representation of measured and computed VSWR versus frequency for the exemplary quadrifilar helical antenna of FIG. 9A; 15 FIG. 9C is a graphical representation of the measured and computed input impedance versus frequency for the exemplary quadrifilar helical antenna of FIG. 9A; FIG. 9D is a graphical representation of the computed directivity ($\phi = 0$) versus frequency for the exemplary quadrifilar helical antenna of FIG. 9A; FIG. 10A is a perspective view of an exemplary sleeve helical antenna 20 embodiment in accordance with the presently disclosed technology, having dimensions a = 0.814mm, d = 2cm, w = 3.256mm, $h_1 = 0.91$ cm, $h_2 = 8.85$ cm, $Z_0 = 50\Omega$; FIG. 10B is a graphical representation of measured and computed VSWR versus frequency for the exemplary sleeve helical antenna of FIG. 10A; FIG. 10C is a graphical representation of the measured and computed input 25 impedance versus frequency for the exemplary sleeve helical antenna of FIG. 10A; FIG. 10D is a graphical representation of the computed directivity ($\phi = 0$) versus

11

FIG. 11A illustrates a curved wire helix for use in exemplary antenna technology

frequency for the exemplary sleeve helical antenna of FIG. 10A;

of the present subject matter:

30

	FIG. 11B illustrates a curved wire loop for use in exemplary antenna technology
of the	present subject matter;
	FIG. 11A illustrates a curved wire meander line for use in exemplary antenna
echno	plogy of the present subject matter;
	FIG. 12 illustrates an arbitrary curved wire of radius a with source point,
bserv	vation point, and unit vectors;
	FIG. 13 illustrates an exemplary straight line segment approximation of a curved-
ire a	<u>xis;</u>
	FIG. 14 illustrates exemplary geometric parameters for adjacent straight line
egme	ents:
	FIG. 15 represents a triangular basis function Λ_n ;
	FIG. 16 illustrates an exemplary piecewise linear expansion of the current along a
<u>ieanc</u>	ler line;
	FIG. 17 represents a testing pulse Π_n ;
	FIG. 18 illustrates exemplary source and observation points on adjacent straight-
vire s	egments;
	FIG. 19 illustrates exemplary source and observation points on different linear
ire s	egments;
	FIG. 20 represents a composite triangle basis function $\tilde{\Lambda}_q$ with five constituent
riang	<u>les;</u>
	FIG. 21 represents an exemplary constituent triangle Λ_i^q ;
	FIG. 22 represents an exemplary composite testing pulse $\underline{\widetilde{\Pi}_p}$;
	FIG. 23 represents an exemplary constituent testing pulse Π_k^p ;
	FIG. 24 illustrates current expansion with composite basis functions;
	FIG. 25A is a graphical representation of the real part of current versus degrees on
vire le	oop antennas;
	FIG. 25B is a graphical representation of the imaginary part of current versus
degree	es on wire loop antennas:

FIG. 26A is a graphical representation of the real part of current on the wire loop antenna of FIGS. 25A and 25B without composite basis function at the source; FIG. 26B is a graphical representation of the imaginary part of current on the wire loop antenna of FIGS. 25A and 25B without composite basis function at the source; FIG. 27 is a graphical representation of mode 2 current on one arm of four arm 5 Archimedian spiral antenna having spiral constant 0.02λ , arm length 12λ and wire radius 0.006λ ; FIG. 28 is a graphical representation of the magnitude of mode 2 current on one arm of four arm Archimedian spiral antenna having spiral constant 0.02λ , arm length 12λ and wire radius 0.006λ ; 10 FIG. 29 is a graphical representation of the magnitude of mode 2 current on one arm of four arm Archimedian spiral antenna having spiral constant 0.02λ, arm length 12λ and wire radius 0.006λ with data for comparison; FIG. 30A is a perspective view of an exemplary helical geometry; FIG. 30B represents additional exemplary definitions of helical parameters; 15 FIG. 31 is a graphical representation of current versus arc displacement on a helix illuminated by a plane wave, $E = (\hat{x}\cos\theta + \hat{z}\sin\theta)e^{-jk(x\sin\theta - z\cos\theta)}$, $(\theta = 45^{\circ}, L = 0.5\lambda, v = 10, \alpha = 20^{\circ}, a = 0.0005\lambda);$ FIG. 32 is a graphical representation of current versus arc displacement on a helix illuminated by a plane wave, $E = (\hat{x}\cos\theta + \hat{z}\sin\theta)e^{-jk(x\sin\theta - z\cos\theta)}$, 20 $(\theta = 45^{\circ}, L = 0.35\lambda, v = 10, \alpha = 20^{\circ}, a = 0.0005\lambda);$ FIG. 33 is a graphical representation of current versus arc displacement on a helix illuminated by a plane wave, $E = \hat{z}e^{-jk\alpha}$, $(L = 2\lambda, v = 50, \alpha = 20^{\circ}, a = 0.0005\lambda)$; FIG. 34 is a graphical representation of current versus arc displacement on a helix driven by delta-gap source ($L = 0.25\lambda$, v = 25, $\alpha = 20^{\circ}$, $a = 0.0005\lambda$); 25 FIG. 35 is a graphical representation of current versus arc displacement on a helix driven by delta-gap source ($L = \lambda$, v = 25, $\alpha = 20^{\circ}$, $a = 0.0005\lambda$); FIG. 36 is a graphical representation of current versus arc displacement on a helix driven by delta-gap source ($L = 0.5\lambda$, $C_h = 0.1\lambda$, $\alpha = 12.5^{\circ}$, $a = 0.005\lambda$);




	FIG. 44C is a graphical representation of input impedance versus frequency for
	the exemplary antenna of FIG. 44B;
	FIG. 44D is a graphical representation of directivity versus frequency for the
	exemplary antenna of FIG. 44B;
5	FIG. 45A is a graphical representation of VSWR versus frequency for the
	exemplary antenna of FIG. 45B;
	FIG. 45B is a perspective view of an exemplary helix antenna with inner and
	outer helical parasites;
	FIG. 46A is a perspective view of an exemplary antenna base portion and
10	representative cylinder around which the coils of a triple helix antenna are wound;
	FIG. 46B is a perspective view of an exemplary triple helix antenna;
	FIG. 46C is a graphical representation of VSWR versus frequency for a triple
	helix antenna (such as one depicted in FIGS. 46A and 46B) compared with a single helix
	antenna;
15	FIG. 47A is a graphical representation of VSWR versus frequency for the
	exemplary antenna of FIG. 47B compared with a single helix and a triple helix antenna;
	FIG. 47B is a perspective view of an exemplary triple helix antenna with four
	straight wire parasites;
	FIG. 47C is a graphical representation of directivity versus frequency for a triple
20	helix antenna;
	FIG. 47D is a graphical representation of directivity versus frequency for a triple
	helix antenna with parasites, such as the one illustrated in FIG. 47B;
	FIG. 48A is a graphical representation of VSWR versus frequency for cage
	monopole antenna optimization for VSWR < 2.5;
25	FIG. 48B is a graphical representation of directivity versus frequency for cage
	monopole antenna optimization for VSWR < 2.5;
	FIG. 49A is a graphical representation of VSWR versus frequency for cage
	monopole antenna optimization for VSWR < 2.0; and
	FIG. 49B is a graphical representation of directivity versus frequency for cage
30	monopole antenna optimization for VSWR < 2.0.

<u>DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS</u> <u>DESIGN PROCEDURE:</u>

5

10

15

20

25

30

We modeled and measured the properties of a so-called cage monopole. The cage monopole shown in Figure 101aFIG. 1A consists of four vertical straight wires connected in parallel and driven from a common stalk at the ground plane. The ground plane in this model is assumed to be of infinite extent to facilitate analysis. The parallel straight wires are joined by crosses constructed of brass strips. The strip width was selected to be electrically equivalent to the wire radius for the purpose of modeling the structure. Compared to a single, thin, straight wire, the cage structure with multiple wires has a lower peak voltage standing wave ratio (VSWR) over the band. This is important since a structure which has a comparatively small VSWR over a band is more amenable to improvements in bandwidth with the addition of other components such as loads or parasites than is the common single-wire monopole with higher VSWR.

Next we add four parasitic straight wires of equal height (h) and distance (r) from the center of the cage to create the so-called "sleeve-cage monopole" of Figure 102aFIG. 2A. The A genetic algorithm (GA) of (D.L. Carroll, "A FORTRAN Genetic Algorithm" Driver", Univ. of Illinois, Urbana, IL, http://www.staff.uiuc.edu/~carroll/ga.html) is used to determine the optimum distance and height of these parasitic straight wires. In this example the fitness value assigned to each antenna in the optimization process is the bandwidth ratio defined by f_2 / f_1 , where f_2 and f_1 are, respectively, the largest and smallest frequencies between which the VSWR is 3.5 or less. We interpolate the impedance matrix with respect to frequency in order to increase the speed of the optimization process. To design antennas that are smaller, we turn our attention to the normal mode helix, since, for operation about a given frequency, it can be made shorter than the vertical whip by adjustment of the pitch angle. Also, we observe a decrease in the peak VSWR when additional filaments are added to the helix driven from a central straight wire. Generally, a normal mode helix will exhibit electrical properties similar to those of a straight wire having the same wire length, though the peak VSWR for the helix is usually greater. The quadrifilar helix of Figure 103aFIG. 3A whose height is 9.8 cm can be used in the same bands as a cage monopole of height about 14 cm. Thus, the total height of the antenna can be reduced by 30% with the 42° pitch angle. Parasitic straight

wires of optimum height and distance are added to create what we call the "sleeve helical monopole" shown in Figure 104aFIG. 4A.

RESULTS AND DISCUSSION:

5

10

15

20

As one can see from the VSWR data, good agreement is achieved between predictions computed by means of our numerical techniques and results measured on a model mounted over a large ground plane. The frequency range over which data are presented is dictated by the frequencies over which our ground plane is electrically large. The slight discrepancies in the computed and measured results are attributed to imprecision in the construction of the antennas. The predicted results of bandwidth and VSWR of each antenna are summarized in the table Table 1 below.

Structure	VSWR	BW Ratio	BW %	Frequency Range	Height	Width
				(MHZ)	(cm)	(cm)
Cage monopole	<5.0	11.7:1	312	300-3500	17.2	2.2
	<3.5	3:1	115	950-2850		
Sleeve-cage	<5.0	5.2:1	185	315-1650	17.2	5
monopole	<3.5	4.4:1	163	350-1550		
Quadrifilar helix	<5.0	5.8:1	199	475-2750	9.8	2
	<3.5	1.6:1	47	500-800		
Sleeve helix	<5.0	3.9:1	147	475-1850	9.8	6
•	<3.5	3.5:1	134	500-1750		

Table 1

We point out that when the parasitic elements are added to each structure, the bandwidth ratio increases for the VSWR < 3.5 requirement. However, outside of this frequency range the VSWR is worse than that of the antenna without parasites. In other words, VSWR has, indeed, been improved markedly over the design range but at a sacrifice in performance outside the range, where presumably the antenna would not be operated. Also, notice that the deep nulls in the directivity at the horizon for the cage and the quadrifilar helix structures have been eliminated with the addition of the parasites. Thus the directivity is improved in the band where on the basis of VSWR this antenna is deemed operable, although there was no constraint on directivity specified in the objective function.

CAGE ANTENNAS OPTIMIZED FOR BANDWIDTH

Design Method: The antenna whose characteristics are represented in FIGS. 5A and 5B is optimized for a design goal of VSWR < 2.0 over the frequency band 500 to 1600 MHz. The cage antenna is depicted in Fig. 201FIG. 7A where one sees four vertical wires joined to the feed and stabilized by thin brass strips of width w. The strips are treated as wires of radius a = w/4. The A GA of (CARROLL, D.L.: 'Chemical Laser Modeling with Genetic Algorithms', AIAA Journal, Feb. 1996, 34, (2), pp. 338-346) is applied to optimize the diameter (a) of the cage structure and the length (a) of the wires in the cage. Each function evaluation consists of numerically solving the electric field integral equation for the cage geometry (having dimensions chosen by the GA) over the band of interest. Candidate antennas are given a fitness score equal to the bandwidth ratio a0 ft is the lowest and a1 is the highest frequency of operation over a band where the VSWR meets the design goal.

Results: The antenna of Fig. 202whose characteristics are represented in FIGS. 5A and 5B is optimized for a design goal of VSWR < 2.0 over the frequency band 500 to 1600 MHz. The GA picks the parameter d from a range of 1 cm to 5 cm with a resolution of 0.13 cm (5 bits, 32 possibilities). The range specified for parameter h_2 is 8 cm to 12 cm with a resolution of 0.27 cm (4 bits, 16 possibilities). The GA converges to an optimum solution after three generations with five antennas per generation. A sensitivity analysis reveals that antenna input characteristics change only modestly with small geometric variation. The directivity of this cage antenna for $\phi = 0^{\circ}$ and $\phi = 75^{\circ}$,90° is above 4 dBi over the entire band. The properties of this antenna and those of Nakano's helical monopole (NAKANO, H., IKEDA, N., WU, Y., SUZUKI, R., MIMAKI, H., and YAMAUCHI, J.: 'Realization of dual-frequency and wide-band VSWR performances using normal-mode helical and inverted-F antennas', IEEE Trans. Antennas Propagat., June 1998, 46, (6), pp. 788-793), which is designed to operate with VSWR < 2.0 in two frequency bands, are listed in Table 201 for comparison.

Structure	Cage	HX-MP	Cage	Sleeve Dipole
	(Figure 6)		(Figure 7)	
VSWR	<2	<3.5	<2.5	<2.5
Bandwidth Ratio	2.6	1.7	5.4	1.8
f (MHz)	575-1500	627-1048	210-1130	225-400

Height (cm)	10.3	19.8	26.55	51
Width (cm)	4.7	0.47	8.2	13
Wire radius (mm)	0.814	0.3	3.175	14.3

Table 2

The antenna of Fig. 203 whose characteristics are represented in FIGS. 6A and 6B is optimized for a design goal of VSWR < 2.5 in the frequency range 200 to 1200 MHz. This range is chosen for comparison of the cage antenna to the open sleeve dipole of (KING, H.E., and WONG, J.L.: 'An experimental study of a balun-fed open-sleeve dipole in front of a metallic reflector', *IEEE Trans. Antennas Propagat.*, March 1972, 20, (2), pp. 201-204) which operates over the frequency range 225 to 400 MHz. The GA is allowed to choose parameter d from 1 cm to 10 cm with a resolution of 0.6 cm (4 bits, 16 possibilities). The parameter h_2 is selected from 20 cm to 25 cm with a resolution of 0.33 cm (4 bits, 16 possibilities). An optimum result is reached after 11 generations with five antennas per generation. This cage monopole is not useful over the entire frequency range for which its VSWR is less than 2.5 since there is a null in the directivity within this range. It is operable over a 3.6:1 bandwidth for VSWR less than 2.5 and directivity greater than 0 dBi. In Table 201 are listed the properties of the cage antenna together with those of the sleeve dipole.

CAGE MONOPOLE AND SLEEVE-CAGE MONOPOLE

5

10

15

20

25

The cage monopole shown in Figure 301aFIG. 7A consists of four vertical straight wires connected in parallel and driven from a common wire which is the extension of the center conductor of a coaxial cable protruding from the ground plane. The ground plane in this model is assumed to be of infinite extent in the analysis of the structure. The parallel straight wires are joined by crosses constructed of brass strips. The strip width w was selected to be electrically equivalent to the wire radius a for the purpose of modeling the structure (w=4 a) (C.M. Butler, "The equivalent radius of a narrow conducting strip," *IEEE Trans. Antennas Propagat.*, vol. AP-30, pp.755-758, July 1982). Compared to a single, thin, straight wire, the cage structure with multiple wires has a lower peak VSWR over the band as seen in Figure 301bFIG. 7B. This is important since a structure which has a comparatively small VSWR over a band is more amenable

to improvements in bandwidth with the addition of other components such as loads or parasites than is the common single-wire monopole with higher VSWR.

Four parasitic straight wires of equal height (h) and radial distance (r) from the center line of the cage are added to create the so-called "sleeve-cage monopole" of Figure 302aFIG. 8A. The genetic algorithm of (D.L. Carroll, "Chemical Laser Modeling with Genetic Algorithms," ALAA Journal, vol. 34, no. 2), pp. 338-346, Feb. 1996) A GA is used to determine optimum values of h and r for given design goals. An objective function evaluation for one antenna in the GA population involves numerically solving the electric field integral equation for many frequencies within the band of interest. Since this must be done for many candidate antennas, it is advantageous to interpolate the integral equation impedance matrix elements with respect to frequency (E.H. Newman, "Generation of wide-band data from the method of moments by interpolating the impedance matrix," IEEE Trans. Antennas Propagat., vol. AP-36, pp. 1820-1824, Dec. 1988). Each candidate structure is assigned a fitness value based on its electrical properties. A simple fitness value used here is the antenna bandwidth ratio which measures the performance of the antenna over a frequency band of interest denoted by $[f_A, f_B]$. The bandwidth ratio for a particular antenna is considered a function of its geometry and is computed from

$$F(h,r) = \frac{f_2}{f_1}$$

20 where

5

10

15

$$f_1 = \min_{f \in [f_a, f_B]} f$$
 such that $VSWR(f) \le limit$

and

$$f_2 = \max_{f \in [f_1, f_2]} f(f)$$
 such that $VSWR(f) \le \text{limit for all } f \in [f_1, f_2].$

Another viable fitness value is the percent bandwidth defined here as

$$\%BW = 100 \frac{f_2 - f_1}{\sqrt{f_2 f_1}}.$$

25 QUADRIFILAR HELIX AND SLEEVE HELIX

To design low profile antennas, we turn our attention to the normal mode helix, since, for operation about a given frequency, it can be made shorter than the vertical whip by adjustment of the helix pitch angle. Generally, a normal mode helix will exhibit electrical properties similar to those of a straight wire having the same wire length, though the peak VSWR for the helix is usually greater. The helix exhibits vertical polarization as long as it operates in the normal mode. There is a decrease in the peak VSWR, relative to that of a single-wire helix, when additional helical filaments are added to one driven from a central straight wire. The quadrifilar helix of Figure 303FIG. 9A whose height is 9.8 cm can be used in the same bands as a cage monopole of height about 14 cm. Thus, the total height of the antenna can be reduced by 30% with the 42° pitch angle. Parasitic straight wires of optimum height and distance are added to create what we call the "sleeve helical monopole" shown in Figure 304FIG. 10A. Most integral equation solution techniques for the helix are, in general, more computationally expensive since these require many basis functions to represent the vector direction of the current along the meandering wire. A solution procedure which uncouples the representation of the geometry from the representation of the unknown current is developed in (S.D. Rogers and C.M. Butler, "An efficient curved-wire integral equation solution technique," submitted to IEEE Trans. Antennas Propagat.) and is used here to reduce the time in optimization of antennas with curved wires.

RESULTS

5

10

15

20

25

30

As one can see from the VSWR data, good agreement is achieved between predictions computed by means of numerical techniques (S.D. Rogers and C.M. Butler, "An efficient eurved-wire integral equation solution technique," submitted to IEEE Trans. Antennas Propagat.) and results measured on a model mounted over a large ground plane. The frequency range over which our experiments are conducted is dictated by the frequencies over which the ground plane is electrically large. Of course, the dimensions of the antenna may be scaled for use in other bands. The slight discrepancies in the computed and measured results are attributed to the difficulty in building the antenna to precise dimensions. However, a sensitivity analysis reveals that the antenna performance changes minimally with small variations in geometry. The reflection coefficient is measured at the input of the coaxial cable driving the monopoles and of a

shorted section of coaxial line having the same length. Applying basic transmission line theory to these data, one can determine the measured input impedance of the antenna with the reference "at the ground plane." All VSWR data is for a 50Ω system. As the feed point properties of the various antennas are evaluated, we must also keep in mind the radiation properties of the antenna, so computed directivity is included herein. The predicted results of bandwidth and VSWR of each antenna are summarized in Table 301.

5

10

15

20

We point out that, when the parasitic elements are added to each structure, the bandwidth ratio increases for the VSWR < 3.5 requirement. However, outside of this frequency range the VSWR is worse than that of the antenna without parasites. In other words, VSWR has, indeed, been improved markedly over the design range but at a sacrifice in performance outside the range, where presumably the antenna would not be operated. Also, notice that the deep nulls in the directivity at the horizon for the cage and the quadrifilar helix structures have been eliminated with the addition of the parasites. Thus the directivity is improved in the band where, on the basis of VSWR, this antenna is deemed operable, although there was no constraint on directivity specified in the objective function.

A summary and comparison of the results for the various antenna structures represented in FIGS. 7A, 8A, 9A and 10A as well as Nakano's Helix Monopole and a SINCGARS dipole antenna that was developed and produced by ITT for the Army is included in the following Table 3.

Structure	<u>VSWR</u>	$\frac{\underline{\mathbf{BW Ratio}}}{\underline{f_1}}$	$ \frac{\mathbf{BW \%}}{100 \frac{(f_1 - f_2)}{\sqrt{f_1 f_2}}} $	Frequency Range (MHZ)	Height (cm)	Width (cm)
Cage monopole	<u><3.5</u>	3:1	<u>115</u>	950-2850	17.2	2.2
Sleeve-cage monopole	≤3.5	4.4:1	163	350-1550	17.2	5
Quadrifilar helix	≤3.5	1.6:1	<u>47</u>	500-800	9.8	2
Sleeve helix	≤3.5	3.5:1	134	<u>500-1750</u>	9.8	6
SINCGARS Antenna	≤3.5	2.9	112	30-88	280	2
Nakano's Helix Monopole	≤3.5	1.7	52	627-1048	19.8	0.4

Table 3

Additional results are now presented for the antenna of FIG. 7A with optimization for VSWR of less than 2.5. An antenna is tested having the following parameters: a =

3.175mm, d = 7.6cm, w = 1.27 cm, $h_1 = 2.55$ cm and $h_2 = 22.95$ cm. As seen in the graph of FIG. 48A, a VSWR of less than 2.5 is achieved over a frequency band of 212-1155 MHz, resulting in a bandwidth ratio of 5.5:1. FIG. 48B shows the directivity versus frequency for the same antenna for different angles of theta (θ). A summary and comparison of results for the optimization with VSWR<2.5 described above is listed in Table 4 below.

5

10

15

20

Structure	<u>VSWR</u>	$\frac{\textbf{BW Ratio}}{f_1}$	$\frac{\mathbf{BW \%}}{100 \frac{(f_1 - f_2)}{\sqrt{f_1 f_2}}}$	Frequency Range (MHZ)	Height (cm)	Width (cm)
King's open sleeve dipole	<u><2.5</u>	1.77	58.3	<u>225-400</u>	<u>51</u>	<u>13</u>
NTDR Antenna	<u><2.5</u>	2.0	<u>70</u>	<u>225-450</u>	<u>200</u>	<u>6.4</u>
Cage monopole	<u><2.5</u>	3.7	<u>139</u>	212-775	<u>25.5</u>	<u>7.6</u>

Table 4

Additional results are now presented for the antenna of FIG. 7A with optimization for VSWR of less than 2.0. An antenna is tested having the following parameters: a = 0.814mm, d = 4.8cm, w = 3.256cm, $h_1 = 1$ cm and $h_2 = 9$ cm. Results are presented in FIG. 49A for the described cage monopole antenna as well as for thin straight wire antenna and a fat straight wire antenna. As seen in the graph of FIG. 49A, a VSWR of less than 2.0 is achieved over a frequency band of 575-1500 MHz, resulting in a bandwidth ratio of 2.6:1. FIG. 49B shows the directivity versus frequency for the same antenna for different angles of theta (θ). A summary and comparison of results for the optimization with VSWR<2.0 described above is listed in Table 5 below.

Structure	VSWR	$\frac{\textbf{BW Ratio}}{f_1}$	$\frac{\mathbf{BW \%}}{100 \frac{(f_1 - f_2)}{\sqrt{f_1 f_2}}}$	Frequency Range (MHZ)	Height (cm)	Width (cm)	<u>a</u> (mm)
Nakano's Helix	≤2.0	1.14	13.44	662-757	19.8	0.4	<u>0.015</u> ,
<u>Monopole</u>	≤2.0	1.05	5.78	957-1014			0.003
Cage monopole	≤2.0	3.7	139	212-775	25.5	7.6	0.814

Table 5

Conclusions from the above numerical results include recognition that cage structures can be optimizes for lower VSWR, parasites of optimum size and placement improve VSWR of driven antenna, helical elements reduce height at sacrifice of bandwidth, and wire radius is an important parameter.

The following is a detailed description (including documentary references, a list for which is provided after the detailed description) of an exemplary efficient curved-wire integral equation solution technique as may be practiced in accordance with the subject invention.

AN EFFICIENT CURVED-WIRE INTEGRAL EQUATION SOLUTION TECHNIQUE:

Shawn D. Rogers and Chalmers M. Butler

Department of Electrical and Computer Engineering, P.O. Box 340915, Clemson
University

Clemson, SC 29634-0915

ABSTRACT

5

10

15

20

25

30

Computation of currents on curved wires by integral equation methods is often inefficient when the structure is tortuous but the length of wire is not large relative to wavelength at the frequency of operation. The number of terms needed in an accurate piecewise straight model of a highly curved wire can be large yet, if the total length of wire is small relative to wavelength, the current can be accurately represented by a simple linear function. In embodiments of the present invention, a new solution method for the curved-wire integral equation is introduced. It is amenable to uncoupling of the number of segments required to accurately model the wire structure from the number of basis functions needed to represent the current. This feature lends itself to high efficiency. The principles set forth can be used to improve the efficiency of most solution techniques applied to the curved-wire integral equation. New composite basis and testing functions are defined and constructed as linear combinations of other commonly used basis and testing functions. We show how the composite basis and testing functions can lead to a reduced-rank matrix which can be computed via a transformation of a system matrix created from traditional basis and testing functions. Supporting data demonstrate the accuracy of the technique and its effectiveness in decreasing matrix rank and solution time for curved-wire structures.

I. INTRODUCTION:

5

10

15

20

25

30

Numerical techniques for solving curved-wire integral equations [1] may involve large matrices, often due primarily to the resources needed to model the structure geometry rather than due to the number of basis functions needed to represent the unknown current. This is obviously true when a subdomain model is used to approximate a curvilinear structure in which the total wire length is small compared to the wavelength at the frequency of operation. Usually the number of segments needed in such a model is dictated by the structure curvature rather than by the number of weighted basis functions needed in the solution method to represent the unknown current. There is a demand for a general solution technique in which the number of unknowns needed to accurately represent the current is unrelated to the number of straight segments required to model (approximately) the meandering contour of the wire and the vector direction of the current. In recent years attention in the literature has been given to improving the numerical efficiency of integral equation methods for curved-wire structures [2]-[13]. For the most part, presently available techniques incorporate basis functions defined on circular or curved wire segments. The authors of [2] define basis and testing functions along piecewise quadratic wire segments and achieve good results with fewer unknowns than would be needed in a piecewise straight model of a wire loop and of an Archimedian spiral antenna. Others introduce solution techniques for structures comprising circular segments that numerically model the current specifically on circular loop antennas [3], [4]. An analysis of general wire loops is presented in [5], where a Galerkin technique is employed over a parametric representation of a superquadric curve. In [6] aArcs of constant radii are employed to define the geometry of arbitrarily shaped antennas from which is developed a technique for analyzing helical antennas. Other methods which utilize curved segments for subdomain basis and testing functions are available [7]-[10].

There are several advantages inherent in techniques in which basis and testing functions are defined over curved wire segments. Geometry modeling error can be made small and solution efficiency can be increased since to "fit" some structural geometries fewer curved segments are needed than is feasible with straight segments. Although these techniques are successful, they suffer disadvantages as well. First, the integral equation solution technique must be formulated to account for the new curved-segment basis and

testing functions. This means that computer codes must be written to take advantage of the numerical efficiency of these new formulations incorporating the curved elements. A second disadvantage of curvilinear basis function modeling is that they fit one class of curve very well but are not well suited to structures comprising wires of mixed curvature. That is, circles fit loops and helices well but not spirals. Clearly, when a given structure comprises several arcs of different curvatures, the efficiency of methods employing a single curved-segment representation suffers. Elements like the quadratic segment or the arc-of-constant-radius segment increase the complexity of modeling. The third disadvantage of these techniques is that, for many structures, they do not lead to complete uncoupling of the number of the unknown current coefficients from the number of segments needed to model the structure geometry. For example, several quadratic segments or arcs, with one weighted unknown defined on each, would be required to model the geometry of one turn of a multiturn helix, yet the current itself may be represented accurately in many cases by a simple linear function over several turns.

In this paperdescription, an efficient method for solving for currents induced on curved-wire structures is presented. The solution method is based on modeling the curved wire by piecewise-straight segments but the underlying principles are general and can be exploited in conjunction with solution procedures which depend upon other geometry representations, including those that use arcs or curves. It is ideal for multi-curvature wire structures [12], [13]. The improved solution technique depends upon new basis and testing functions which are defined over more than two contiguous straight-wire segments. Composite basis functions are created as sums of weighted piecewise linear functions on wire segments, and composite testing functions compatible with the new basis functions are developed. The new technique allows one to reduce the rank of the traditional impedance matrix. We show how the matrix elements for a reduced-rank matrix can be computed from the matrix elements associated with a traditional integral equation solution method. Of paramount importance is the fact that the number of elements employed to model the geometric features of the structure is unrelated to the number of unknowns needed to accurately represent the wire current.

The concept of creating a new basis function as a linear combination of other basis functions is used in [14] for a multilevel iterative solution procedure for integral equations. Perhaps the composite basis function defined herein can be thought of as a "coarse level" basis function in multilevel terminology, although the method described in this specification is not related to the so-called multilevel or multigrid theory of [14]-[16].

The improved solution technique requires fewer unknowns than the traditional solution to represent the current on an Archimedian spiral antenna. Results comparable to those presented in [2] are achieved for the spiral. The improved technique also allows one to significantly reduce the number of unknowns required to solve for the current on wire helices. Specifically, the results of a convergence test show that the current on a helix can be modeled accurately with the same number of unknowns needed for a "similar" straight wire even though the helix has a large number of turns.

H.—INTEGRAL EQUATION FOR GENERAL CURVED WIRES:

5

10

15

20

25

In this section we present the integro-differential equation governing the electric current on a general three-dimensional curved or bent wire. Examples are the wire loop, the helix, and the meander line shown respectively in FIGS. 11A, 11B and 11C. The wire is assumed to be a perfect electrical conductor and to be thin which means that the radius is much smaller than the wavelength and the length of wire. Under these thin-wire conditions the current is taken to be axially directed, circumferentially invariant, and zero at free ends. The equation governing the total axial current $I(s)\hat{s}$ on the thin curved wire is

$$-j\frac{\eta}{4\pi k} \left\{ k^2 \int_C I(s') \hat{\mathbf{s}}' \cdot \hat{\mathbf{s}} K(s,s') ds' + \frac{d}{ds} \int_C \frac{d}{ds'} I(s') K(s,s') ds' \right\} = -\mathbf{E}'(s) \cdot \hat{\mathbf{s}}, s \in C \quad (1)$$

in which C is the wire axis contour, s denotes the arc displacement along C from a reference to a point on the wire axis, and $\hat{\mathbf{s}}$ is the unit vector tangent to C at this point. The positive sense of this vector is in the direction of increasing s. K(s,s') is the kernel or Green's function,

$$K(s,s') = \frac{1}{2\pi} \int_{-R}^{\pi} \frac{e^{-jkR}}{R} d\phi', \qquad (2)$$

in which R is the distance between the source and observation points on the wire surface, and E'(s) is the incident electric field which illuminates the wire, evaluated in (1) on the wire surface at arc displacement s. Geometric parameters for an arbitrary curved wire are depicted in FIG. 12.

III.—TRADITIONAL SOLUTION TECHNIQUE:

The new solution method proposed in this specification can be viewed as an improvement to present methods. In fact, employing the ideas set forth in Section IV, one can modify an existing subdomain solution method to render it more efficient for solving the curved-wire integral equation. Hence, the new method is explained in this specification as an enhancement of a method that has proved useful for a number of years. The method selected for this purpose is based on modeling the curved wire as an ensemble of straight-wire segments, with the unknown current represented as a linear combination of triangle basis functions and testing done with pulses. In this section this method is outlined as a basis for the explanation of the new method in Section IV.

The first step in modeling a curved wire is to select points on the wire axis and define vectors \mathbf{r}_0 , \mathbf{r}_1 ,..., \mathbf{r}_p from a reference origin to the selected points. The curved wire is modeled approximately as an ensemble of contiguous straight-wire segments joining these points (cf. Fig. 3FIG. 13). The arc displacement along the axis of the piecewise linear approximation of C is measured from the reference point labeled \mathbf{r}_0 . The arc displacement between \mathbf{r}_0 and the n^{th} point located by \mathbf{r}_n is l_n . A general point on the piecewise-straight approximation of the wire axis is located alternatively by means of the vector \mathbf{r} and by the arc displacement l from the reference to the point. Various geometrical parameters describing the wire can be expressed in terms of the vectors locating the points on the wire axis. The unit vectors along the directions of the segments adjacent to the point \mathbf{r}_p shown in Fig. 4FIG. 14 are given by

$$\hat{\mathbf{l}}_{p-} = \frac{\mathbf{r}_p - \mathbf{r}_{p-1}}{\Delta_{p-}} \tag{3}$$

$$\hat{\mathbf{l}}_{p+} = \frac{\mathbf{r}_{p+1} - \mathbf{r}_p}{\Delta_{p+}} \tag{4}$$

where

5

10

15

20

25

$$\Delta_{p-} = \left| \mathbf{r}_p - \dot{\mathbf{r}}_{p-1} \right| \tag{5}$$

$$\Delta_{p+} = \left| \mathbf{r}_{p+1} - \mathbf{r}_{p} \right|. \tag{6}$$

The midpoint of the straight-wire segment joining \mathbf{r}_p and $\mathbf{r}_{p\pm 1}$ is located by

$$\mathbf{r}_{p\pm} = \frac{1}{2} \left[\mathbf{r}_{p} + \mathbf{r}_{p\pm 1} \right]. \tag{7}$$

In order to emphasize the fact that the model is now a straight wire segmentation of the original curved wire, s in (1) is replaced by l, the arc displacement along the axis of the straight wire model. With this notation and subject to the piecewise straight wire approximation, Eq. (1) becomes

$$-j\frac{\eta}{4\pi k}\left\{k^2\int_{L}I(l')\hat{\mathbf{l}}'\cdot\hat{\mathbf{l}}K(l,l')dl' + \frac{d}{dl}\int_{L}\frac{d}{dl'}I(l')K(l,l')dl'\right\} = -\mathbf{E}^{i}(l)\cdot\hat{\mathbf{l}}, l\in L \quad (8)$$

where L is the piecewise straight approximation to C.

5

10

15

20

In a numerical solution of the integral equation for a curved wire structure, the (vector) current is expanded in a linear combination of weighted basis functions defined along the straight-wire segments. Even though they can be any of a number of functions, those employed here, for the purpose of illustration in this specification, are chosen to be triangle functions with support over two adjacent segments. Thus the current may be approximated by

$$I(l)\hat{\mathbf{l}}(l) \approx \sum_{n=1}^{N} I_{n} \Lambda_{n}(l) \hat{\mathbf{l}}_{n}(l)$$
(9)

in which the triangle function Λ_n about the n^{th} point on the segmented wire, as depicted in Fig. 5FIG. 15, is defined by

$$\Lambda_{n}(l) = \begin{cases}
\frac{l - l_{n-1}}{\Delta_{n}}, l \in (l_{n-1}, l_{n}) \\
\frac{l_{n+1} - l}{\Delta_{n}}, l \in (l_{n}, l_{n+1})
\end{cases}$$
(10)

where the unit vector $\hat{\mathbf{l}}_n$ is defined in terms of the unit vectors associated with the segments adjacent to the n^{th} point:

$$\hat{\mathbf{l}}_{n} = \begin{cases} \hat{\mathbf{l}}_{n-}, l \in (l_{n-1}, l_{n}) \\ \hat{\mathbf{l}}_{n+}, l \in (l_{n}, l_{n+1}) \end{cases}$$
 (11)

N is the number of basis functions and unknown current coefficients I_n in the finite series approximation (9) of the current. N unknowns are employed to represent the current on a wire having two free endpoints and modeled by N+1 straight-wire segments. In this traditional solution technique described here, N must be large enough to accurately model the geometric structure and vector direction of the current, even if a large number of unknowns is not required to approximate the current I(l) to the accuracy desired. The triangle basis functions overlap as suggested in Fig. 6FIG. 16 so an approximation with N terms incorporates, at most, N+1 vector directions of current on the wire. These point-by-point directions of current on a curved wire must be accounted for accurately by the N+1 unit vectors, yet N piecewise linear basis functions may be far more than may be needed to accurately represent the current I(l).

Testing the integro-differential equation is accomplished by taking the inner product of (8) with the testing function

$$\Pi_{m}(l) = \begin{cases}
1, & l \in (l_{m-}, l_{m+}) \\
0, & \text{otherwise}
\end{cases}$$
(12)

depicted in Fig. 7FIG. 17 for m = 1, 2, ..., N. The inner product of this testing pulse with a function of the variable l is defined by

$$\left\langle f, \Pi_{m} \right\rangle = \int_{m}^{m+} f(l) dl$$
 (13)

Expanding the unknown current I with (9) and taking the inner product of (8) with (12) for m = 1, 2, ..., N yield a system of equations written in matrix form as

$$[Z_{mn}][I_n] = [V_m] \tag{14}$$

where

5

10

15

$$Z_{mn} = -j \frac{\eta}{4\pi k} \left\{ \frac{k^{2}}{2} \left[(\Delta_{m-} \hat{\mathbf{I}}_{m-} \cdot \hat{\mathbf{I}}_{n-} + \Delta_{m+} \hat{\mathbf{I}}_{m+} \cdot \hat{\mathbf{I}}_{n-}) \int_{n-1}^{l_{n}} \Lambda_{n}(l') K(R_{m}) dl' + (\Delta_{m-} \hat{\mathbf{I}}_{m-} \cdot \hat{\mathbf{I}}_{n+} + \Delta_{m+} \hat{\mathbf{I}}_{m+} \cdot \hat{\mathbf{I}}_{n+}) \int_{n}^{l_{n+1}} \Lambda_{n}(l') K(R_{m}) dl' \right] + \frac{1}{\Delta_{n-}} \int_{n-1}^{n} K(R_{m+}) dl' - \frac{1}{\Delta_{n+}} \int_{n}^{n} K(R_{m-}) dl' + \frac{1}{\Delta_{n+}} \int_{n}^{n+1} K(R_{m-}) dl' \right\}$$

$$(15)$$

is an element of the $N \times N$ impedance matrix with

$$R_{m} = \begin{cases} \sqrt{4a^{2} \sin^{2} \frac{\phi'}{2} + (l_{m} - l')^{2}}, & l_{m} \text{ and } l' \text{ on same segment} \\ \sqrt{|\mathbf{r}_{m} - \mathbf{r'}|^{2} + a^{2}}, & \text{otherwise} \end{cases}$$
(16)

and

5

$$R_{m\pm} = \begin{cases} \sqrt{4a^{2} \sin^{2} \frac{\phi'}{2} + (l_{m\pm} - l')^{2}}, & l_{m\pm} \text{ and } l' \text{ on same segment} \\ \sqrt{|\mathbf{r}_{m\pm} - \mathbf{r}'|^{2} + a^{2}}, & \text{otherwise} \end{cases}$$
(17)

When the source $(\mathbf{r}' \text{ or } l')$ and observation $(\mathbf{r} \text{ or } l = (l_{m\pm}, l_m))$ points reside on the same straight wire segment of radius a, as in Fig. 8FIG. 18 the exact kernel given by

$$K(l,l') = \frac{1}{2\pi} \int_{-\pi}^{\pi} \frac{e^{-jkR}}{R} d\phi'$$
 (18)

is used. Otherwise for source and observation points on different straight-wire segments (cf. Fig. 9FIG. 19), the exact kernel is approximated by the so-called reduced kernel,

$$K(l,l') = \frac{e^{-jkR}}{R} . \tag{19}$$

The approximation below, which is excellent when the segment lengths are small compared with the wavelength, is employed in arriving at the first two terms of (15):

$$\langle \hat{\mathbf{l}}(l) \cdot \mathbf{f}(l), \mathbf{\Pi}_{m}(l) \rangle \approx \mathbf{f}(l_{m}) \cdot \left[\frac{1}{2} \Delta_{m-} \hat{\mathbf{l}}_{m-} + \frac{1}{2} \Delta_{m+} \hat{\mathbf{l}}_{m+} \right].$$
 (20)

The same approximation can be used to compute the elements of the excitation column vector,

$$V_{m} = \left\langle -\mathbf{E}^{i}(l) \cdot \hat{\mathbf{l}}, \mathbf{\Pi}_{m} \right\rangle \approx -\mathbf{E}^{i}(l_{m}) \cdot \left[\frac{1}{2} \Delta_{m-1} \hat{\mathbf{l}}_{m-1} + \frac{1}{2} \Delta_{m+1} \hat{\mathbf{l}}_{m+1} \right], \tag{21}$$

where $\mathbf{E}^{i}(l_{m})$ is the known incident electric field at point l_{m} on the wire. Of course, if desired the left hand side of (21) can be evaluated numerically in those situations in which the incident field varies appreciably over a subdomain. We also point out that testing with pulses allows one to integrate directly the second term on the left side of (8). The derivative of the piecewise linear current in (8) leads to a pulse doublet (for charge) over two adjacent straight wire segments. These operations on the second term in the left side of (8) lead to the last four integrals in (15).

IV. IMPROVED SOLUTION TECHNIQUE

5

10

15

20

25

In this section a new technique for solving the curved-wire integral equation is presented. It is very efficient for tortuous wires on which the actual variation of the current is modest, a situation which often occurs when the length of wire in a given curve is small relative to wavelength, regardless of the degree of curvature. Composite basis and testing functions are introduced as an extension of the functions of the traditional solution method outlined in Section III. The composite basis function serves to uncouple the number of straight segments needed to model the curved-wire geometry and the vector direction of the current from the number of unknowns needed to accurately represent the current on the wire. This new basis function is a linear combination of appropriately weighted generic basis functions, e.g., basis functions (9) in the traditional method outlined in Section III, and is defined over a number of contiguous straight segments. This new basis function is referred to as a composite basis function since it is constructed from others. Even though the solution method can incorporate any number of different generic basis and testing functions, the piecewise linear or triangle basis function and the pulse testing function are adopted here to facilitate explanation. Also, this pair leads to a very efficient and practicable solution scheme.

The notion of a composite triangle made up of constituent triangles is suggested in Fig. 10FIG. 20. For simplicity in illustration, the composite triangle is shown over a straight line though in practice it would be over a polygonal line comprising straight-line segments, which approximate the curved wire axis. The q^{th} composite vector triangle function can be constructed as

$$\widetilde{\Lambda}_{q}(l)\hat{\mathbf{l}}_{q} = \sum_{i=1}^{N^{q}} h_{i}^{q} \Lambda_{i}^{q}(l)\hat{\mathbf{l}}_{i}^{q}$$
(22)

in which Λ_i^q is the i^{th} constituent triangle defined by

5

10

15

$$\Lambda_{i}^{q}(l)\hat{\mathbf{l}}_{i}^{q} = \begin{cases}
\frac{l - l_{i}^{q}}{\Delta_{i-}^{q}} \hat{\mathbf{l}}_{i}^{q}, & l \in (l_{i-1}^{q}, l_{i}^{q}) \\
\frac{l_{i}^{q} - l}{\Delta_{i+}^{q}} \hat{\mathbf{l}}_{i+}^{q}, & l \in (l_{i}^{q}, l_{i+1}^{q})
\end{cases}$$
(23)

and illustrated in Fig. 11FIG. 21. When q is used as a superscript it identifies a parameter related to the q^{th} composite triangle function. The constitutive elements of the q^{th} composite basis function are denoted by the subscript i. The parameter h_i^q is the weight or magnitude of the i^{th} constituent triangle within $\tilde{\Lambda}_q$. These weights are functions of the segment lengths within each composite basis function and are adjusted so that the ordinate to the composite triangle is a linear function of displacement along the polygonal line which forms the base of the composite triangle. For example, for five constituent triangles in the q^{th} composite triangle of Fig. 10FIG. 20, the weights h_1^q and h_2^q are

$$h_1^q = \frac{\Delta_1^q}{\Delta_1^q + \Delta_2^q + \Delta_3^q}$$
 (24)

$$h_{2}^{q} = \frac{\Delta_{1}^{q} + \Delta_{2}^{q}}{\Delta_{1}^{q} + \Delta_{2}^{q} + \Delta_{3}^{q}}.$$
 (25)

The other weights are computed in a similar fashion. The parameter N^q is the number of triangle functions Λ^q_i employed to represent $\widetilde{\Lambda}_q$. The example composite basis function of Fig. 10FIG. 20 is illustrated as the sum of five identical constituent triangles, but, of course, the constituents need not be the same if convenience or efficiency dictates otherwise. Also, this composite basis function is illustrated without the vector directions associated with each subdomain. In general the individual straight-wire segments over which a composite basis function is defined may each have a different vector direction. Finally, the current expanded with a reduced number of unknowns \widetilde{N} is

5

10

15

20

$$I(l)\hat{\mathbf{l}}(l) = \sum_{q=1}^{\tilde{N}} \tilde{I}_{q} \tilde{\Lambda}_{q}(l)\hat{\mathbf{l}}_{q}(l)$$
(26)

where $\tilde{\Lambda}_q(l)\hat{\mathbf{l}}_q(l)$ is the q^{th} vector composite basis function defined earlier in (22) and \tilde{I}_q is its unknown current coefficient. It is worth noting that constituent triangles are employed above to construct composite triangles but, if desired, they could be used to construct other basis functions, e.g., an approximate, composite piecewise sinusoidal function.

If the number of unknowns in a solution procedure is reduced, then, of course, the number of equations must be reduced too which means that the testing procedure must be modified to achieve fewer equations. This is easily accomplished by defining composite testing pulses, compatible with the composite basis functions, as a linear combination of appropriately weighted constituent pulses. An example composite test pulse is depicted in Fig. 12FIG. 22. Such a p^{th} composite testing pulse is defined by

$$\widetilde{\Pi}_{p}(l) = \sum_{k=1}^{N^{p}} u_{k}^{p} \Pi_{k}^{p}(l)$$
(27)

where the constituent pulses associated with this p^{th} pulse are

$$\Pi_{k}(l) = \begin{cases}
1, & l \in (l_{k-}^{p}, l_{k+}^{p}) \\
0, & \text{otherwise}
\end{cases}$$
(28)

and shown in Fig. 13FIG. 23. If with every constituent triangle there were associated a corresponding constituent pulse, then the testing functions $\widetilde{\Pi}_p$ would overlap, which is not desired and can be avoided by selecting the weight u_k^p to be 0 or 1 depending upon whether or not the k^{th} constituent pulse in $\widetilde{\Pi}_p$ is to be retained. To this end, the inner product of (13) is modified in the composite testing procedure to become

$$\left\langle f, \widetilde{\mathbf{\Pi}}_{p} \right\rangle = \sum_{k=1}^{N^{p}} u_{k}^{p} \int_{p}^{p} f(l) dl. \qquad (29)$$

Now that we have described the new basis and testing functions, we substitute the current expansion of (26) into (8) and form the inner product (29) of the resulting expression with $\widetilde{\Pi}_p$ for $p = 1, 2, ..., \widetilde{N}$. This yields the following matrix equation having a reduced number (\widetilde{N}) of unknowns and equations:

$$[\widetilde{Z}_{pq}][\widetilde{I}_{q}] = [\widetilde{V}_{p}] \tag{30}$$

where

5

10

15

$$\widetilde{Z}_{pq} = \sum_{k=1}^{N^{p}} u_{k}^{p} \sum_{i=1}^{N^{q}} h_{i}^{q} - j \frac{\eta}{4\pi k} \left[\frac{k^{2}}{2} \left\{ \left(\Delta_{k-}^{p} \hat{\mathbf{l}}_{k-}^{p} \cdot \hat{\mathbf{l}}_{i-}^{q} + \Delta_{k+}^{p} \hat{\mathbf{l}}_{k-}^{p} \cdot \hat{\mathbf{l}}_{i-}^{q} \right) \int_{i-1}^{q} \Lambda_{i}^{q} (l') K(R_{k}^{p}) dl' + \left(\Delta_{k-}^{p} \hat{\mathbf{l}}_{i+}^{p} \cdot \hat{\mathbf{l}}_{i+}^{q} + \Delta_{k+}^{p} \hat{\mathbf{l}}_{i+}^{p} \right) \int_{i}^{q} \Lambda_{i}^{q} (l') K(R_{k}^{p}) dl' + \left(\Delta_{k-}^{p} \hat{\mathbf{l}}_{i-}^{p} \cdot \hat{\mathbf{l}}_{i+}^{q} + \Delta_{k+}^{p} \hat{\mathbf{l}}_{i+}^{p} \right) \int_{i}^{q} \Lambda_{i}^{q} (l') K(R_{k}^{p}) dl' + \left(\Delta_{k-}^{p} \hat{\mathbf{l}}_{i-}^{q} \cdot K(R_{k+}^{p}) dl' - \frac{1}{\Delta_{i-}^{q}} \int_{i-1}^{q} K(R_{k-}^{p}) dl' + \left(\Delta_{i-}^{p} \hat{\mathbf{l}}_{i-}^{q} \cdot K(R_{k-}^{p}) dl' - \Delta_{i+}^{q} \cdot K(R_{k-}^{p}) dl' - \Delta_{i-}^{q} \cdot K(R_{k-}^{p}) dl' \right) \right\}$$

$$+ \frac{1}{\Delta_{i+}^{q}} \int_{i}^{q} K(R_{k-}^{p}) dl' + \left(\Delta_{i+}^{p} \hat{\mathbf{l}}_{i+}^{q} \cdot K(R_{k-}^{p}) dl' - \Delta_{i+}^{q} \cdot K(R_{k-}^{p}) dl' - \Delta_{i-}^{q} \cdot K(R_{k-}^{p}) dl' \right) \right\}$$

$$+ \frac{1}{\Delta_{i+}^{q}} \int_{i}^{q} K(R_{k-}^{p}) dl' + \Delta_{i+}^{p} \cdot K(R_{k-}^{p}) dl' + \Delta_{i+}^{q} \cdot K(R_{k-}^{p}) dl' + \Delta$$

represents an element of the reduced-rank $(\widetilde{N} \times \widetilde{N})$ impedance matrix. At this point the reader is cautioned to distinguish between the index k which only appears in (31) as a

subscript and the wave number $k = \omega \sqrt{\mu \varepsilon}$. The distances $R_{k\pm}^{\ p}$ and $R_k^{\ p}$ are given in (16) or (17) with m replaced by index k, and the forcing function is given by

$$\widetilde{V}_{p} = -\sum_{k=1}^{N_{p}} u_{k}^{p} \int_{k}^{p} \mathbf{E}^{i} (l_{k}^{p}) \cdot \hat{\mathbf{l}}(l) dl.$$

One could compute the terms within the reduced-rank impedance matrix directly from (31). However, this would require more computation time than needed to fill the original impedance matrix of (14) since some constituent triangles within adjacent composite basis functions have the same support (Fig. 14FIG. 24). The constituent triangles within the overlapping portions of two adjacent composite basis functions differ only in the weight h_i^q . Therefore (31) incorporates redundancies which should be avoided. Also, a study of (15) and (31) reveals that the term within the braces of (31) is identical to Z_{mn} of (15) if subscript i is replaced by n, subscript k by m, and the superscripts p and q are suppressed. Hence, the elements \widetilde{Z}_{pq} of the reduced-rank matrix can be computed from the elements Z_{mn} of the original matrix by means of the transformation

5

10

$$\widetilde{Z}_{pq} = \sum_{k=1}^{N^p} u_k^p \sum_{i=1}^{N^q} h_i^q Z_{ki}^{pq}$$
(32)

where Z_{ki}^{pq} is a term in the original impedance matrix Z_{mn} of (15). The key to selecting appropriate Z_{mn} term is the combination of indices p, q, k, and i. The index p (q) indicates a group of rows (columns) in $\left[Z_{mn}\right]$ which are ultimately combined by the transformation in (32) to form the new matrix. The appropriate matrix element Z_{ki}^{pq} in $\left[Z_{mn}\right]$ is determined by intersecting the k^{th} row within the set of rows identified by index p with the i^{th} column of the group of columns specified by index q. Of course the groupings of rows and columns are determined when one defines the composite basis and testing functions.

A transformation for computing the reduced-rank matrix $[\widetilde{Z}_{pq}]$ from the traditional matrix $[Z_{mn}]$ which is more efficient than is the construction of the matrix from (31) can be developed. The key to this transformation is (32). First, two auxiliary matrices $[L_{pm}]$ and $[R_{nq}]$ are constructed and, then, the desired transformation is

5 expressed as

$$[\widetilde{Z}_{pq}] = [L_{pm}][Z_{mn}][R_{nq}]$$
 (33)

where

and

 $[R_{nq}] = \begin{bmatrix} h_1^1 & & & & & & & & \\ h_2^1 & & & & & & & \\ \vdots & h_1^2 & & & & & & \\ h_{N^1}^1 & h_2^2 & & & & & \\ & \vdots & h_1^3 & & & & \\ & & \vdots & & & & \\ & h_{N^3}^3 & & & & \\ & & & \vdots & & & \\ & & & h_{N^3}^q & & & \\ & & & & h_{N^q}^q & & \\ & & & & & h_{N^q}^{\tilde{q}} & \\ & & & & & h_{N^q}^{\tilde{q}} & \\ & & & & & h_{N^q}^{\tilde{N}} & \\ & & & & & h_{N^q}^{\tilde{N}} & \\ & & & & & h_{N^q}^{\tilde{N}} & \\ \vdots & & & & & \vdots & \\ 0 & \cdots & & & & h_{N^N}^{\tilde{N}} & \\ \end{bmatrix}$ (35)

It is easy to show that the above matrix transformation is equivalent to (32).

An alternative development of the transformation, which renders the meaning and construction of the matrices $[L_{pm}]$ and $[R_{nq}]$ more transparent is presented. We begin with the traditional $N \times N$ system matrix equation,

$$[Z_{mn}][I_n] = [V_m],$$
 (36)

which is to be transformed to the $\widetilde{N} \times \widetilde{N}$ reduced-rank matrix equation

5

$$[\widetilde{Z}_{pq}][\widetilde{I}_{q}] = [\widetilde{V}_{p}]. \tag{37}$$

The number of unknown current coefficients in the original system of equations (36) is reduced by expressing the \widetilde{N} coefficients \widetilde{I}_q as linear combinations of the N coefficients

 $I_n(\widetilde{N} < N)$. The \widetilde{I}_q are constructed from the I_n by means of a scheme which accounts for the representation of the composite basis functions in terms of the original triangles on the structure. The resulting relationships among the original and the composite coefficients are expressed as

$$[I_n] = [R_{na}][\widetilde{I}_a] \tag{38}$$

where $[R_{nq}]$ embodies weights of the constituent triangles needed to synthesize composite basis function triangles. The matrix $[R_{nq}]$ directly combines unknown current coefficients consistent with the composite basis functions to result in a reduced number of unknowns. The construction is simple. If the triangle n from the original basis functions is to be used in the q^{th} composite basis function, the appropriate weight of this triangle is placed in row n and column q of $[R_{nq}]$. Otherwise zero is placed in this position. Again we point out that a given triangle may appear in more than one composite basis function. After substituting (38) into (36) we arrive at a modified system of linear equations

$$[Z_{mn}][R_{na}][\widetilde{I}_{a}] = [V_{m}] \tag{39}$$

which has a reduced number (\widetilde{N}) of unknowns but the original number (N) of equations. To reduce the number of equations to \widetilde{N} , tested linear equations are selectively added, which is accomplished by pre-multiplying (39) by $[L_{pm}]$ to arrive at

$$[L_{pm}][Z_{mn}][R_{na}][\widetilde{I}_{a}] = [L_{pm}][V_{m}]. \tag{40}$$

20 The identifications,

$$[\widetilde{Z}_{pq}] = [L_{pm}][Z_{mn}][R_{nq}]$$
 (41)

and

10

15

$$[\widetilde{V}_{p}] = [L_{pm}][V_{m}], \tag{42}$$

in (40) lead to the desired expression (37). The matrix $[L_{pm}]$ effectively creates composite testing functions from the original testing pulses. If the p^{th} composite testing pulse contains the m^{th} testing pulse from the original formulation, a one is placed in row p and column m of $[L_{nm}]$. Otherwise, a zero is placed in this position.

5

10

15

20

25

There are other important considerations in the implementation of this technique. Again, we label the number of basis functions in the traditional formulation N and the number of composite basis functions \widetilde{N} . In the previous section the number of constituent triangles for the q^{th} composite basis function is designated N^q . Here for ease of implementation it is convenient to chose N^q to be the same value for every q, which we designate τ ($N^q = \tau$ for all q). Also, in the present discussion, we restrict τ to be one of the members of the arithmetic progression 5, 9, 13, 17,...,. With τ one of these integers, half-width constituent pulses are not required within the composite testing functions. N must be sufficiently large to ensure accurate modeling of the wire geometry and vector direction of the current as well as to preserve the numerical accuracy of the approximations. In addition, \widetilde{N} must be large enough to accurately represent the variation of the current. A convergence test must be conducted to arrive at acceptable values of N and \widetilde{N} . Also, N, \widetilde{N} and τ must be defined carefully so that a value of τ in the arithmetic progression will allow an $N \times N$ matrix to be reduced to an $\widetilde{N} \times \widetilde{N}$ matrix. The following formula is useful for determining relationships between N and \widetilde{N} , for a given value of τ , in the case of a general three-dimensional curved wire (without junctions):

$$\widetilde{N} = 2\frac{N+1}{\tau+1} - 1. \tag{43}$$

For a wire structure with a junction, *e.g.*, a circular loop, where overlapping basis functions typically are used in the traditional formulation to satisfy Kirchhoff's current law, (43) becomes

$$\widetilde{N} = \frac{2N}{\tau + 1} \,. \tag{44}$$

Once N, \widetilde{N} and τ are determined, it is easy to write a routine which determines the original basis and testing functions to be included in the composite functions. This information is then stored in the matrices $[L_{pm}]$ and $[R_{nq}]$.

In the above, composite triangle expansion functions are synthesized from generic triangle functions but one could as well, if desired, approximate other composite expansion functions, e.g., "sine triangles" by adjustment of the coefficients h_i^q . Similarly, other approximate testing functions could be created by adjustment of the factors u_k^p . Thus, a reduced-rank solution method with composite expansion and testing functions different from triangles and pulses could be readily created from the techniques discussed in this section. Only h_i^q and u_k^p , peculiar to the functions selected in the method to be implemented, must be changed in (32) in order to arrive at the appropriate reduced-rank matrix elements \widetilde{Z}_{pq} . If $[L_{pm}]$ of (34) were replaced by $[R_{nq}]^T$ in (33) where $[R_{nq}]$ is defined in (35) and T denotes transpose, then the resulting reduced-rank matrix $[\widetilde{Z}_{pq}]$ would be that for a method which employs composite triangle expansion and (approximate) composite triangle testing functions.

V. RESULTS

5

10

15

20

25

Results obtained by solving the integral equation of (15) with the improved solution method developed above are presented in this section as are values of current determined by the traditional method. In some cases data obtained from the literature are displayed for comparison. Results are presented for the wire loop, an Archimedian spiral antenna, and several different helical antennas and scatterers. Current values on a small wire loop antenna are depicted in Fig. 15FIG. 25. The loop is modeled by 32 linear segments (and 32 unknowns) in the traditional solution technique. Also shown are values obtained from the new solution method with eight composite basis functions (eight unknowns) each having five constituent triangles constructed on twenty four linear

segments. These current values compare well with those from the traditional solution and with data from [2] where the loop is modeled with eight unknowns on quadratic segments. There is slight disagreement at the driving point which is to be expected (with eight unknowns) near a delta gap source where the current varies markedly. To investigate this discrepancy we use three triangle basis functions in the vicinity of the delta-gap source and do not form composite triangles in this region. The results are shown in Fig. 16FIG. 26. Here the loop problem has been solved with 28 unknowns for the traditional method and twelve unknowns for the composite basis function solution. It is seen that the agreement is excellent even in the vicinity of the delta-gap source.

5

10

15

20

25

30

The improved solution method is applied to a four arm Archimedian spiral antenna. This antenna is chosen since it is used in [2] to illustrate the usefulness of the quadratic subdomains for wires having significant curvature. A description of the geometry of Archimedian spiral antennas is found in [17] and [18]. The antenna is excited by a delta gap source on each arm located near the junction of the four arms. The results presented in this section are for mode 2 excitation [19]. The antenna is also modeled by the traditional technique with 725 unknowns on each arm (725*4+3=2903). In [17] certain literature the authors implement a discrete body of revolution technique so that the number of unknowns needed for one arm is sufficient for solving the problem. Since our goal is to employ the such data of [17] to demonstrate the accuracy of our method and not to create the best analytical tool for the Archimedian spiral antenna, we solve this problem by including the same number of linear segments on each arm and placing overlapping triangles at the wire junction to enforce Kirchhoff's current law. In 12 iIt is found that each arm requires 504 linear segments to obtain an accurate solution. They also obtain accurate values of the current with 242 quadratic segments. We reproduce these results with our improved solution method as illustrated in Figs. 17-19FIGS. 27-29, respectively. The number of unknowns for each arm is 725 for the traditional technique and 241 for the improved method. In each composite basis function there are five constituent triangles. In Fig. 17FIG. 27 the difference in the solution of the current for the two methods is seen to be negligible. Good agreement is also achieved for the current magnitude (cf. Fig. 18FIG. 28). A favorable comparison with data from [2] is observed in Fig. 19FIG. 29. Since the symmetry in the geometry is not used to further

reduce the number of unknowns required for the structure, the actual number of unknowns in the impedance matrices are 2903 and 967, respectively. The computation times for the various routines of the FORTRAN 90 code are presented in <u>Table 6</u> the table below. All times are for runs on a 375 MHz DEC Alpha processor. The time study shows that the reduction technique is successful in significantly reducing matrix solve time for this four-arm Archimedian spiral antenna.

5

10

15

20

25

A standard linear equation solution method is employed to solve both sets of linear equations since the objective of this comparison is to delineate the enhanced efficiency of the reduced-rank method.

TABLE [[1]]6

COMPUTATION TIMES FOR ARCHIMEDIAN SPIRAL

Event	Time in Seconds
Fill matrix N=2903	1020
Solve matrix equation N=2903	1329
Reduce matrix from 2903 to 967	5.54
Solve reduced matrix equation N=967	45.81
Traditional method total time	2349
Improved method total time	1071

Consider next a ten-turn helix having a total wire length of 0.5λ and illuminated by a plane wave. The geometry of the helical scatterer is depicted in Fig. 20FIG. 30. The current shown in Fig. 21FIG. 31 is "converged" when the number of unknowns in the traditional solution technique reaches 259. Thus one concludes that 260 linear segments are required to accurately represent the geometry of this structure and vector nature of the current. We determine convergence by examining the real and imaginary parts of the current along the structure. When changes in the current are sufficiently small as the number of segments is increased, convergence is assumed [2]. The results of a convergence test show that an accurate solution of the current can be achieved with 51 composite basis functions. The number of constituent triangles in each basis function in this case is nine. We note that the solution with 27 composite basis functions differs only slightly from the converged solution.

The current is shown in Fig. 22FIG. 32 for another helical scatterer of geometry similar to that described above and subject to the same excitation and geometry similar to

that described above. The circumference of each turn of this ten-turn helix is 0.035λ making the total wire length 0.35λ . These results are given as an example to illustrate that the composite basis function scheme works well with curved-wire structures having a wire length which is not an integer multiple of half wavelength.

5

10

15

20

25

The data of Fig. 23 FIG. 33 are for a 50-turn helix having a total wire length of 2λ and illuminated by a plane wave traveling in the positive x direction. One sees that 27 unknowns are adequate to accurately represent the current along the helix. However, 1483 unknowns are required in the traditional solution method since many linear segments are required to define the 50-turn structure and the vector properties of the current. In this example there are 105 constituent triangles in each composite basis function. The table Table 7 below shows the computational savings enjoyed by the method of this invention.

TABLE [[II]]7 COMPUTATION TIMES FOR FIFTY-TURN

HELIX

Event	Time in Seconds
Fill matrix N=1483	300
Solve matrix equation N=1483	267
Reduce matrix rank from 1483 to 27	1.84
Solve reduced matrix equation N=27	Negligible
Traditional method total time	567
Improved method total time	302

Next we illustrate the prowess of the solution technique for helical antennas. Specifically the data presented in Fig. 24FIG. 34 and Fig. 25FIG. 35 are for helical antennas driven above a ground plane by a delta gap source. The geometry of the helix is given in Fig. 20FIG. 30 and the ground plane is located at z = 0. The data of the improved method compare well with those of the traditional solution technique, but, again, there is a slight difference in the currents at the ground plane due to the nature of the delta gap source. In each of these figures the number of unknowns given is the number for the structure plus its image, but data are plotted only for the part of the structure above the ground plane. Since there are many turns, the number of segments needed to represent the geometry of the antenna and its image is large. The number of unknowns is reduced from

N=917 in the traditional method to N=53 in the improved technique. Of course, one could employ image theory to modify the integral equation which could be solved by the new method with an even more dramatic savings in computer resources.

The last example is a five-turn helical antenna over an infinite ground plane, driven by a delta gap source. This structure is included here because it is used in [6] to exhibit the accuracy of a technique employing basis and testing functions defined over arcs of constant radii. It is modeled by straight wire segments in [20]. In [6] certain literature the authors discretize the antenna into fifteen arcs and then compare solutions of 135 unknowns with forty-five unknowns. They find that forty-five unknowns is enough to obtain an accurate solution for the current when the geometry is defined by arcs. We reproduce these results except that the antenna geometry is defined by many straight wire segments. In the method of this invention we include the unknowns on the image (269 unknowns on the antenna plus its image corresponds to 135 unknowns on the antenna above the ground plane). Likewise, 89 unknowns on the antenna and image are equivalent to 45 unknowns on the antenna. We find that helical antennas require a minimum of 25 unknowns per turn in the traditional solution technique in order to represent the geometry. In order to reduce the number of unknowns over the antenna and its image from 269 to 89, each composite basis function is constructed with 5 constituent triangles. A qualitative comparison of our data and that of [6] suggests agreement in the two methods.

VI. CONCLUSIONS

5

10

15

20

25

. 30

The solution method presented in this specification is very simple and practicable for reducing the rank of the impedance matrix for curved-wire structures. It should be mentioned that rank reduction is realized only when the number of segments needed to model the geometry and vector direction of the current exceeds the number of unknown current coefficients necessary to characterize the variation of the current. We define composite basis and testing functions as the sum of constituents over linear segments on a wire and arrive at a new impedance matrix of reduced rank. It is shown how this reduced-rank matrix can be determined from the original impedance matrix by a matrix transformation. Thus one advantage of this technique is that it can be applied to almost

any existing curved-wire codes which define basis and testing functions over straightwire segments or curved-wire segments.

Dramatic savings in matrix solve time are realized for the cases of the four-arm Archimedian spiral antenna and the helical antenna. The benefits for reducing unknowns on, for example, a helical antenna become much more significant as the number of turns increases. It should be pointed out that this method does not reduce matrix fill time since the elements of the original impedance matrix are computed as a step in the determination the elements of the reduced-rank matrix. Problems involving large curved-wire structures can be solved readily by this method, *e.g.*, a straight wire antenna loaded with multiple, tightly wound helical coils and an array of Archimedian spiral antennas. The principles described here can be used in addition to other methods such as those based upon iteration.

VI. REFERENCES

5

10

15

25

40

- [1] R.F. Harrington, Field Computation by Moment Methods. Malabar, FL: Krieger, 1968.
- [2] N.J. Champagne, II, J.T. Williams, and D.R. Wilton, "The use of curved segments for numerically modeling thin wire antennas and scatterers," *IEEE Trans.*Antennas Propagat., vol. 40, pp. 682-689, June 1992.
 - [3] E.K.N. Yung and R.S.K. Wong, "Analysis of an array of circular loops." Annals of Telecommunications, vol. 48, no. 9-10, pp. 491-497, 1993.
 - [4] E.K.N. Yung and R.S.K. Wong, "Analysis of a thin wire circular loop antenna,"

 International Journal of Numerical Modelling: Electronic Networks, Devices

 and Fields, vol. 7, pp. 189-199, 1994.
- 30 [5] M.A. Jensen and Y. Rahmat-Samii, "Electromagnetic characteristics of superquadric wire loop antennas," *IEEE Trans. Antennas Propagat.*, vol. 42, pp. 264-269, February 1997.
- [6] E.K.N. Yung and R.S.K.Wong, "Analysis of a wire antenna of arbitrary shape," *J. Electromagnetic Waves and Applications*, vol. 9, no. 7/8, pp. 855-869, 1995.
 - [7] S.K. Khamas, G.G. Cook, and R.J. Waldron, "Moment-Method analysis of printed circular wire-loop antenna using curved piecewise sinusoidal subdomain basis and test functions," *IEEE Trans. Antennas Propagat.*, vol. 44, pp. 1303-1305, Sept. 1996.

- [8] S.K. Khamas, G.G. Cook, "Moment-Method analysis of printed wire spirals using curved piecewise sinusoidal subdomain basis and test functions," *IEEE Trans. Antennas Propagat.*, vol. 45, pp. 1016-1022, June 1997.
- [9] G.G. Cook and S.K. Khamas, "Efficient moment method for analysing printed wire loop antennas," *IEE Proc. Microw. Antennas Propag.*, vol. 144, no.5, pp.364-366, October 1997.

5

20

35

45

- 10 [10] S.K. Khamas, et. al., "Moment method analysis of printed single arm wire spiral antennas using curved segments," *IEE Proc. Microw. Antennas Propag.*, vol. 144, no. 4., pp. 261-265, August 1997.
- [11] B.M. Kolundzija and B.D. Popovic, "Entire domain Galerkin method for analysis of generalised wire antennas and scatterers," *IEE Proc.-Microw. Antennas Propag.*, vol. 139, no. 1 pp. 17-24, Feb. 1992.
 - [12] S.D. Rogers and C.M. Butler, "Reduced Rank Matrices for Curved Wire Structures," Digest of IEEE APS/URSI Radio Science Meeting, July 1997.
 - [13] S.D. Rogers, "Efficient Numerical Techniques for Curved Wires," M.S.E.E. thesis, Clemson University, Clemson, SC, 1997.
- [14] K. Kalbasi and K.R. Demarest, "A Multilevel Formulation of the Method of Moments," *IEEE Trans. Antennas Propagat.*, vol. 41, pp. 589-599, May 1993.
 - [15] J.H. Bramble, Multigrid Methods. New York: John Wiley and Sons, 1993.
- [16] S.F. McCormick, *Multigrid Methods: Theory, Applications, and Supercomputing*.
 30 New York: Marcel Dekker, 1988.
 - [17] N.J. Champagne, II, "Method of moments formulations for thin wire antennas and scatterers using piecewise linear and curved wire segments," M.S.E.E. thesis, Univ. Houston, Houston, TX, 1991.
 - [18] N.J. Champagne, H. J.T. Williams, R.M. Sharpe, S.U. Hwu, and D.R. Wilton, "Numerical modeling of impedance loaded multi-arm Archimedian spiral antennas," *IEEE Trans. Antennas Propagat.*, vol. 40, pp. 102-108, Jan. 1992.
- 40 [19] H. Nakano, J. Yamauchi, and S. Hashimoto, "Numerical Analysis of 4-Arm Archimedian spiral antenna," *Electron. Lett.*, vol. 19, no. 3, pp. 78-80, 1983.
 - [20] H. Nakano, *Helical and Spiral Antennas*, John Wiley & Sons, Inc, New York, pp. 122-126, 1987.

- [21] H. Nakano, S.R. Kerner, A.G. Alexopoulos, "The moment method solution for printed wire antennas of arbitrary configuration," *IEEE Trans. Antennas Propagat.*, vol. 36, pp.1667-1674, Dec. 1988.
- 5 [22] M. Ali, S.S. Stuchly, and K. Caputa, "Characteristics of bent wire antennas," *J. Electromagnetic Waves and Applications*, vol. 9, no. 9, pp. 1149-1162, 1995.
 - [23] K.K. Mei, "On the Integral Equations of Thin Wire Antennas," *IEEE Trans. Antennas Propagat.*, vol. 13, pp. 374-378, May 1965.

10

15

The following is a detailed description of an An exemplary genetic algorithm that can be used in accordance with the subject invention to obtain optimal antenna parameters for given design criteria is included in the computer program listing appendix provided on compact disc and is incorporated by reference herein.

```
program-gafortran
e
  This is version 1.7a, last updated on 4/2/2001.
e
  Last minor bug found 6/14/00.
e
e
  Copyright David L. Carroll; this code may not be reproduced for sale
æ
  or for use in part of another code for sale without the express
e
  written permission of David L. Carroll.
e
4
C.
  David L. Carroll
e
  CU Aerospace
  2004 South Wright Street Extended
e
  Urbana, IL 61802
  e-mail: carroll@cuaerospace.com
æ
  Phone: 217-333-8274
e
          217-244-7757
  <del>fax:</del>
C
  This genetic algorithm (GA) driver is free for public use. My only
C
  request is that the user reference and/or acknowledge the use of this
   driver in any papers/reports/articles which have results obtained
æ
   from the use of this driver. I would also appreciate a copy of such
   papers/articles/reports, or at least an e-mail message with the
C
   reference so I can get a copy. Thanks.
e
   This program is a FORTRAN version of a genetic algorithm driver.
a
   This code initializes a random sample of individuals with different
   parameters to be optimized using the genetic algorithm approach, i.e.
  evolution via survival of the fittest. The selection scheme used is
  tournament selection with a shuffling technique for choosing random
  pairs for mating. The routine includes binary coding for the
  individuals, jump mutation, creep mutation, and the option for
   single-point or uniform crossover. Niching (sharing) and an option
   for the number of children per pair of parents has been added.
e
   An option to use a micro-GA is also included.
e
   For companies wishing to link this GA driver with an existing code,
C
   I am available for some consulting work. Regardless, I suggest
   altering this code as little as possible to make future updates
   easier to incorporate.
e
   Any users new to the GA world are encouraged to read David Goldberg's
   "Genetic Algorithms in Search, Optimization and Machine Learning,"
e
   Addison-Wesley, -1989.
C
   Other associated files are:
                               ga.inp
e
                               ga.out
e
                               ga.restart
e
                               params.f
\boldsymbol{\mathcal{C}}
                               ReadMe
                               qa2.inp (w/ different namelist identifier)
   I have provided a sample subroutine "func", but ultimately
   the user must supply this subroutine "func" which should be your
e
   cost function. You should be able to run the code with the
   sample subroutine "func" and the provided ga.inp file and obtain
   the optimal function value of 1.0000 at generation 187 with the
```

```
uniform crossover micro-GA enabled (this is 935 function evaluations).
æ
G
  The code is presently set for a maximum population size of 200,
e
  30 chromosomes (binary bits) and 8 parameters. These values can be
e
  changed in params.f as appropriate for your problem. Correspondingly
æ
  you will have to change a few 'write' and 'format' statements if you
  change nchrome and/or nparam. In particular, if you change nchrome
e
  and/or nparam, then you should change the 'format' statement numbers
e
   1050, 1075, 1275, and 1500 (see ReadMe file).
e
C.
  Please feel free to contact me with questions, comments, or errors
e
   (hopefully none of latter).
€
e
  Disclaimer: this program is not guaranteed to be free of error
C
  (although it is believed to be free of error), therefore it should
C
  not be relied on for solving problems where an error could result in
   injury or loss. If this code is used for such solutions, it is
e
   entirely at the user's risk and the author disclaims all liability.
e
implicit real*8 (a-h,o-z)
      save
      include 'params.f'
      dimension parent (nparmax, indmax), child (nparmax, indmax)
      dimension fitness(indmax), nposibl(nparmax), nichflg(nparmax)
      dimension iparent(nchrmax,indmax),ichild(nchrmax,indmax)
      dimension g0(nparmax),g1(nparmax),ig2(nparmax)
      dimension ibest (nchrmax)
      dimension parmax(nparmax),parmin(nparmax),pardel(nparmax)
      dimension_geni(1000000),genavg(1000000),genmax(1000000)
       real*4 cpu, cpu0, cpu1, tarray(2)
      common / gal
                    / npopsiz, nowrite
      common / ga2
                    / nparam, nchrome
                    / parent, iparent
      common / qa3
      common / ga4
                    / fitness
      common / ga5
                    <del>/ g0,g1,ig2</del>
                    / parmax, parmin, pardel, nposibl
      common / ga6
                    / child, ichild
      common / ga7
                    / nichflg
      common / qa8
      common /inputga/-pcross,pmutate,pcreep,maxgen,idum,irestrt,
                      itourny, ielite, icreep, iunifrm, iniche,
                      ickip, iend, nchild, microga, kountmx
Input variable definitions:
e
e
            - 0 for no creep mutations
   icreep
G
            - 1 for creep mutations; creep mutations are recommended.
            The initial random number seed for the GA run. Must equal
   idum
G
           a negative integer, e.g. idum -- 1000.
            - 0 for no elitism (best individual not necessarily
   <del>iclite</del>
                replicated from one generation to the next).
e
            - 1 for elitism to be invoked (best individual replicated
æ
                into next generation); elitism is recommended.
                - 0 for normal GA run (this is standard).
e
   iend
            - number of last population member to be looked at in a set
e
              of individuals. Setting iend-0 is only used for debugging
```

```
purposes and is commonly used in conjunction with iskip.
e
            - 0 for no niching
  iniche
e
            - 1 for niching; niching is recommended.
е
            - 0 for a new GA run, or for a single function evaluation
e
   <del>irestrt</del>
            ■ 1 for a restart continuation of a GA run.
æ
            - 0 for normal-GA run (this is standard).
  iskip
e
            - number in population to look at a specific individual or
e
              set of individuals. Setting iskip-0 is only used for
e
              debugging purposes.
e
           No longer used. The GA is presently set up for only
e
  itourny
            tournament selection.
e
            - 0 for single-point crossover
   iunifrm
e
            - 1 for uniform crossover; uniform crossover is recommended.
e
            - the maximum value of kount before a new restart file is
  kountmx
e
              written; presently set to write every fifth generation.
C
              Increasing this value will reduce I/O time requirements
æ
              and reduce wear and tear on your storage device
е
            The maximum number of generations to run by the GA.
е
   maxgen
            For a single function evaluation, set equal to 1.
e
            - 0 for normal conventional GA operation
   microga
e
            - 1 for micro-GA operation (this will automatically reset
e
              some of the other input flags). I recommend using
e
              npopsiz-5 when microga-1.
e
            - 1 for one child per pair of parents (this is what I
   nchild
C
                typically use).
e
            - 2 for two children per pair of parents (2 is more common
C
                in GA work).
C
           - array of 1/0 flags for whether or not niching occurs on
  nichflg
e
              a particular parameter. Set to 0 for no niching on
e
              a parameter, set to 1 for niching to operate on parameter.
e
              The default value is 1, but the implementation of niching
e
              is still controlled by the flag iniche.
e
            - 0 to write detailed mutation and parameter adjustments
C
  nowrite
            - 1 to not write detailed mutation and parameter adjustments
            Number of parameters (groups of bits) of each individual.
   nparam
æ
            Make sure that nparam matches the number of values in the
e
            parmin, parmax and nposibl input arrays.
e
            The population size of a GA run (typically 100 works well).
   npopsiz
C
            For a single calculation, set equal to 1.
e
            - array of integer number of possibilities per parameter.
   nposibl
e
              For optimal code efficiency set nposibl=2**n, i.e. 2, 4,
e
              8, 16, 32, 64, etc.
е
            - array of the maximum allowed values of the parameters
  <del>parmax</del>
e
            - array of the minimum allowed values of the parameters
   parmin
            The creep mutation probability. Typically set this
   pcreep
            - (nchrome/nparam)/npopsiz.
            The crossover probability. For single-point crossover, a
e
   peross
            value of 0.6 or 0.7 is recommended. For uniform crossover,
e
            a value of 0.5 is suggested.
            The jump mutation probability. Typically set - 1/npopsiz.
e
  pmutate
e
C
  For single function evaluations, set npopsizel, maxgenel, & irestrte0.
e
æ
  My favorite initial choices of GA parameters are:
e
      microga-1, npopsiz-5, iunifrm-1, maxgen-200
      microga=1, npopsiz=5, iunifrm=0, maxgen=200
æ
   I generally get good performance with both the uniform and single-
  point crossover micro-GA.
e
  For those wishing to use the more conventional GA techniques,
```

```
my old favorite choice of GA parameters was:
e
      iunifrm-1, iniche-1, ielite-1, itourny-1, nchild-1
e
  For most problems I have dealt with, I get good performance using
e
      npopsiz=100, pcross=0.5, pmutate=0.01, pcreep=0.02, maxgen=26
е
е
   <del>or</del>
      npopsiz-50, peross-0.5, pmutate-0.02, percep-0.04, maxgen-51
е
e
   Any negative integer for idum should work. I typically arbitrarily
G.
   choose idum--10000 or -20000.
e
C
e
   Code variable definitions (those not defined above):
e
€
            - the best fitness of the generation
   best
e
            - the floating point parameter array of the children
   child
e
            - cpu time of the calculation
e
   epu
   epu0, cpu1 = cpu times associated with 'etime' timing function
æ
            -+1-or-1, indicates which direction parameter creeps
   creep
e
            - del/nparam
   <del>delta</del>
   diffrac - fraction of total number of bits which are different
æ
              between the best and the rest of the micro-GA population.
e
              Population convergence arbitrarily set as diffrac<0.05.
e
            - number of function evaluations
   <del>evals</del>
æ
            - average fitness of population
   fbar
   fitness - array of fitnesses of the parents
e
            - sum of the fitnesses of the parents
   <u>fitsum</u>
            - array of average fitness values for each generation
e
   <del>genavg</del>
            generation array
   geni
æ
            - array of maximum fitness values for each generation
   genmax
e
            - lower bound values of the parameter array to be optimized.
   <del>q0</del>
e
               The number of parameters in the array should match the
e
               dimension set in the above parameter statement.
e
             - the increment by which the parameter array is increased
e
   <del>g1</del>
               from the lower bound values in the g0 array. The minimum
e
               parameter value is g0 and the maximum parameter value
e
               equals g0+g1*(2**g2-1), i.e. g1 is the incremental value
e
               between min and max.
e
             - array of the number of bits per parameter, i.e. the number
e
   iq2
               of possible values per parameter. For example, ig2-2 is
C
               equivalent to 4 (=2**2) possibilities, ig2=4 is equivalent
е
               to 16 (-2**4)-possibilities.
æ
             sum of the number of possibilities of ig2 array
   <del>ig2sum</del>
e
             - binary array of chromosomes of the best individual
   ibest
             - binary array of chromosomes of the children
   ichild
             - counter of number of different bits between best
   icount
               individual and other members of micro-GA population
             - the crossover point in single-point crossover
æ
   icross
             - maximum # of individuals allowed, i.e. max population-size
   <del>indmax</del>
e
            - binary array of chromosomes of the parents
   <del>iparent</del>
             - the generation to be started from
   istart
             - the member in the population with the best fitness
   <del>jbest</del>
             - a counter which tracks the number of bits of an individual
    <del>jelite</del>
a
               which match those of the best individual
             - used in conjunction with iend for debugging
   <del>jend</del>
             - used in conjunction with iskip for debugging
   istart
             - a counter which controls how frequently the restart
   kount
               file is written
             - kelite set to unity when jelite-nchrome, indicates that
   kelite
æ
               the best parent was replicated amongst the children
e
             - the number of the population member chosen as matel
    mate1
```

```
- the number of the population member chosen as mate2
  mate2
           - maximum # of chromosomes (binary bits) per individual
  nchrmax
e.
e nehrome - number of chromosomes (binary bits) of each individual
           - # of creep mutations which occurred during reproduction
e <del>ncreep</del>
e nmutate - # of jump mutations which occurred during reproduction
  nparmax - maximum # of parameters which the chromosomes make up
e
  paramav - the average of each parameter in the population
e
  paramsm - the sum of each parameter in the population
           - the floating point parameter array of the parents
  <del>parent</del>
e
           - array of the difference between parmax and parmin
  <del>pardel</del>
e
           - the value of the current random number
   rand
  npossum - sum of the number of possible values of all parameters
e
           - time array used with 'etime' timing function
   <del>tarray</del>
            - clock time at start of run
   time0
e
Subroutines:
e
e
C
            - Codes floating point value to binary string.
   code
e
   crosovr - Performs crossover (single-point or uniform).
e
           - Decodes binary string to floating point value.
   <del>decode</del>
e
   evalout - Evaluates the fitness of each individual and outputs
              generational information to the 'ga.out' file.
e
            - The function which is being evaluated.
   func
e
   gamicro - Implements the micro-GA technique.
e
            - Inputs information from the 'ga.inp' file.
   input
e
   initial - Program initialization and inputs information from the
e
              'qa.restart' file.
e
            - Performs mutation (jump and/or creep).
e
   mutate
            - Writes child array back into parent array for new
   newgen
e
              generation; also checks to see if best individual was
e
              replicated (elitism).
e
            - Performs niching (sharing) on population.
   <del>niche</del>
C
   possibl - Checks to see if decoded binary string falls within
C.
              specified range of parmin and parmax.
            - The random number generator.
   ran3
e
   restart - Writes the 'ga.restart' file.
e
            - A subroutine of 'selectn'.
   <del>select</del>
   selectn - Performs selection; tournament selection is the only
e
              option in this version of the code.
e
   shuffle - Shuffles the population randomly for selection.
e
e
e
       call etime(tarray)
e
       write(6,*) tarray(1),tarray(2)
e
       epu0-tarray(1)
e
æ
   Call the input subroutine.
e
       TIMEO-SECNDS (0.0)
C
      call input
   Perform necessary initialization and read the ga.restart-file.
      call initial (istart, npossum, ig2sum)
 e
   $$$$$ Main generational processing loop. $$$$$
      kount-0
       do 20 i=istart, maxgen+istart-1
         write (6,1111) i
```

```
write (24,1111) i
        write(24,1050)
  Evaluate the population, assign fitness, establish the best
  individual, and write output information.
        call evalout(iskip,iend,ibest,fbar,best)
        geni(i)=float(i)
        genavg(i)-fbar
        genmax(i)-best
        if (npopsiz.eq.1 .or. iskip.ne.0) then
           close (24)
           stop
        endif
  Implement "niching".
        if (iniche.ne.0) call niche
e
  Enter selection, crossover and mutation loop.
        ncross-0
        ipick-npopsiz
        do 45 j=1,npopsiz,nchild
  Perform selection.
           call selectn(ipick,j,mate1,mate2)
  Now-perform crossover between the randomly selected pair.
           call crosovr(ncross, j, matel, mate2)
45
        continue
        write(6,1225) ncross
        write(24,1225) ncross
   New perform random mutations. If running micro-GA, skip mutation.
        if (microga.eg.0) call mutate
  Write child array back into parent array for new generation. Check
  to see if the best parent was replicated.
         call newgen(ielite, npossum, ig2sum, ibest)
  Implement micro-GA if enabled.
e
        if (microga.ne.0) call gamicro(i,npossum,ig2sum,ibest)
  Write to restart file.
         call-restart(i,istart,kount)
     continue
  $$$$$ End of main generational processing loop. $$$$$
      <del>continue</del>
     write(24,3000)
      do 100 i=1, maxqen
         evals-float (npopsiz) *geni(i)
        write(24,3100) geni(i), evals, genavg(i), genmax(i)
 100 continue
      call etime (tarray)
æ
      write(6,*) tarray(1),tarray(2)
e
      cpul=tarray(1)
e
      epu-(cpul-cpu0)
æ
      write(6,1400) cpu,cpu/60.0
e
      write(24,1400) cpu,cpu/60.0
      CLOSE (24)
                        Binary Code',16x,'Paraml Param2 Fitness')
 1050 format (1x, ' #
```

```
1225 format (/ ' Number of Crossovers
                                           =1,15)
c 1400 format(2x, 'CPU time for all generations-', e12.6, ' sec'/
                                                <del>',e12.6,' min')</del>
              2x,-
3000 format(2x//'Summary of Output'/
                                                           Best Fitness')
                              Evaluations
             2x, Generation
                                             Avg.Fitness
3100 format (2x, 3 (e10.4, 4x), e11.5)
      stop
      end
subroutine input
e
   This subroutine inputs information from the ga.inp (gafort.in) file.
e
e
      implicit real*8 (a-h,o-z)
      save
      include 'params.f'
      dimension nposibl (nparmax), nichflg (nparmax)
      dimension parmax (nparmax), parmin (nparmax), pardel (nparmax)
      common / gal
                     / npopsiz, nowrite
      common / ga2
                     / nparam, nchrome
                     / parmax, parmin, pardel, nposibl
      common / qa6
      common / ga8
                     / nichflq
      common /inputga/ pcross,pmutate,pcreep,maxgen,idum,irestrt,
                       itourny, ielite, icreep, iunifrm, iniche,
                       iskip, iend, nchild, microga, kountmx
C
                      /-irestrt,npopsiz,pmutate,maxgen,idum,pcross,
      namelist / ga
                        itourny, ielite, icreep, pcreep, iunifrm, iniche,
                        iskip, iend, nchild, nparam, parmin, parmax, nposibl,
                        nowrite, nichflg, microga, kountmx
e
      kountmx=5
      irestrt=0
      itourny=0
      ielite-0
      iunifrm-0
      iniche-0
      iskip=0
      <del>iend=0</del>
      nchild-1
      do 2 i=1, nparmax
         nichflg(i)=1
 2
      continue
      microga-0
      OPEN (UNIT-24, FILE-'ga.out', STATUS-'UNKNOWN')
      rewind 24
      OPEN (UNIT-23, FILE-'ga.inp', STATUS-'OLD')
      READ (23, NML - qa)
      CLOSE (23)
      itourny-1
      irestrt=0
      kountmx-maxgen
       if (itourny.eq.0) nchild=2
C
   Check for array sizing errors.
      if (npopsiz.qt.indmax) then
```

```
write(6,1600) npopsiz
        write(24,1600) npopsiz
        close (24)
        stop
     <del>endif</del>
     if (nparam.gt.nparmax) then
        write(6,1700) nparam
        write(24,1700) nparam
        close (24)
        stop
     endif
  If using the microga option, reset some input variables
     if (microga.ne.0) then
        pmutate=0.0d0
        pcreep=0.0d0
        itourny-1
        ielite-1
        iniche=0
        nchild-1
        if (iunifrm.eq.0) then
           pcross-1.0d0
        else
           pcross-0.5d0
        endif
     endif
1600 format(1x, 'ERROR: npopsiz > indmax. Set indmax = ', i6)
1700 format(1x, 'ERROR: nparam > nparmax. Set nparmax = ', i6)
     return
     end
subroutine initial (istart, npossum, ig2sum)
e
  This subroutine sets up the program by generating the g0, g1 and
  ig2 arrays, and counting the number of chromosomes required for the
  specified input. The subroutine also initializes the random number
  generator, parent and iparent arrays (reads the ga.restart file).
      implicit real*8 (a-h,o-z)
      save
      include 'params.f'
      dimension parent (nparmax, indmax), iparent (nchrmax, indmax)
      dimension nposibl (nparmax)
      dimension_q0(nparmax),q1(nparmax),ig2(nparmax)
      dimension parmax (nparmax), parmin (nparmax), pardel (nparmax)
                    / npopsiz, nowrite
      common / gal
                    /-nparam,nchrome
      common / qa2
                    / parent, iparent
      common / qa3
      common / qa5
                    / q0,q1,iq2
      common / ga6
                    / parmax, parmin, pardel, nposibl
      common /inputga/ peross,pmutate,pereep,maxgen,idum,irestrt,
                      itourny, ielite, icreep, iunifrm, iniche,
                      iskip, iend, nchild, microga, kountmx
C
      do 3 i=1, nparam
         q0(i)=parmin(i)
```

```
pardel(i)-parmax(i)-parmin(i)
        q1(i)-pardel(i)/dble(nposibl(i)-1)
     continue
     do 6 i-1, nparam
        do 7 j=1,30
           n2j=2**j
           if (n2j.ge.nposibl(i)) then
              ig2(i)=j
              <del>goto 8</del>
           endif
           if (j.ge.30) then
              write(6,2000)
              write(24,2000)
              close (24)
              stop
           endif
        continue
8
        continue
6
     continue
  Count the total number of chromosomes (bits) required
     nchrome-0
     npossum-0
     ig2sum=0
     do 9 i=1, nparam
        nchrome-nchrome+ig2(i)
        npossum-npossum+nposibl(i)
        iq2sum-ig2sum+(2**ig2(i))
     continue
Ω
     if (nchrome.gt.nchrmax) then
        write(6,1800) nchrome
        write(24,1800) nchrome
        close(24)
        stop
     <del>endif</del>
     if (npossum.lt.ig2sum .and. microga.ne.0) then
        write(6,2100)
        write(24,2100)
     endif
  Initialize random number generator
     call ran3 (idum, rand)
     if (irestrt.eq.0) then
  Initialize the random distribution of parameters in the individual
  parents when irestrt-0.
        istart-1
        do 10 i=1,npopsiz
           do 15 j-1, nchrome
               call ran3(1, rand)
               iparent(j,i)=1
               if (rand.lt.0.5d0) iparent (j,i)=0
15
           continue
10
        continue
        if (npossum.lt.ig2sum) call possibl(parent,iparent)
     else
  If irestrt.ne.0, read from restart file.
        OPEN (UNIT-25, FILE-'ga.restart', STATUS-'OLD')
        rewind 25
        read(25,*) istart, npopsiz
```

```
do 1 j-1, npopsiz
           read(25,*) k, (iparent(1,j),l=1,nchrome)
        continue
1
        CLOSE (25)
     endif
     if(irestrt.ne.0) call ran3(idum-istart,rand)
1800 format (1x, 'ERROR: nchrome > nchrmax. Set nchrmax = ', i6)
2000 format(1x, 'ERROR: You have a parameter with a number of '/
                    possibilities > 2**30! If you really desire this, '/
             <del>1x, '</del>
    +
                    change the DO loop 7 statement and recompile.'//
             1x, '
                   You may also need to alter the code to work with'/
            1x, 1
                    REAL numbers rather than INTEGER numbers; Fortran'/
             1x, !
                    does not like to compute 2**j when j>30.')
             1x, !
2100 format(1x,'WARNING: for some cases, a considerable performance'/
                    reduction has been observed when running a non-1/
             1x, 1
    +
                    optimal number of bits with the micro-GA. '/
             <del>1x, |</del>
    +
                   If possible, use values for nposibl of 2**n,'/
             1x,'
                    e.g. 2, 4, 8, 16, 32, 64, etc. See ReadMe file.')
             1x, !
      return
      end
subroutine evalout(iskip,iend,ibest,fbar,best)
C
  This subroutine evaluates the population, assigns fitness,
e
   establishes the best individual, and outputs information.
      implicit real*8 (a-h,o-z)
      save
      include 'params.f'
      dimension parent (nparmax, indmax), iparent (nchrmax, indmax)
      dimension fitness(indmax)
      dimension paramsm(nparmax), paramav(nparmax), ibest(nchrmax)
                     / npopsiz, nowrite
      common / qal
                     / nparam, nchrome
      common / qa2
                     / parent, iparent
      common / ga3
                     / fitness
      common / ga4
      fitsum=0.0d0
      best=-1.0d10
      do 29 n-1, nparam
         paramsm(n)=0.0d0
 29
      continue
      <del>jstart-1</del>
      <del>jend-npopsiz</del>
      if(iskip.ne.0) jstart=iskip
      if (iend.ne.0) jend=iend
      do 30 j=jstart, jend
         call decode (j, parent, iparent)
         if(iskip.ne.0 .and. iend.ne.0 .and. iskip.eq.iend)
         write(6,1075) j, (iparent(k,j),k=1,nchrome),
                          (parent (kk, j), kk=1, nparam), 0.0
   Call function evaluator, write out individual and fitness, and add
   to the summation for later averaging.
         call func (j, funcval)
         fitness(j)=funcval
```

```
write(24,1075) j, (iparent(k,j),k=1,nchrome),
                       (parent (kk, j), kk=1, nparam), fitness(j)
        fitsum-fitsum+fitness(j)
        do 22 n-1, nparam
           paramsm(n) =paramsm(n) +parent(n, j)
22
        continue
  Check to see if fitness of individual j is the best fitness.
        if (fitness(j).gt.best) then
           best-fitness(j)
           <del>jbest-j</del>
            do 24 k=1,nchrome
               ibest(k)-iparent(k,j)
            continue
24
         <del>endif</del>
      continue
30
e
  Compute parameter and fitness averages.
e
      fbar=fitsum/dble(npopsiz)
      do 23 n=1,nparam
         paramav(n)=paramsm(n)/dble(npopsiz)
      continue
23
  Write output information
      if (npopsiz.eq.1) then
         write(24,1075) -1, (iparent(k,1),k=1,nchrome),
                        (parent(k,1),k=1,nparam),fitness(1)
         write(24,*) ' Average Values: '
         write(24,1275) (parent(k,1),k=1,nparam),fbar
      else
         write(24,1275) (paramav(k),k-1,nparam),fbar
      endif
      write(6,1100) fbar
      write(24,1100) fbar
      write(6,1200) best
      write (24, 1200) best
 1075 format(i3,1x,30i1,2(1x,f7.4),1x,f8.5)
 1100 format(1x,'Average Function Value of Generation-',f8.5)
                                                     =1, f8.5/)
 1200 format(1x, 'Maximum Function Value
 1275 format(/' Average Values:',18x,2(1x,f7.4),1x,f8.5/)
      return
      end
subroutine niche
e
   Implement "niching" through Goldberg's multidimensional phenotypic
   sharing scheme with a triangular sharing function. To find the
   multidimensional distance from the best individual, normalize all
   parameter differences.
C
      implicit real*8 (a-h,o-z)
      save
      include 'params.f'
      dimension parent (nparmax, indmax), iparent (nchrmax, indmax)
      dimension fitness(indmax), nposibl(nparmax), nichflg(nparmax)
      dimension parmax (nparmax), parmin (nparmax), pardel (nparmax)
e
                     / npopsiz, nowrite
      common / qal
```

```
/ nparam, nchrome
      common / ga2
                     / parent, iparent
      common / ga3
                     / fitness
      common / ga4
                     / parmax, parmin, pardel, nposibl
      common / ga6
      common / ga8
                     / nichflg
e
    Variable definitions:
e
a
           - power law exponent for sharing function; typically - 1.0
   alpha
           - normalized multidimensional distance between ii and all
   del
e
             other members of the population
G
             (equals the square root of del2)
C
           - sum of the squares of the normalized multidimensional
   del2
C
             distance between member ii and all other members of
             the population
e
   nniche - number of niched parameters
e
   sigshar - normalized distance to be compared with del; in some sense,
             1/gigshar can be viewed as the number of regions over which
a
             the sharing function should focus, e.g. with sigshar=0.1,
             the sharing function will try to clump in ten distinct
             regions of the phase space. A value of sigshar on the
C
             order of 0.1 seems to work best.
e
           - sharing function between individual ii and j
e
   sumshar - sum of the sharing functions for individual ii
æ
       alpha-1.0
      sigshar-0.1d0
      nniche=0
      do 33 jj-1, nparam
         nniche-nniche + nichflg (jj)
      continue
 33
      if (nniche.eq.0) then
         write(6,1900)
         write(24,1900)
         close (24)
         stop
      <del>endif</del>
      do 34 ii-1, npopsiz
         sumshar-0.0d0
         do 35 j=1, npopsiz
            del2=0.0d0
            do 36 k∍1,nparam
                if (nichflq(k).ne.0) then
                   del2-del2+((parent(k,j)-parent(k,ii))/pardel(k))**2
                endif
            continue
 36
            del-(dsqrt(del2))/dble(nniche)
            if (del.lt.sigshar) then
                 share-1.0-((del/sigshar)**alpha)
                share=1.0d0-(del/sigshar)
            else
                share-0.0d0
            end if
             sumshar-sumshar+share/dble(npopsiz)
 35
         if (sumshar.ne.0.0d0) fitness(ii)-fitness(ii)/sumshar
      continue
 34
 1900 format(1x, 'ERROR: iniche=1 and all values in nichflg array = 0'/
                         Do you want to niche or not?')
             1x, 1
```

e

```
return
     end
subroutine selectn(ipick, j, matel, mate2)
a
  Subroutine for selection operator. Presently, tournament selection
   is the only option available.
      implicit real*8 (a-h,o-z)
      save
      include 'params.f'
      dimension parent (nparmax, indmax), child (nparmax, indmax)
      dimension fitness (indmax)
      dimension-iparent(nchrmax, indmax), ichild(nchrmax, indmax)
                    / npopsiz, nowrite
      common / gal
                    / nparam, nchrome
      common / qa2
      common / ga3
                    / parent, iparent
      common / ga4
                    / fitness
      common / ga7
                    / child, ichild
      common /inputga/ pcross, pmutate, pcreep, maxgen, idum, irestrt,
                      itourny, ielite, icreep, iunifrm, iniche,
                      iskip, iend, nchild, microga, kountmx
   If tournament selection is chosen (i.e. itourny-1), then
e
   implement "tournament" selection for selection of new population.
      if (itourny.eq.1) then
         call select (matel, ipick)
         call select (mate2, ipick)
         write(3,*) mate1, mate2, fitness(mate1), fitness(mate2)
         do 46 n=1, nchrome
            ichild(n,j)=iparent(n,matel)
            if(nchild.eq.2)-ichild(n,j+1)-iparent(n,mate2)
         continue
 46
      endif
C
      return
      end
subroutine crosovr(ncross, j, mate1, mate2)
Q
   Subroutine for crossover between the randomly selected pair.
      implicit real*8 (a-h,o-z)
      save
      include 'params.f'
      dimension parent (nparmax, indmax), child (nparmax, indmax)
      dimension iparent(nchrmax, indmax), ichild(nchrmax, indmax)
                     / nparam, nchrome
      common / qa2
                     / parent, iparent
      common / ga3
                     / child, ichild
      common / qa7
      common /inputga/ pcross, pmutate, pcreep, maxgen, idum, irestrt,
                       itourny, ielite, icreep, iunifrm, iniche,
                       iskip, iend, nchild, microga, kountmx
      if (iunifrm.eq.0) then
   Single-point crossover at a random chromosome point.
```

```
call ran3 (1, rand)
        if (rand.gt.pcross) goto 69
        ncross-ncross+1
        call ran3 (1, rand)
        icross=2+dint(dble(nchrome-1)*rand)
        do 50 n-icross, nchrome
           ichild(n,j)=iparent(n,mate2)
           if (nchild.eq.2) ichild(n,j+1)=iparent(n,mate1)
        continue
50
     else
  Perform uniform crossover between the randomly selected pair.
        do 60 n=1, nchrome
           call ran3(1, rand)
           if (rand.le.pcross) then
              ncross-ncross+1
              ichild(n,j)=iparent(n,mate2)
              if (nchild.eq.2) ichild(n,j+1) ⇒iparent(n,matel)
            endif
        continue
60
     end i f
     continue
69
4
     return
      end
subroutine mutate
e
      implicit real*8 (a-h,o-z)
      include 'params.f'
      dimension nposibl(nparmax)
      dimension_child(nparmax,indmax),ichild(nchrmax,indmax)
      dimension g0(nparmax),g1(nparmax),ig2(nparmax)
      dimension parmax(nparmax), parmin(nparmax), pardel(nparmax)
                     / npopsiz, nowrite
      common / gal
                     / nparam, nchrome
      common / qa2
                     <del>/-g0,g1,ig2</del>
      common / ga5
                     / parmax,parmin,pardel,nposibl
      common / ga6
                     / child, ichild
      common / qa7
      common /inputga/ pcross, pmutate, pcreep, maxgen, idum, irestrt,
                       itourny, ielite, icreep, iunifrm, iniche,
                       iskip, iend, nchild, microga, kountmx
C
   This subroutine performs mutations on the children generation.
   Perform random jump mutation if a random number is less than pmutate.
   Perform random creep mutation if a different random number is less
   than pcreep.
      nmutate-0
      ncreep=0
      do 70 i=1, npopsiz
         do 75 k=1, nchrome
   Jump mutation
            call ran3(1, rand)
            if (rand.le.pmutate) then
               nmutate=nmutate+1
               if(ichild(k,j).eq.0) then
                  ichild(k,j)-1
               else
```

```
ichild(k, j) = 0
              endif
              if (nowrite.eq.0) write(6,1300) j,k
              if (nowrite.eq.0) write(24,1300) j,k
           endif
75
        continue
e Creep mutation (one discrete position away).
        if (icreep.ne.0) then
           do 76 k=1,nparam
              call ran3(1, rand)
              if (rand.le.pcreep) then
                 call decode(j,child,ichild)
                 ncreep-ncreep+1
                 creep=1.0d0
                 call ran3 (1, rand)
                 if (rand.lt.0.5d0) creep-1.0d0
                 child(k, j) -child(k, j) +gl(k) *creep
                 if (child(k,j).gt.parmax(k)) then
                    child(k,j) = parmax(k) - 1.0d0*g1(k)
                 elseif (child(k,j).lt.parmin(k)) then
                    child(k,j) = parmin(k) + 1.0d0*g1(k)
                 endif
                 call code(j,k,child,ichild)
                 if (nowrite.eq.0) write(6,1350) j,k
                 if (nowrite.eq.0) write(24,1350) j,k
              endif
           continue
76
        endif
70
     continue
     write(6,1250) nmutate,ncreep
     write(24,1250) nmutate,ncreep
1250 format (/' Number of Jump Mutations =', i5/
             Number of Creep Mutations =',i5)
1300 format ('*** Jump mutation performed on individual ',i4,
            ', chromosome ', i3, ' ***!)
1350 format('*** Creep mutation performed on individual-',i4,
            ', parameter ',i3,' ***1)
     return
     end
subroutine newgen(ielite,npossum,ig2sum,ibest)
  Write child array back into parent array for new generation. Check
C
  to-see if the best parent was replicated; if not, and if ielite-1,
  then reproduce the best parent into a random slot.
æ
     implicit real*8 (a-h,o-z)
     save
     include 'params.f'
     dimension parent(nparmax, indmax), child(nparmax, indmax)
     dimension iparent(nchrmax,indmax),ichild(nchrmax,indmax)
     dimension ibest (nchrmax)
                    /_npopsiz,nowrite
     common / gal
                    / nparam, nchrome
     common / qa2
                    / parent, iparent
     common-/ qa3
     common / ga7
                    /-child, ichild
```

```
if (npossum.lt.ig2sum) call possibl(child,ichild)
     kelite=0
     do 94 j=1,npopsiz
        <del>jelite-0</del>
        do 95 n-1, nchrome
           iparent(n,j)=ichild(n,j)
           if (iparent(n,j).eq.ibest(n)) jelite=jelite+1
           if (jelite.eq.nchrome) kelite=1
95
        continue
     continue
94
     if (ielite.ne.0 .and. kelite.eq.0) then
        call ran3(1, rand)
        irand-1d0+dint(dble(npopsiz)*rand)
        do 96 n=1,nchrome
           iparent(n,irand)=ibest(n)
96
        continue
        write(24,1260) irand
     endif
1260 format(' Elitist Reproduction on Individual ', i4)
     return
     end
subroutine gamicro(i,npossum,ig2sum,ibest)
e
  Micro-GA implementation subroutine
e
     implicit real*8 (a-h,o-z)
     cave
     include 'params.f'
     dimension parent (nparmax, indmax), iparent (nchrmax, indmax)
     dimension ibest (nchrmax)
                    / npopsiz, nowrite
      common / gal
                    / nparam, nchrome
      common / ga2
     common / ga3
                    / parent, iparent
  First, check-for convergence of micro population.
  If converged, start a new generation with best individual and fill
  the remainder of the population with new randomly generated parents.
a
  Count number of different bits from best member in micro-population
      icount-0
      do 81 j-1, npopsiz
        do 82 n-1, nchrome
           if(iparent(n,j).ne.ibest(n)) icount=icount+1
 82
        continue
      continue
 81
  If icount less than 5% of number of bits, then consider population
  to be converged. Restart with best individual and random others.
      diffrac-dble(icount)/dble((npopsiz-1)*nchrome)
      if (diffrac.lt.0.05d0) then
      do 87 n-1, nchrome
        iparent(n,1)-ibest(n)
 87
      continue
      do 88-i-2, npopsiz
```

```
do 89 n-1, nchrome
          call ran3(1, rand)
          iparent(n, j) = 1
          if(rand.lt.0.5d0) iparent(n,j)=0
        continue
89
     continue
88
     if (npossum.lt.ig2sum) call possibl(parent,iparent)
     write(6,1375) i
     write(24,1375) - i
     endif
1375 format(//'%%%%%%% Restart micro-population at generation',
            <del>i5,' %%%%%%')</del>
c
     return
     end
subroutine select (mate, ipick)
  This routine selects the better of two possible parents for mating.
e
     implicit real*8 (a-h,o-z)
     save
e
     include 'params.f'
     common / gal / npopsiz, nowrite
                  / nparam, nchrome
     common / ga2
     common / ga3 / parent, iparent
     common / ga4 / fitness
     dimension parent (nparmax, indmax), iparent (nchrmax, indmax)
     dimension fitness (indmax)
     if(ipick+1.gt.npopsiz) call shuffle(ipick)
     ifirst-ipick
     isecond-ipick+1
     ipick-ipick+2
     if(fitness(ifirst).gt.fitness(isecond)) then
        mate=ifirst
      else
        mate=isecond
      endif
      write(3,*)'select',ifirst,isecond,fitness(ifirst),fitness(isecond)
      return
      end
subroutine shuffle(ipick)
C
   This routine shuffles the parent array and its corresponding fitness
æ
      implicit real*8 (a-h,o-z)
      save
      include 'params.f'
      common / gal / npopsiz, nowrite
      common / qa2
                   / nparam, nchrome
                   / parent, iparent
      common / ga3
                   / fitness
      common / qa4
      dimension parent (nparmax, indmax), iparent (nchrmax, indmax)
```

```
dimension fitness (indmax)
     ipick-1
     do 10 j-1, npopsiz-1
        call ran3 (1, rand)
        iother=j+1+dint(dble(npopsiz-j)*rand)
        do 20 n-1, nchrome
          itemp=iparent(n,iother)
          iparent(n,iother)=iparent(n,j)
           iparent(n,j)=itemp
20
        continue
        temp=fitness(iother)
        fitness(iother)-fitness(j)
        fitness(i)-temp
     continue
10
e
     return
     end
subroutine decode(i,array,iarray)
e
  This routine decodes a binary string to a real number.
e
     implicit real*8 (a-h,o-z)
     save
     include 'params.f'
                   / nparam, nchrome
     common / qa2
                   / g0,g1,ig2
     common / qa5
     dimension array (nparmax, indmax), iarray (nchrmax, indmax)
     dimension g0 (nparmax), g1 (nparmax), ig2 (nparmax)
e
     do 10 k-1, nparam
        iparam=0
        m-1
        do-20-j-m,m+ig2(k)-1
           iparam-iparam+iarray(j,i)*(2**(m+ig2(k)-1-j))
 20
        array(k, i) = g0(k) + g1(k) * dble(iparam)
 10
     continue
return
     end
subroutine code(j,k,array,iarray)
e
  This routine codes a parameter into a binary string.
C
     implicit real*8 (a-h,o-z)
     save
     include 'params.f'
     common / ga2
                   /-nparam, nchrome
     common / ga5
                   / q0, q1, ig2
     dimension array (nparmax, indmax), iarray (nchrmax, indmax)
     dimension g0 (nparmax), g1 (nparmax), ig2 (nparmax)
```

C

```
First, establish the beginning location of the parameter string of
  interest.
     ictart-1
      do 10 i=1.k-1
        istart-istart+ig2(i)
10
     continue
e
  Find the equivalent coded parameter value, and back out the binary
G
  string by factors of two.
     m=ig2(k)-1
      if (q1(k).eq.0.0d0) return
      iparam=nint((array(k,j)-g0(k))/g1(k))
      do 20 i-istart, istart+ig2(k)-1
        iarray(i,j)=0
        if ((iparam+1).gt.(2**m)) then
           iarray(i,j)=1
           iparam-iparam-2**m
        endif
        m=m-1
20
      continue
      write(3,*)array(k,j),iparam,(iarray(i,j),i=istart,istart+ig2(k)-1)
e
c
      return
      end
e
      subroutine possibl (array, iarray)
æ
  This subroutine determines whether or not all parameters are within
  the specified range of possibility. If not, the parameter is
  randomly reassigned within the range. This subroutine is only
  necessary when the number of possibilities per parameter is not
   optimized to be 2**n, i.e. if npossum < ig2sum.
      implicit real*8 (a-h,o-z)
      save
      include 'params.f'
      common / gal / npopsiz, nowrite
                    / nparam, nchrome
      common / qa2
      common / qa5
                    <del>/ q0,q1,iq2</del>
                    / parmax, parmin, pardel, nposibl
      common / qa6
      dimension array (nparmax, indmax), iarray (nchrmax, indmax)
      dimension-g0(nparmax),g1(nparmax),ig2(nparmax),nposibl(nparmax)
      dimension-parmax(nparmax), parmin(nparmax), pardel(nparmax)
      do 10 i=1, npopsiz
        call decode (i, array, iarray)
        do 20 j-1, nparam
           n2ig2j-2**ig2(j)
            if(nposibl(j).ne.n2ig2j .and. array(j,i).gt.parmax(j)) then
              call ran3 (1, rand)
              irand-dint(dble(nposibl(j))*rand)
              array(j,i)=g0(j)+dble(irand)*g1(j)
              call-code(i,j,array,iarray)
              if (nowrite.eq.0) write(6,1000) i,j
              if (nowrite.eq.0) write(24,1000) i,j
           endif
 20
         continue
 10
      continue
```

```
1000 format('*** Parameter adjustment to individual
                                                     1, 14,
            ', parameter ', i3, ' ***!)
e
     return
     end
subroutine restart (i, istart, kount)
  This subroutine writes restart information to the ga.restart file.
e
e
     implicit real*8 (a-h,o-z)
     save
     include 'params.f'
     common / gal / npopsiz, nowrite
                   / nparam, nchrome
     common / qa2
                  / parent, iparent
     common / qa3
     dimension parent (nparmax, indmax), iparent (nchrmax, indmax)
     common /inputga/ pcross,pmutate,pcreep,maxgen,idum,irestrt,
                     itourny, ielite, icreep, iunifrm, iniche,
                     iskip, iend, nchild, microga, kountmx
     kount-kount+1
     if(i.eq.maxgen+istart-1.or. kount.eq.kountmx) then
        OPEN (UNIT-25, FILE-'ga.restart', STATUS-'OLD')
        rewind 25
        write(25,*) i+1, npopsiz
        do 80 i=1, npopsiz
           write(25,1500) j,(iparent(1,j),1=1,nchrome)
 80
        continue
        CLOSE (25)
        kount-0
     endif
 1500 format (i5,3x,30i2)
e
     return
     end
subroutine ran3 (idum, rand)
e
   Returns a uniform random deviate between 0.0 and 1.0. Set idum to
   any negative value to initialize or reinitialize the sequence.
   This function is taken from W.H. Press', "Numerical Recipes" p. 199.
     implicit real*8 (a-h,m,o-z)
      save
      implicit real*4(m)
      parameter (mbig-4000000., mseed-1618033., mz-0., fac-1./mbig)
     parameter (mbig=1000000000, mseed=161803398, mz=0, fac=1./mbig)
   According to Knuth, any large mbig, and any smaller (but still large)
   mseed can be substituted for the above values.
      dimension ma (55)
      data iff /0/
      if (idum.lt.0 .or. iff.eq.0) then
        iff-1
        mi-mseed-dble(iabs(idum))
```

```
mi-dmod (mj, mbig)
        ma (55) -mi
        mk=1
        do 11 i=1,54
           ii - mod(21 * i, 55)
           ma(ii)-mk
           mk-mj-mk
           if (mk.lt.mz) - mk-mk+mbig
           mj=ma(ii)
        continue
11
        do 13 k=1,4
           do 12 i=1.55
              ma(i) = ma(i) - ma(1 + mod(i + 30, 55))
              if (ma(i).lt.mz) ma(i)-ma(i)+mbig
           continue
12
        continue
13
        inext-0
        inextp-31
        idum-1
     endif
     inext=inext+1
     if (inext.eq.56) inext=1
     inextp-inextp+1
     if(inextp.eq.56) inextp=1
     mi-ma(inext)-ma(inextp)
     if (mi.lt.mz) mj=mj+mbig
     ma(inext)-mj
     rand-mj*fac
     return
     end
subroutine func(j,funcval)
     implicit real*8 (a-h,o-z)
     save
     include 'params.f'
     dimension parent (nparmax, indmax)
     dimension iparent (nchrmax, indmax)
      dimension parent2(indmax, nparmax), iparent2(indmax, nchrmax)
æ
                    / nparam, nchrome
     common / qa2
                    / parent, iparent
      common / qa3
  This is an N-dimensional version of the multimodal function with
  decreasing peaks used by Goldberg and Richardson (1987, see ReadMe
  file for complete reference). In N dimensions, this function has
  (nvalley-1) ^nparam peaks, but only one global maximum. It is a
  reasonably tough problem for the GA, especially for higher dimensions
   and larger values of nvalley.
     nvallev-6
     pi=4.0d0*datan(1.d0)
      funcval-1.0d0
      do 10 i=1, nparam
         f1=(sin(5.1d0*pi*parent(i,j) + 0.5d0))**nvalley
         £2-exp(-4.0d0*log(2.0d0)*((parent(i,j)-0.0667d0)**2)/0.64d0)
         funcval-funcval*f1*f2
      continue
```

```
As mentioned in the ReadMe file, The arrays have been rearranged
e to enable a more efficient caching of system memory. If this causes
e interface problems with existing functions used with previous
e versions of my code, then you can use some temporary arrays to bridge
e this version with older versions. I've named the temporary arrays
  parent2 and iparent2. If you want to use these arrays, uncomment the
  dimension statement above as well as the following do loop lines.
      do 11 i=1, nparam
e
        parent2(j,i)-parent(i,j)
e
      continue
c 11
      do 12 k=1, nchrome
e
         iparent2(j,k)=iparent(k,j)
C
      continue
c 12
     return
     end
```

e

```
$<del>ga</del>
irestrt-0,
microga-1,
npopsiz- 5,
nparam- 2,
pmutate=0.02d0,
maxgen-200,
idum = -1000,
peross=0.5d0,
itourny-1,
ielite=1,
icreep-0,
pcreep=0.04d0,
iunifrm-1,
iniche-0,
nchild-1,
iskip- 0, iend- 0,
nowrite=1,
kountmx-57
parmin- 2*0.0d0,
parmax= 2*1.0d0,
nposibl=2*32768,
nichflg-2*1,
$end
```

```
<del>&ga</del>
irestrt-0,
microga-1,
npopsiz=5,
<del>nparam- 2,</del>
pmutate=0.02d0,
maxgen=200,
idum=-1000,
peross-0.5d0,
itourny-1,
ielite-1,
icreep-0,
pcreep-0.04d0,
iunifrm-1,
iniche=0,
nchild-1,
iskip- 0, iend- 0,
nowrite-1,
kountmx=5,
parmin-2*0.0d0,
parmax = 2*1.0d0,
nposibl=2*32768,
nichflg-2*1,
+
```

################ Generation

Binary Code

```
2 000110010010001101001110011100 0.0982 0.6532 0.10147
 \frac{3-110010101011001110110101011010}{0.7918}
 4 \ 01010011100010111011111111010001 \ 0.3263 \ 0.8736 \ 0.00064
 5 111011111100000100100111110101 0.9366 0.5778 0.00000
                                  0.5429 0.6200 0.02047
Average Values:
Average Function Value of Generation= 0.02047
                                   = -0.10147
Maximum Function Value
 Number of Crossovers
 Elitist Reproduction on Individual
                               2 ##################
################## Generation
                                  Paraml Param2 Fitness
        Binary Code
 #
 \frac{1-010010110011001110011111011110}{0.2937} 0.8115 0.00916
 2 000110010010001101001110011100 0.0982 0.6532 0.10147
 3 110010010010001110111101011000 0.7857 0.8699 0.00008
 4 \quad 00010001101010110101111100111101 \quad 0.0690 \quad 0.6845 \quad 0.09532
 5 110110101011101110110111011011 0.8544 0.8583 0.00430
                                  0.4202 0.7755 0.04206
Average Values:
 Average Function Value of Generation 0.04206
                                   -0.10147
 Maximum Function Value
                               73
 Number of Crossovers
  Elitist Reproduction on Individual
                               3 ################
################### Generation
                                  Paraml Param2 Fitness
        Binary Code
  \frac{1 \cdot 000010010011001110001110011100}{0.0359} \cdot 0.7782 \cdot 0.00019
  <del>2 000100011010101101001110011100 0.0690 0.6532 0.22390</del>
  3 000100010010001101001110011100 0.0669 0.6532 0.22471
  4 000110010010001101001110011100 0.0982 0.6532 0.10147
  5 000110010010101101001110011101 0.0983 0.6532 0.10080
                                  0.0737 0.6782 0.13021
 Average Values:
 Average Function Value of Generation= 0.13021
                                   -0.22471
 Maximum Function Value
                               70
  Number of Crossovers
                                                 3 %%%%%%
****** Restart micro-population at generation
                                4 ################
Paraml Param2 Fitness
        Binary Code
  \frac{1.000100010010001101001110011100}{0.0669}
```

1 #################

Paraml Param2 Fitness

http://www.cuaerospace.com/carroll/ga/ga.out

Average Values:

0.5745 0.5886 0.04967

Average Function Value of Generation= 0.04967
Maximum Function Value = 0.22471

Number of Crossovers = 67
Elitist Reproduction on Individual 5

Average Values: 0.3111 0.6398 0.04622

Average Function Value of Generation = 0.04622
Maximum Function Value = 0.22471

Number of Crossovers = 81
Elitist Reproduction on Individual 2

Average Values: 0.3857 0.7149 0.06616

Average Function Value of Generation - 0.06616
Maximum Function Value - 0.22471

Number of Crossovers = 78
Elitist Reproduction on Individual 5

Average Values:

0.3669 0.6782 0.06470

```
Average Function Value of Generation- 0.06470
Maximum Function Value - 0.22471
```

Number of Crossovers = 80

```
#################
################ Generation
                                    Paraml Param2 Fitness
        Binary Code
 \frac{1\ 00010001001001010101110011100}{0.0069}\ 0.6532\ 0.22471
 2 - 01110001001000110100111100111110 - 0.4419 - 0.6533 - 0.09732
 \frac{3.010100010010001101001110011110}{0.3169}
 4 \quad 0111000100100011000011100111111 \quad 0.4419 \quad 0.5283 \quad 0.00132
 5 001100010010001101001110011100 0.1919 0.6532 0.00115
                                    0.2919 0.6283 0.06744
Average Values:
Average Function Value of Generation- 0.06744
                                     -0.22471
Maximum Function Value
                                78
 Number of Crossovers
 Elitist Reproduction on Individual
                                 9 #############
############## Generation
         Binary Code
                                    Paraml Param2 Fitness
```

Average Values: 0.2669 0.6033 0.06783

Average Function Value of Generation - 0.06783
Maximum Function Value - 0.22471

Number of Crossovers = 80

****** Restart micro-population at generation 9 *******

Average Function Value of Generation= 0.04531
Maximum Function Value = 0.22471

Number of Crossovers - 71
Elitist Reproduction on Individual 5

```
11 #################
############### Generation
                                   Paraml Param2 Fitness
        Binary Code
 \tfrac{1-10000001010010010010010111100}{1-100000010100100111100} - \tfrac{0.5025}{0.1425} - \tfrac{0.1425}{0.00016}
 2-0101000100000011000111101111110 0.3164 0.5605 0.00000
 \frac{3-00110001001000101001110101100}{0.1919}
  4 111000010110010000100010101100 0.8805 0.0678 0.02852
 5 000100010010001101001110011100 0.0669 0.6532 0.22471
                                   0.3916 0.4155 0.05091
 Average Values:
 Average Function Value of Generation= 0.05091
                                    -0.22471
 Maximum Function Value
                                72
  Number of Crossovers
  Elitist Reproduction on Individual
                                12 #################
##################### Generation
                                   Param1 Param2 Fitness
         Binary Code
  \frac{1-000100010010001101001110011100}{0.0669}
  2 110100010110001100001110001100 0.8179 0.5277 0.00012
  \frac{3}{101100010110010001001010101100} \frac{0.6930}{0.1459} \frac{0.00004}{0.00004}
  4 001100010010001101001110011100 0.1919 0.6532 0.00115
  5 00010001001000101001110001100 0.0669 0.6527 0.22492
                                    0.3673 0.5266 0.09019
 Average Values:
 Average Function Value of Generation - 0.09019
                                     -0.22492
 Maximum Function Value
  Number of Crossovers
                                67
                                13 #################
Paraml Param2 Fitness
         Binary Code
  \frac{1-001100010010000101001110011100}{0.1919} 0.6532 0.00115
  2 001100010010000101001110011100 0.1919 0.6532 0.00115
  3 000100010010001101001110001100 0.0669 0.6527 0.22492
  4 001100010010001101001110011100 0.1919 0.6532 0.00115
  5 000100010010000101001110001100 0.0669 0.6527 0.22492
                                    0.1419 0.6530 0.09066
 Average Values:
 Average Function Value of Generation= 0.09066
                                     = 0.22492
 Maximum Function Value
                                77
  Number of Crossovers
%%%%%% Restart micro-population at generation 13 %%%%%%
                                14 ################
################# Generation
                                    Param1 Param2 Fitness
         Binary Code
  <del>1 000100010010000101001110001100 0.0669 0.6527 0.22492</del>
  2 01000101101000000001101011101 0.2720 0.0263 0.19778
```

```
http://www.cuaerospace.com/carroll/ga/ga.out
```

3 000001101111110101100000111110 0.0273 0.6894 0.01945 4 101001101011000111110111100100 0.6511 0.9836 0.00012 5 000010000101100100110111010111 0.0326 0.6081 0.01638

0.2100 0.5920 0.09173 Average Values:

Average Function Value of Generation= 0.09173 Maximum Function Value = 0.22492

86 Number of Crossovers Elitist Reproduction on Individual

############### Generation

Param1 Param2 Fitness Binary Code $\tfrac{1 \ 000100010010000101001110001100}{1 \ 000100010010001110001100} \ 0.0669 \ 0.6527 \ 0.22492$ $\frac{2 \cdot 000001111010110000101000011101}{0.0300} \cdot \frac{0.0790}{0.29078}$ $\frac{3-000000101111110101101000101110}{0.0117}$ 4-00000010010000001001111001100 0.0044 0.1547 0.00000 5-0001010100111101010001101111110 0.0829 0.6386 0.16025

0.0392 0.4459 0.13545 Average Values:

Average Function Value of Generation= 0.13545 = 0.29078Maximum Function Value

Number of Crossovers 76 Elitist Reproduction on Individual

16 ################# ############### Generation

Paraml Param2 Fitness Binary Code $\frac{1 - 0001011100\overline{10110001101000011110} - 0.0905}{1 - 0.011100\overline{10110001101000011110}} - 0.0905 - 0.2040 - 0.02422$ 2 000101010011000101001110001100 0.0828 0.6527 0.18437 $\frac{3 + 000001111010110000101000011101}{0.0300} = \frac{0.0790}{0.29078}$ 4 000000111010010001001100001101 0.0142 0.1488 0.00002 5 000001110010110100101110011101 0.0280 0.5907 0.00161 0.0491 0.3351 0.10020

Average Function Value of Generation - 0.10020 -0.29078Maximum Function Value

Number of Crossovers Elitist Reproduction on Individual 2

Average Values:

17 ################ ############## Generation

Binary Code Param1 Param2 Fitness $\frac{1.000001110010110000101000011100}{0.0280} \quad \frac{0.0790}{0.25527}$ 2 000001111010110000101000011101 0.0300 0.0790 0.29078 3 000001111010110001101000011111 0.0300 0.2041 0.01239 4 000101110010110001101000011111 0.0905 0.2041 0.02431 5 000101110010110000101000011100 0.0905 0.0790 0.57101

0.0538 0.1290 0.23075 Average Values:

Average Function Value of Generation= 0.23075

-0.57101

Number of Crossovers = 69
Elitist Reproduction on Individual 3

Average Function Value of Generation - 0.45152
Maximum Function Value = 0.57101

Number of Crossovers = 88

የተያዩተያዩ Restart micro-population at generation 18 ******

Average Function Value of Generation - 0.12465
Maximum Function Value - 0.57101

Number of Crossovers = 72 Elitist Reproduction on Individual 3

Average Function Value of Generation= 0.12011
Maximum Function Value = 0.57101

Number of Crossovers = 72 Elitist Reproduction on Individual 3

```
21 #################
################ Generation
                                        Paraml Param2 Fitness
         Binary Code
  \frac{1-0000100100\overline{10100010101000001100}}{1-0000100010101000001100} \quad 0.0358 \quad 0.3285 \quad 0.00512
  2 000011110010100110101000101100 0.0592 0.8295 0.05316
  3 000101110010110000101000011100 0.0905 0.0790 0.57101
  4-000001110010110000101010001100 0.0280 0.0824 0.23691
  5-0001111000101010101010100001100 0.1178 0.3363 0.00024
                                        0.0663 0.3311 0.17329
 Average Values:
 Average Function Value of Generation= 0.17329
                                         = 0.57101
 Maximum Function Value
                                   72
  Number of Crossovers
  Elitist Reproduction on Individual
                                   ############### Generation
                                        Paraml Param2 Fitness
          Binary Code
  #
  \begin{smallmatrix} 1 & 0000111100 \bar{1}01001001010000111100 & 0.0592 & 0.5790 & 0.00051 \end{smallmatrix}
  \frac{2 \cdot 0001011100101100001010100111100}{0.0905} \cdot \frac{0.0829}{0.52352}
  \frac{3 \cdot 00001111001010001010101010001100}{0.0592} \cdot \frac{0.3324}{0.00522}
                                       0.0905 0.0790 0.57101
  4 000101110010110000101000011100
  \begin{smallmatrix} 5 & 000001110010100001010001111100 \end{smallmatrix} \  \  \, \frac{0.0280}{0.0800} \  \, \frac{0.24931}{0.0800}
                                        0.0655 0.2306 0.26991
 Average Values:
 Average Function Value of Generation= 0.26991
                                         -0.57101
 Maximum Function Value
                                    91
  Number of Crossovers
  Elitist Reproduction on Individual
23 ################
                                        Paraml Param2 Fitness
          Binary Code
  \frac{1-000101110010100000101000111100}{0.0905}
  \frac{2}{2} 000101110010110000101010011100 0.0905 0.0829 0.52352
  \frac{3 + 0001111100101100001010100111100}{0.1218} = \frac{0.0829}{0.05388}
  \frac{4 \cdot 000001110010110000101000011100}{0.0280} \cdot \frac{0.0790}{0.25527}
  5 000101110010110000101000011100 0.0905 0.0790 0.57101
                                         0.0843 0.0807 0.39301
 Average Values:
 Average Function Value of Generation= 0.39301
                                         -0.57101
 Maximum Function Value
                                    68
   Number of Crossovers
                                                        23 8888888
 %%%%%% Restart micro-population at generation
                                    24 ################
                     <del>Generation</del>
 #################
                                         Paraml Param2 Fitness
          Binary Code
```

1 000101110010110000101000011100 0.0905 0.0790 0.57101

```
http://www.cuaerospace.com/carroll/ga/ga.out
```

Average Values: 0.3410 0.5523 0.11921

Average Function Value of Generation= 0.11921
Maximum Function Value = 0.57101

Number of Crossovers = 73 Elitist Reproduction on Individual 3

Binary Code Paraml Param2 Fitness
1 01010110000001001001011001111 0.3360 0.1469 0.00000
2 0011001001001010101110001100 0.1959 0.0902 0.00705
3 00010111001011000101010110 0.4610 0.2682 0.41717
5 00010111001011100111010111100 0.0905 0.4559 0.32995

Average Values: 0.2348 0.2081 0.26504

Average Function Value of Generation= 0.26504
Maximum Function Value = 0.57101

Number of Crossovers = 63
Elitist Reproduction on Individual 2

Binary Code
1 0001011100100010100010100011100
2 0001011100101000101000011100
3 011101110010101010101010001100
4 000101110010110000101010001100
5 011101100010101000110101011010
6 0.0905
6 0.0787
7 0.43583
7 0.0010111001010100011001
7 0.0905
7 0.0824
7 0.00485

Average Values: 0.2397 0.1800 0.41568

Average Function Value of Generation= 0.41568
Maximum Function Value = 0.57101

Number of Crossovers - 79

Binary Code Param1 Param2 Fitness
1 000101110010101010101000011100 0.0905 0.3290 0.00659
2 000101110010110000101000011100 0.0904 0.0824 0.53182
3 000101110010010000101000011100 0.0905 0.0790 0.57101
4 000101110010110000101000011100 0.0904 0.0790 0.57370
5 000101110010110000101000011100 0.0905 0.0790 0.57101

Average Values: 0.0905 0.1297 0.45083

Average Function Value of Generation= 0.45083

Maximum Function -Value

Number of Crossovers = 73

ዩዩዩዩዩዩዩ Restart micro-population at generation 27 ዩዩዩዩዩዩዩ

Average Function Value of Generation= 0.12107

Maximum Function Value = 0.57370

Number of Crossovers = 65
Elitist Reproduction on Individual 4

Average Function Value of Generation= 0.12556
Maximum Function Value = 0.57370

Number of Crossovers = 72
Elitist Reproduction on Individual 2

Average Function Value of Generation - 0.12597
Maximum Function Value - 0.57370

Number of Crossovers = 80 Elitist Reproduction on Individual 5

```
31 #################
################# Generation
                                    Paraml Param2 Fitness
        Binary Code
  #
 \frac{1~0001011100\overline{10010001101001011100}}{1~000101110010111100} ~0.0904 ~0.2059 ~0.03095
  2 1001011100100010011010011111100 0.5904 0.2069 0.00029
 \frac{3 - 010101110010010000111000111101}{0.3404} = \frac{0.1112}{0.00015}
  4 - 100101100010010000101001011100 0.5865 0.0809 0.00235
  5 000101110010010000101000011100 0.0904 0.0790 0.57370
                                    0.3396 0.1368 0.12149
 Average Values:
 Average Function Value of Generation- 0.12149
                                     = 0.57370
 Maximum Function Value
                                75
  Number of Crossovers
                                32 ################
                  <del>Generation</del>
################
                                    Paraml Param2 Fitness
         Binary Code
  {\color{red}1\phantom{-}000101110010010000101000011100}\phantom{-}0.0904\phantom{-}0.0790\phantom{-}0.57370\phantom{-}0}
  \frac{3-000101110010010000101001011100}{0.0904}
  4 + 100101100010010000101000011100 + 0.5865 + 0.0790 + 0.00245
  5-000101110010010001101001011100 \quad 0.0904 \quad 0.2059 \quad 0.03095
                                     0.1888 0.1048 0.36312
 Average Values:
 Average Function Value of Generation= 0.36312
 Maximum Function Value
                                     -0.65745
                                 66
  Number of Crossovers
                                     ################ Generation
                                 33
                                     Param1 Param2 Fitness
         Binary Code
                                     0.0904 0.2040 0.02414
  1 000101110010010001101000011100
  2-000101100010010000101000011100 0.0865 0.0790 0.65745
  3 000101110010010001101000011100 0.0904 0.2040 0.02414
                                    0.0904 0.0790 0.57370
  4 000101110010010000101000011100
                                     0.0904 0.0790 0.57370
  5-000101110010010000101000011100
                                     0.0896 0.1290 0.37062
 Average Values:
 Average Function Value of Generation= 0.37062
                                      -0.65745
 Maximum Function Value
  Number of Crossovers
  Elitist Reproduction on Individual
                                                   33 %%%%%%
 %%%%%%% Restart micro-population at generation
                                 34 ################
 ################
                    Generation
                                     Paraml Param2 Fitness
         Binary Code
   1 000101100010010000101000011100 0.0865
                                             0.0790 0.65745
   2 001110111001101110111010100110 0.2328 0.8645 0.02375
```

```
http://www.cuaerospace.com/carroll/ga/ga.out
```

 3
 1110000001011010101011110000110
 0.8764
 0.3400
 0.00003

 4
 0010010011100101111100100100101
 0.1280
 0.9465
 0.00000

 5
 001001110101001010110011010
 0.1536
 0.2938
 0.00001

Average Values: 0.2955 0.5047 0.13625

Average Function Value of Generation - 0.13625
Maximum Function Value = 0.65745

Number of Crossovers = 69 Elitist-Reproduction-on-Individual 1

Binary Code Param1 Param2 Fitness
1-0001011000100101000011100 0.0865 0.0790 0.65745
2-001101110010001001011110011110 0.2154 0.0595 0.12518
3-00110111101001010010100101 0.2181 0.2863 0.08669
4-0010011001110110110110011100 0.1502 0.3563 0.00000
5-001001100001000000111110011010 0.1487 0.1219 0.00002

Average Values: 0.1638 0.1806 0.17387

Average Function Value of Generation= 0.17387
Maximum Function Value = 0.65745

Number of Crossovers = 83 Elitist Reproduction on Individual 5

Average Values: 0.1401 0.0617 0.21879

Average Function Value of Generation= 0.21879
Maximum Function Value = 0.65745

Number of Crossovers = 86 Elitist Reproduction on Individual 3

Binary Code Param1 Param2 Fitness
1 000101101111010000111010010110 0.0897 0.1140 0.09775
2 0001011000100000101000011110 0.0862 0.0790 0.66297
3 00010110010010000101000011100 0.0865 0.0790 0.65745
4 00010111011010000111000011100 0.0994 0.0790 0.57370
5 0001011011111010000111010010110 0.0897 0.1140 0.09775

Average Values: 0.0885 0.0930 0.41793

Average Function Value of Generation= 0.41793

Number of Crossovers - 75

Average Function Value of Generation 0.54695
Maximum Function Value = 0.66297

Number of Crossovers - 70

Average Function Value of Generation= 0.66060
Maximum Function Value = 0.66672

Number of Crossovers - 58

Average Function Value of Generation= 0.66447
Maximum Function Value = 0.66797

Number of Crossovers - 76

%%%%%% Restart micro-population at generation 40 %%%%%%%

```
http://www.cuaerospace.com/carroll/ga/ga.out
                                   Paraml Param2 Fitness
        Binary Code
 \frac{1 - 0001011000000000000101000011110}{1 - 0001011000011110} - 0.0859 - 0.0790 - 0.66797
 <del>2 100010101111011111000110101100 0.5428 0.8881 0.00000</del>
 3 00011010110110100010001000001 0.1052 0.5332 0.00030
 4 1110111101011101111110000010110 0.9350 0.9695 0.00000
 \frac{5-01111000110000110110110101101111}{0.4717}
                                   0.4281 \quad 0.6357 \quad 0.13478
Average Values:
Average Function Value of Generation= 0.13478
                                    -0.66797
Maximum Function Value
 Number of Crossovers
                               69
 Elitist-Reproduction on Individual
Paraml Param2 Fitness
        Binary Code
 #
 \frac{1}{1} \cdot \frac{1001011001\overline{1100111001110001110}}{0.5877} \cdot \frac{0.4497}{0.00169}
 \frac{2}{2} 00011010100000000101000011111 0.1035 0.0791 0.29375
  \frac{3-101010001100001111101010111110}{0.6592}
  4 000101100000000000101000011110 0.0859 0.0790 0.66797
  5 100010100110011001000000111100 0.5406 0.1268 0.00000
                                    0.3954 0.3387 0.19268
 Average Values:
 Average Function Value of Generation= 0.19268
                                    =-0.66797
 Maximum Function Value
  Number of Crossovers
  Elitist Reproduction on Individual
                                43 ################
Paraml Param2 Fitness
        Binary Code
  \frac{1\ 000101100010000001101010001110}{0.0864}
  2-00010110011100101010100100011110 0.0877 0.3212 0.02359
  \frac{3 \cdot 0001011000000000000101000011110}{0.0859} \cdot \frac{0.0790}{0.66797}
  4 000101100100000011100000001110 0.0869 0.4379 0.28284
  5-1001001000110010101010101011110 0.5711 0.3330 0.00000
                                    0.1836 0.2757 0.20342
 Average Values:
 Average Function Value of Generation= 0.20342
                                     -0.66797
 Maximum Function Value
  Number of Crossovers
  Elitist Reproduction on Individual
                                44 #################
################### Generation
                                    Paraml Param2 Fitness
        Binary Code
  1 000101100000000000101000011110 0.0859 0.0790 0.66797
  <del>2 000101100110000001101000001110 0.0874 0.2036 0.02538</del>
  3 000101100110000010100000011110 0.0874 0.3134 0.05935
                                    0.0869 0.4575 0.37484
  4 000101100100000011101010001110
```

5 00010110000000011101000001110 0.0859 0.4536 0.38353

Average Values:

0.0867 0.3014 0.30221

Average Function Value of Generation= 0.30221
Maximum Function Value = 0.66797

Number of Crossovers = 82

Average Values: 0.0859 0.2552 0.43109

Average Function Value of Generation= 0.43109
Maximum Function Value = 0.67412

Number of Crossovers - 68

%%%%%% Restart micro-population at generation 45 %%%%%%

Average Function Value of Generation= 0.13565
Maximum Function Value = 0.67412

Number of Crossovers = 81
Elitist Reproduction on Individual 1

Average Function Value of Generation= 0.16292
Maximum Function Value = 0.67412

Number of Crossovers = 66
Elitist Reproduction on Individual

################ Generation 48 ################### Paraml Param2 Fitness Binary Code 1 00010110000000000101000001110 0.0859 0.0786 0.67412 2 000100010000000101000000101011 0.0664 0.6263 0.13309 3 00010000000000000001000001010 0.0625 0.0159 0.10110 4 010101111000000000000001001010 0.3418 0.0023 0.00001 5 000101110000000101101000001010 0.0898 0.7035 0.01507 0.1293 0.2853 0.18468 Average Values:

Average Function Value of Generation - 0.18468
Maximum Function Value - 0.67412

Number of Crossovers = 70 Elitist Reproduction on Individual 4

Average Function Value of Generation - 0.17738
Maximum Function Value - 0.67412

Number of Crossovers ≈ 68 Elitist Reproduction on Individual 3

Average Function Value of Generation = 0.66804
Maximum Function Value = 0.98354

Number of Crossovers - 66
Elitist Reproduction on Individual 1

```
http://www.cuaerospace.com/carroll/ga/ga.out
```

Average Values: 0.0836 0.0636 0.77344

Average Function Value of Generation - 0.77344
Maximum Function Value - 0.98354

Number of Crossovers = 70 Elitist Reproduction on Individual 1

%%%%%% Restart micro-population at generation 51 %%%%%%%

Average Values: 0.5036 0.2993 0.19704

Average Function Value of Generation= 0.19704
Maximum Function Value = 0.98354

Number of Crossovers - 78
Elitist Reproduction on Individual 2

Average Values: 0.1755 0.2102 0.22770

Average Function Value of Generation= 0.22770

Maximum Function Value = 0.98354

Number of Crossovers = 83 Elitist Reproduction on Individual 2

##################	Generation	54	#############			
# Binary Co	de		Paraml	Param2	Fitness	
1 00101010100001		L 000	0.1661	0.4768	0.00000	
2-0001001000000			0.0703	0.0638	0.98354	
3 0011101000000			0.2266	0.1888	0.00078	
4 00000010000001	000000000010	1000	0.0079	0.0012	0.00059	
5 0001101000000			0 1016	0 3529	0.0000	

```
Average Values:
```

0.1145 0.2167 0.19698

0.0953 0.1919 0.30077

Average Function Value of Generation= 0.19698 Maximum Function Value -0.98354

78 Number of Crossovers Elitist Reproduction on Individual

55 ################ ############### Generation Paraml Param2 Fitness Binary Code # 1 00011010000000011110000101010 0.1016 0.4700 0.16761 2 00011010000000010100100101010 0.1016 0.3216 0.01180 3-000100100000000000100000101010 0.0703 0.0638 0.983545-00010010000000000110100101011 0.0703 0.1029 0.34068

Average Values:

Average Function Value of Generation= 0.30077 Maximum Function Value = 0.98354

80 Number of Crossovers Elitist Reproduction on Individual

56 ################ ############### Generation Paraml Param2 Fitness Binary Code $\frac{1}{1}$ 000110100000000011100000101010 0.1016 0.4388 0.14865 2 000110100000000000100000101010 0.1016 0.0638 0.37014 3-00011010000000001110000101010 0.1016 0.2200 0.07195 4-000100100000000000100000101010 0.0703 0.0638 0.98354 5-00011010000000001100000101010 0.1016 0.1888 0.00095 0.0953 0.1950 0.31505 Average Values:

Average Function Value of Generation- 0.31505 -0.98354Maximum Function Value

70 Number of Crossovers

57 ################# Paraml Param2 Fitness Binary Code $\frac{1.000110100000000000100000101010}{0.1016}$ 2 00011010000000011100000101010 0.1016 0.4388 0.14865 3 00010010000000001100000101010 0.0703 0.1888 0.00254 4 000110100000000000100000101010 0.1016 0.0638 0.37014 5 00010010000000000100000101010 0.0703 0.0638 0.98354 0.0891 0.1638 0.37500 Average Values:

Average Function Value of Generation= 0.37500 -0.98354Maximum Function Value

75 Number of Crossovers

```
57 %%%%%%
%%%%%% Restart micro-population at generation
                                  58 #################
############### Generation
                                       Paraml Param2 Fitness
         Binary Code
  \frac{1\ 0001001000000000000100000101010}{0.0703}
  <del>2 1111111110001010111110110110010 0.9982 0.4820 0.00091</del>
  3 111110000101100111110101101110 0.9701 0.9799 0.00000
  4 011000000110101010111101101110 0.3766 0.3706 0.00000
  5 000011111100101110100011001000 0.0617 0.8186 0.03601
                                       0.4954 0.5430 0.20409
 Average Values:
 Average Function Value of Generation = 0.20409
 Maximum Function Value
                                        -0.98354
  Number of Crossovers
  Elitist Reproduction on Individual
                                  59 ################
################
                    Generation
                                       Paraml Param2 Fitness
         Binary Code
  \begin{smallmatrix} 1 & 0001001000000000000100000101010 \end{smallmatrix} \quad \begin{smallmatrix} 0.0703 & 0.0638 & 0.98354 \end{smallmatrix}
  \frac{2000011101100101000100001101000}{2000011010000} = \frac{0.0578}{0.0657} = \frac{0.93723}{0.0657}
  3 000010100100100100100011101010 0.0402 0.5697 0.00001
  4 000110100101100101110101101110 0.1029 0.7299 0.00012
  \begin{smallmatrix} 5 & 11111010000010001010010010010010 & 0.9767 & 0.3214 & 0.00001 \end{smallmatrix}
                                       0.2496 0.3501 0.38418
 Average Values:
 Average Function Value of Generation= 0.38418
                                        = 0.98354
 Maximum Function Value
  Number of Crossovers
  Elitist-Reproduction on Individual
60 ################
                    <del>Generation</del>
                                       Param1 Param2 Fitness
         Binary Code
  \frac{1-000010100100100100100011101010}{0.0402} \quad \frac{0.5697}{0.00001}
  <del>2 00011010010010010010010101010 0.1027 0.5677 0.00000</del>
  3 00010010000100001100000101010 0.0704 0.1888 0.00253
  4 000100100000000000100000101010 0.0703 0.0638 0.98354
                                       0.0421 0.0696 0.61152
  5-000010101100100000100011101000
                                       0.0651 0.2919 0.31952
 Average Values:
 Average Function Value of Generation = 0.31952
 Maximum Function Value
                                        -0.98354
  Number of Crossovers
  Elitist Reproduction on Individual
############### Generation
                                 61 ################
                                       Paraml Param2
                                                        Fitness
         Binary Code
```

http://www.cuaerospace.com/carroll/ga/ga.out 0.0734 0.1927 0.00580 1 000100101100100001100010101010 $\frac{2000100100000000000100000101010}{0.0703}$ 3 000010101100100000100011101010 0.0421 0.0696 0.61136 4-00010010010000000010001010101010 0.0713 0.0677 0.984145-00010010000000001100000101010 0.0703 0.1888 0.002540.0655 0.1165 0.51748 Average Values: Average Function Value of Generation= 0.51748 Maximum Function Value 71 Number of Crossovers 62 ################## Paraml Param2 Fitness Binary Code $\frac{1 \cdot 000100100100100001100010101010}{0 \cdot 0714} = \frac{0.1927}{0 \cdot 00590}$ $\frac{2 \cdot 000100100100000000100000101010}{0.0713} \cdot \frac{0.0638}{0.97764}$ $\frac{3 \cdot 000100100000000000000100010101010}{0.0703} \cdot \frac{0.0677}{0.99008}$ $4 \quad 000100100100000000100010101010 0.0713 \quad 0.0677 \quad 0.98414$ 5 00000101100100000100010101010 0.0109 0.0677 0.05831 0.0590 0.0919 0.60321 Average Values: Average Function Value of Generation= 0.60321 Maximum Function Value = 0.9900885 Number of Crossovers %%%%%% Restart micro-population at generation 62 8888888 63 ################## ################ Ceneration Param1 Param2 Fitness Binary Code $\frac{1000100100000000000100010101010}{0.0703}$ 2 111011111101110111100000000100 0.9370 0.9377 0.00000 $\frac{3}{111011010011100010010010011110101}$ $\frac{0.9267}{0.2887}$ $\frac{0.00004}{0.00004}$ 4-110110011100011100011100111101 0.8507 0.5566 0.000005 110101010001111100001001111010 0.8325 0.5194 0.00083 0.7234 0.4740 0.19819Average Values: Average Function Value of Generation - 0.19819 Maximum Function Value -0.99008Number of Crossovers Elitist Reproduction on Individual 64 ################ Paraml Param2 Fitness Binary Code 1 100100010000101100101011111010 0.5666 0.5858 0.00000 2 011100000010000010010010100101 0.4380 0.2863 0.20530

 Average Values:

0.3932 0.1926 0.27326

Average Function Value of Generation= 0.27326 -0.99008Maximum Function Value

77 Number of Crossovers Elitist Reproduction on Individual

65 ################ ################### Generation Param1 Param2 Fitness Binary Code 1 000100010000000000101010101010 0.0664 0.0833 0.80811 2 01010010000010000100010111010 0.3204 0.0682 0.03682 $\frac{3}{01110001000100100100101010101010}$ $\frac{0.4417}{0.3021}$ $\frac{0.09533}{0.09533}$ 4 000100100000000000100010101010 0.0703 0.0677 0.99008 5 111100010000000010010010100101 0.9414 0.2863 0.00000

0.3681 0.1615 0.38607 Average Values:

Average Function Value of Generation= 0.38607 - 0.99008 Maximum Function Value

Number of Crossovers = Elitist Reproduction on Individual

Param1 Param2 Fitness Binary Code $\frac{1\ 001100100000000000000010101010}{0.0052}\ 0.0052$ 2 0101001000010000100010111010 0.3204 0.0682 0.03682 $\frac{3 000100100000000000100010101010}{0.0703}$ 4 000100010000000000100010101010 0.0664 0.0677 0.99929 5 0001000100000000000100010101010 0.0664 0.0677 0.99929 0.1438 0.0553 0.60515

Average Function Value of Generation = 0.60515 - 0.99929 Maximum Function Value

64 Number of Crossovers

Average Values:

****** Restart-micro-population at-generation 66 ******

67 ################# ############## Generation Paraml Param2 Fitness Binary Code 1 000100010000000000100010101010 0.0664 0.0677 0.99929 2 110010000100000000001001010000 0.7823 0.0181 0.00011 3 001111000000001011101111101001 0.2344 0.4681 0.21614 4 001001101100111101010000100101 0.1516 0.6574 0.00002 5 1010101010101100111111110001100 0.6667 0.4965 0.02681 0.3803 0.3415 0.24847 Average Values:

Average Function Value of Generation= 0.24847 - 0.99929 Maximum Function Value

Number of Crossovers = 59 Elitist Reproduction on Individual 4

```
###################
                   Generation
###############
                                     Paraml Param2
                                                      Fitness
         Binary Code
                                                      0.0000
    100011000100001010001001001001
                                     0.5479 0.2679
  <del>2 000100000000001011100011101001</del>
                                     0.0625 0.4446 0.45230
                                     0.2351 0.4651 0.23296
  3-001111000010111011101110001001
  4 000100010000000000100010101010
                                     0.0664
                                              0.0677
                                                      0.99929
                                                      0.08201
                                     0.6641 0.4739
  5 101010100000010011110010101000
                                                      0.35331
                                      0.3152 0.3438
 Average Values:
 Average Function Value of Generation- 0.35331
                                       = 0.99929
 Maximum Function Value
  Number of Crossovers
                                 aΩ
  Elitist Reproduction on Individual
                                     ###################
###################
                   Generation
                                      Paraml Param2
                                                     Fitness
  #
         Binary Code
                                      0.1882 0.4573 0.00115
  1 001100000010111011101010001001
  <del>2 100110110000000001110010101000</del>
                                     0.6055 0.2239 0.00859
  \frac{3 + 000000100000100001000101010101}{0.0040} = \frac{0.0677}{0.02283}
  4-0001000100000000010001010101010
                                     0.0664 0.0677 0.99929
                                      0.2188 0.2005 0.00401
  5 0011100000000100110011010101
                                      0.2166 0.2034 0.20718
 Average Values:
 Average Function Value of Generation= 0.20718
                                       -0.99929
 Maximum Function Value
                                 67
  Number of Crossovers
############# Generation
                                      ####################
                                 70
                                      Paraml Param2 Fitness
         Binary Code
                                              0.2239 0.00000
                                      <del>0.5665</del>
  \frac{1-10010001000010001110010101000}{1-100100010100001110010101000}
                                                      0.99929
  <del>2-000100010000000000100010101010</del>
                                     0.0664 0.0677
                                                      0.24466
                                      0.0742 0.2239
  3 000100110000000001110010101000
                                                      0.12604
  4 000110110000000000110010101000
                                      0.1055
                                              0.0989
  5 001110000000000001100110101011
                                      0.2188 0.2005 0.00404
                                      0.2063 0.1630 0.27481
 Average Values:
 Average Function Value of Generation= 0.27481
                                       -0.99929
 Maximum Function Value
                                  76
  Number of Crossovers
  Elitist Reproduction on Individual
#################
                                      ##################
                    Generation
```

Binary Code

000100010000000000100010101010

Paraml Param2

0.0677

0.0664

Fitness

0.99929

```
http://www.cuaerospace.com/carroll/ga/ga.out
```

Average Values: 0.0898 0.1521 0.45275

Average Function Value of Generation= 0.45275
Maximum Function Value = 0.99929

Number of Crossovers = 71

Average Values: 0.0656 0.1021 0.67670

Average Function Value of Generation - 0.67670
Maximum Function Value - 0.99929

Number of Crossovers - 75
Elitist Reproduction on Individual 1

Average Function Value of Generation= 0.75027
Maximum Function Value = 0.99929

Number of Crossovers = 80 Elitist Reproduction on Individual 5

Average Function Value of Generation= 0.96535

Number of Crossovers = 68
Elitist Reproduction on Individual 4

Average Function Value of Generation - 0.96535
Maximum Function Value - 0.99929

Number of Crossovers = 72 Elitist Reproduction on Individual

%%%%%% Restart micro-population at generation 75 %%%%%%%

Average Function Value of Generation - 0.20803
Maximum Function Value - 0.99929

Number of Crossovers - 72
Elitist Reproduction on Individual

Average Function Value of Generation= 0.31591
Maximum Function Value = 0.99929

Number of Crossovers = 83

Elitist Reproduction on Individual

################# Generation 78 ################# Paraml Param2 Fitness Binary Code 1 010100101010110010101110101010 0.3229 0.3411 0.00002 2 000100010000000000100010101010 0.0664 0.0677 0.99929 3 000100000000000000010110101010 0.0625 0.0442 0.65745 0.0682 0.0854 0.76094 4 000100010111100000101011101111 5 110100001000010000100010101010 0.8145 0.0677 0.02958 0.2669 0.1212 0.48946 Average Values:

Average Function Value of Generation= 0.48946 = 0.99929Maximum Function Value

75 Number of Crossovers Elitist Reproduction on Individual

################# 79 ################ Generation Paraml Param2 Fitness Binary Code 1 000100010000000000100110101010 0.0664 0.0755 0.94312 2 00010001100001010110101010 0.0668 0.0853 0.76555 3 0001000100111000001010101011110 0.0673 0.0834 0.80553 4 000100010000000000100010101010 0.0664 0.0677 0.99929 5 000100010011000000100010101010 0.0671 0.0677 0.99936 0.0668 0.0759 0.90257 Average Values:

Average Function Value of Generation = 0.90257 -0.99936Maximum Function Value

Number of Crossovers 64 Elitist Reproduction on Individual

80 ################# ############### Generation Paraml Param2 Fitness Binary Code $\frac{1-000100010001000000100010101010}{0.0667} \quad \frac{0.0677}{0.0677} \quad \frac{0.99940}{0.0677}$ $\frac{3.00010001000010000101010101110}{0.0665}$ 4 000100010011000000100010101010 0.0671 0.0677 0.99936 5 000100010001000000100010101010 0.0667 0.0677 0.99940 0.0667 0.0708 0.96061 Average Values:

Average Function Value of Generation - 0.96061 -0.99940Maximum Function Value

72 Number of Crossovers

****** Restart micro-population at generation

Paraml Param2 Fitness Binary Code

```
http://www.cuaerospace.com/carroll/ga/ga.out
```

Average Values:

0.5122 0.2125 0.20034

Average Function Value of Generation= 0.20034
Maximum Function Value = 0.99940

Number of Crossovers = 73 Elitist Reproduction on Individual 3

Binary Code 1 00000011001000010100101011 0 0.5061 0.3216 0.00204 0.00100100100100101101 0 0.6405 0.3142 0.01565 0.00100100100000101010101 0 0.0667 0.0677 0.99940 0.01001110110010000101010101 0 0.0764 0.3177 0.04817 5 110111111001110001100010111001 0 0.8735 0.1932 0.00026

Average Values: 0.4326 0.2429 0.21310

Average Function Value of Generation= 0.21310
Maximum Function Value = 0.99940

Number of Crossovers - 75
Elitist Reproduction on Individual 2

Binary Code Paraml Param2 Fitness
1 001100111101000010100010101010 0.2024 0.3177 0.00157
2 000100010001000000100010101010 0.0667 0.0677 0.99940
3 100100011011110001010010101010 0.5692 0.3177 0.00000
4 100000011111100000100010111110 0.5077 0.0683 0.05532
5 100000011001100000100000110110 0.5062 0.0641 0.06350

Average Values: 0.3704 0.1671 0.22396

Average Function Value of Generation 0.22396
Maximum Function Value = 0.99940

Number of Crossovers = 74
Elitist Reproduction on Individual 1

Binary Code Param1 Param2 Fitness
1 000100010001000000100010101010 0.0667 0.0677 0.99940
2 0001000110010000010000010010 0.0686 0.0637 0.98983
3 100000010011000000100101010 0.5047 0.0677 0.07389
4 10000001101110000010010110110 0.5067 0.0681 0.06088
5 10000001011110000010010111010 0.5058 0.0682 0.06676

Average Values: 0.3305 0.0671 0.43815

http://www.cuacrospace.com/carroll/ga/ga.out Average Function Value of Generation= 0.43815 -0.99940Maximum Function Value 81 Number of Crossovers 85 ################ Paraml Param2 Fitness Binary Code $\frac{1 \cdot 000100010001000000100010101110}{1 \cdot 0.0667} \cdot 0.0678 \cdot 0.99923}$ 2 000100010011000000100010101010 0.0671 0.0677 0.99936 3 100100011011000000100000100110 0.5691 0.0637 0.00002 4 00010001000100000100010101010 0.0667 0.0677 0.99940 $\begin{smallmatrix} 5 & 0001000100010000001000101010101 \end{smallmatrix} \quad \begin{smallmatrix} 0.0667 & 0.0677 & 0.99940 \end{smallmatrix}$ 0.1672 0.0669 0.79948 Average Values: Average Function Value of Generation= 0.79948 -0.99940Maximum Function Value 75 Number of Crossovers %%%%%% Restart micro-population at generation 86 ################ ############### Generation Paraml Param2 Fitness Binary Code 1 - 00010001000100000010001010101010 0.0667 0.0677 0.999402 111101010110111111111101011100011 0.9587 0.9601 0.00000 3 100011110110000111100000010001 0.5601 0.9380 0.00000 4 1101111111011000000000000101101 0.8744 0.0014 0.00058 5 100011010001110001001010000010 0.5512 0.1446 0.00000 0.6022 0.4224 0.20000 Average Values:

Average Function Value of Generation 0.20000

Maximum Function Value = 0.99940

Number of Crossovers = 81
Elitist Reproduction on Individual 5

Average Function Value of Generation= 0.20024

Maximum Function Value = 0.99940

Number of Crossovers = 87

```
88 #################
############## Generation
                                    Paraml Param2 Fitness
        Binary Code
 1 10010101000100000100000101010 0.5823 0.0638 0.00117
                                    0.6165 0.1255 0.00329
 2 100111011101000001000000001111
 3 00011001010100000000010101010 0.0989 0.0052 0.01192
 4 010100010101000000000010001011 0.3176 0.0042 0.00124
                                    0.0667 0.0677 0.99940
 5 000100010001000001000101010101
                                    0.3364 0.0533 0.20341
Average Values:
Average Function Value of Generation= 0.20341
                                     -0.99940
Maximum Function Value
 Number of Crossovers
 Elitist Reproduction on Individual
#################
                 <del>Generation</del>
                                    ###################
                                    Paraml Param2 Fitness
        Binary Code
 \begin{smallmatrix} 1 & 0.00100010101000001000010101110 & 0.0676 & 0.1303 & 0.02076 \end{smallmatrix}
 \frac{2000100010101000000000010101010}{20001010101010}
  3 100101010001000001100000001110 0.5823 0.1879 0.00000
  4 - 000100010001000000000010101010 0.0667 0.0052 0.02742
  5 0001000100010000010001010101010
                                    0.0667 0.0677
                                                    0.99940
                                    0.1702 0.0793 0.21500
Average Values:
Average Function Value of Generation- 0.21500
                                     -0.99940
Maximum Function Value
                                75
 Number of Crossovers
%%%%%% Restart micro-population at generation
                                                     <del>888888</del>
                                                  89
                                90 ################
############# Generation
                                    Paraml Param2 Fitness
        Binary Code
                                    0.0667 0.0677 0.99940
  1 0001000100010000010001010101010
  2 111011100110001000000111101010 0.9312 0.0150 0.00000
  3 000110001000010101011000100101 0.0958 0.6730 0.08067
  4 - 0.01110000010101100101100011001 0.2194 0.5867 0.00052
  5 000001010000000000101010000011 0.0195 0.0821 0.12108
                                    0.2665 0.2849 0.24034
Average Values:
Average Function Value of Generation= 0.24034
                                     -0.99940
Maximum Function Value
 Number of Crossovers
 Elitist Reproduction on Individual
```

Generation

Fitness

###############

Binary Code

```
http://www.cuaerospace.com/carroll/ga/ga.out
```

 $\frac{2 \cdot 000001010001000000100010000011}{0.0198} \cdot \frac{0.0665}{0.14865}$ 3 00010001000100010010010001001 0.0667 0.5706 0.00003 4 001110010001001000101000111001 0.2229 0.0799 0.20940 $\frac{5 \cdot 00000010001000000101010001010}{0.0042} = \frac{0.0823}{0.01946}$

Average Values:

0.0760 0.1734 0.27539

Average Function Value of Generation = 0.27539 -0.99940Maximum Function Value

72 Number of Crossovers

Elitist Reproduction on Individual

92 ################ ################## Generation

Paraml Param2 Fitness Binary Code $\frac{1.00111001000100000100010111010}{0.2229} \quad \frac{0.0682}{0.23824}$ $\frac{2 \cdot 001100010001001000100000101001}{0 \cdot 1917} \cdot \frac{0 \cdot 0638}{0 \cdot 00485}$ $\frac{3-001011010001001000100000101011}{0.1761}$ 4-000100010001000000100010101010 0.0667 0.0677 0.999405 000110010001001000101000111001 0.0979 0.0799 0.40061

0.1510 0.0687 0.32863 Average Values:

Average Function Value of Generation= 0.32863 -0.99940Maximum Function Value

Number of Crossovers Elitist Reproduction on Individual

93 ################ ############### Generation

Paraml Param2 Fitness Binary Code 1 000100010001001000101010111010 0.0667 0.0838 0.79780 $\textcolor{red}{2 \cdot 00111001000100000100000111001} \quad \textcolor{red}{0.2229} \quad \textcolor{red}{0.0642} \quad \textcolor{red}{0.23733}$ 3 000100010001000000100010101000 0.0667 0.0676 0.99948 4 + 001110010001000000101000111001 + 0.2229 + 0.0799 + 0.208955 00010001000100000100010101010 0.0667 0.0677 0.99940

0.1292 0.0726 0.64860 Average Values:

Average Function Value of Generation - 0.64860 -0.99948Maximum Function Value

Number of Crossovers Elitist Reproduction on Individual 3

94 ################

############### Generation Paraml Param2 Fitness Binary Code 1 000100010001000000101010101010 0.0667 0.0833 0.80821 2 00110001000100000100000101000 0.1917 0.0637 0.00481 3 000100010001000000100010101000 0.0667 0.0676 0.99948 4 00111001000100000100000101010 0.2229 0.0638 0.23686 0.0667 0.0837 0.79911 5 00010001000100000101010111000

0.1229 0.0724 0.56969 Average Values:

```
Average Function Value of Generation- 0.56969
                                   -0.99948
Maximum Function Value
                              75
 Number of Crossovers
%%%%%% Restart micro-population at generation 94 %%%%%%
                               95 ################
################## Generation
                                   Paraml Param2 Fitness
        Binary Code
 \frac{1 \cdot 000100010001000000100010101000}{0.0667} \cdot 0.0676 \cdot 0.99948}
 4 - 011110110010111000101011101101 - 0.4812 - 0.0854 - 0.24615
 5 100101000001111110010010000010 0.5786 0.7852 0.00000
                                   0.3470 0.4975 0.26153
 Average Values:
 Average Function Value of Generation= 0.26153
                                    = 0.99948
 Maximum Function Value
 Number of Crossovers
                               87
  Elitist Reproduction on Individual
############## Generation
                               96 ################
                                   Paraml Param2 Fitness
        Binary Code
  \begin{smallmatrix} 1 & 000111110010111010111010100100 \end{smallmatrix} \quad \begin{smallmatrix} 0.1218 & 0.3644 & 0.00000 \end{smallmatrix}
  2 10010000001011110110010101010 0.5629 0.8490 0.00000
  3 000110010011001000100110100000 0.0984 0.0752 0.42211
  4 00010001000100000100010101000 0.0667 0.0676 0.99948
  5 000111010011000000111101110010 0.1140 0.1207 0.01099
                                   0.1927 0.2954 0.28652
 Average Values:
 Average Function Value of Generation= 0.28652
                                    -0.99948
 Maximum Function Value
                               77
  Number of Crossovers
  Elitist Reproduction on Individual
                               97 ################
Paraml Param2 Fitness
         Binary Code
  1 000110010001001000100010101000 0.0979 0.0676 0.45717
  2 000110010011001000111101110000 0.0984 0.1206 0.03357
  \frac{3 \cdot 000100010011001000100010100000}{0.0672} \cdot \frac{0.0674}{0.99967}
                                   0.5667 0.8490 0.00000
  4 100100010001001110110010101010
  5 00010001000100000100010101000
                                   0.0667 0.0676 0.99948
                                   0.1794 0.2344 0.49798
 Average Values:
```

http://www.cuaerospace.com/carroll/ga/ga.out (29 of 64) [6/26/2001 4:58:31 PM]

-0.99967

Average Function Value of Generation= 0.49798

Maximum Function Value

```
Number of Crossovers = 67
Elitist Reproduction on Individual 1
```

```
################ Generation
                              98 ################
                                 Paraml Param2 Fitness
        Binary Code
 \frac{2 \cdot 000100010011001000100010101000}{0.0672} \cdot \frac{0.0676}{0.99942}
 \frac{3 - 000100010011001000100010101000}{0.0672} = \frac{0.0676}{0.99942}
 4 000110010001000000111100111000 0.0979 0.1189 0.04160
 5 000100010011001000100010101000 0.0672 0.0676 0.99942
                                  0.0733 0.0778 0.80791
Average Values:
 Average Function Value of Generation= 0.80791
                                  -0.99967
 Maximum Function Value
                              72
 Number of Crossovers
```

%%%%%% Restart micro-population at generation 98 %%%%%%

Average Function Value of Generation= 0.19996
Maximum Function Value 4 0.99967

Number of Crossovers = 81 Elitist Reproduction on Individual 1

######################################	100010001010		***************************************	####### Param2 0.0674 0.1965	## Fitness 0.99967 0.00000
3 00010011100110			0.0766	0.5742	0.00012
4 01011000001101			0.3446	0.4544	0.00011
5 01011001001101	100010101010	0001	0.3485	0.0830	0.00004
Average Values:			0.2363	0.2751	0.19999

Average Function Value of Generation= 0.19999
Maximum Function Value = 0.99967

Number of Crossovers = 74
Elitist Reproduction on Individual 5

http://www.cuaerospace.com/carroll/ga/ga.out

Average Values:

Binary Code | Param1 | Param2 | Fitness | 0.101000100110010111010101010 | 0.3172 | 0.4583 | 0.02828 | 0.10100010011011001010101000 | 0.3172 | 0.2083 | 0.00346 | 0.10100000011011001010101000 | 0.3133 | 0.0676 | 0.08362 | 0.001001101101100101110100001 | 0.1082 | 0.5909 | 0.00136 | 0.0010010011001001000100000 | 0.0672 | 0.0674 | 0.99967

0.2246 0.2785 0.22328

Average Function Value of Generation= 0.22328

Average Function Value of Generation= 0.22328

Maximum Function Value = 0.99967

Number of Crossovers = 68
Elitist Reproduction on Individual 4

Binary Code Param1 Param2 Fitness
1 010100010011001001100010101000 0.3172 0.1926 0.00033
2 00010000001100100100010101000 0.0633 0.0676 0.98970
3 01010000001101100110001010000 0.3133 0.1926 0.00050
4 00010001001100100010100000 0.0672 0.0674 0.99967
5 000100000011011000100010100000 0.0633 0.0674 0.999029

Average Values: 0.1649 0.1175 0.59610

Average Function Value of Generation- 0.59610
Maximum Function Value - 0.99967

Number of Crossovers = 80
Elitist Reproduction on Individual 5

Binary Code
1 000100010011011000100010100000
2 0101000000110110011000101010000
3 00010001001101100010010100000
4 0001000000110010001001000000
5 0001000100110010001001000000
5 0001000100110010001001000000
6 0.0672
7 0.0674
7 0.98996

Average Values: 0.1156 0.0924 0.79788

Average Function Value of Generation - 0.79788

Maximum Function Value - 0.99967

Number of Crossovers = 74

****** Restart micro-population at generation 103 ******

```
http://www.cuaerospace.com/carroll/ga/ga.out
```

5 10111110101110101011010101010 0.7450 0.3541 0.00000

Average Values: 0.4228 0.4792 0.20232

Average Function Value of Generation= 0.20232

Maximum Function Value = 0.99967

Number of Crossovers - 74
Elitist Reproduction on Individual 4

5 001110010010001100100111001010 0.2232 0.5765 0.00007

Average Values: 0.2849 0.3715 0.20287

Average Function Value of Generation= 0.20287

Maximum Function Value = 0.99967

Number of Crossovers = 63 Elitist Reproduction on Individual 1

Average Values: 0.1222 0.3750 0.40544

Average Function Value of Generation 0.40544

Maximum Function Value = 0.99967

Number of Crossovers = 73
Elitist Reproduction on Individual 4

Binary Code Paraml Param2 Fitness
1 000100010011001000001000000 0.0672 0.0635 0.99124
2 00011000001100100100100000 0.0945 0.3213 0.01785
3 000100000011001100100010100000 0.0633 0.5674 0.00001
4 0001001001100100100100000 0.0672 0.0674 0.99967
5 000110010011001100100000101000 0.0984 0.5637 0.00000

Average Values: 0.0781 0.3167 0.40175

Average Function Value of Generation= 0.40175

Maximum Function Value = 0.99967

```
71
 Number of Crossovers
 Elitist Reproduction on Individual
****** Restart micro-population at generation 107 *******
Binary Code
                                 Paraml Param2 Fitness
 <del>1 000100010011001000100010100000</del>
                                0.0672 0.0674 0.99967
 2 - 101010100101111000111011110010 0.6654 0.5582 0.00000
 3 00000001101110001011000010110 0.0034 0.1726 0.00000
 4 101010110010100110101100111101 0.6686 0.8378 0.01197
                                0.7039 0.8160 0.00070
 5 101101000011000110100001110001
                                0.4217 0.4904 0.20247
Average Values:
Average Function Value of Generation= 0.20247
Maximum Function Value
                                 -0.99967
 Number of Crossovers
 Elitist Reproduction on Individual
############## Generation 109
                                ###################
                                 Paraml Param2 Fitness
      ' Binary Code
                                0.0672 0.0674 0.99967
 1 000100010011001000100010100000
 2 - 100100010011001110100011100000 0.5672 0.8194 0.00000
 3-001100000011001110100000100000 0.1883 0.8135 0.00006
                                0.0638 0.1411 0.00255
 4 000100000101011001001000010000
 5 001100010011001110100011100000 0.1922 0.8194 0.00021
                                 0.2157 0.5321 0.20050
Average Values:
Average Function Value of Generation- 0.20050
                                 -0.99967
Maximum Function Value
 Number of Crossovers
 Elitist Reproduction-on Individual
                                ################
################ Generation 110
        Binary Code
                                 Param1 Param2 Fitness
 1-000100010011001000100010100000
                                0.0672 0.0674 0.99967
 2 00010001010100100100000000000 0.0677 0.1250 0.04423
                                0.0672 0.3193 0.04237
 3-000100010011001010100011100000
                                0.0633 0.0171 0.11419
 4 000100000011011000001000110000
 0.0658 0.1186 0.43743
Average Values:
Average Function Value of Generation - 0.43743
                                 -0.99967
Maximum-Function Value
 Number of Crossovers
                             74
```

Elitist Reproduction on Individual

```
###################
###############
                  Generation 111
                                   Paraml Param2 Fitness
        Binary Code
                                   0.0667 0.0679 0.99915
 1 000100010001011000100010110000
                                   0.0667 0.1924 0.00564
 <del>2 000100010001001001100010100000</del>
                                   0.0672 0.0674 0.99967
 3 000100010011001000100010100000
                                   0.0677 0.1299
                                                  0.02218
 4 000100010101001001000010100000
                                   0.0633 0.0015 0.01517
 5-000100000011011000000000110000
                                   0.0663 0.0918 0.40836
 Average Values:
 Average Function Value of Generation= 0.40836
 Maximum Function Value
                                    = 0.99967
                               67
  Number of Crossovers
###################
                                   Paraml Param2 Fitness
        Binary Code
                                   0.0667 0.0679 0.99915
  \frac{1 - 0001000100010110001000101\dot{1}0000}{1 - 00010001001000101\dot{1}0000}
                                   0.0672 0.0674 0.99967
  2 000100010011001000100010100000
                                   0.0667 0.0674 0.99976
  3 000100010001011000100010100000
                                   0.0667 0.0054 0.02816
  4 000100010001001000000010110000
                                   0.0633 0.0635 0.98193
  5 000100000011011000100000100000
                                   0.0661 0.0543 0.80174
 Average Values:
 Average Function Value of Generation 0.80174
 Maximum Function Value
                                    = 0.99976
                               72
  Number of Crossovers
  Elitist Reproduction on Individual
                                   ######################
                  Generation 113
################
                                   Paraml Param2 Fitness
         Binary Code
                                   0.0633 0.0674 0.99029
  1 000100000011011000100010100000
                                   0.0667 0.0674 0.99976
  2 000100010001011000100010100000
  3 000100010011011000100010100000
                                   0.0672 0.0674 0.99964
                                   0.0672 0.0674 0.99967
  4 000100010011001000100010100000
  5-000100010011011000100010100000
                                   0.0672 0.0674 0.99964
                                    0.0663 0.0674 0.99780
 Average Values:
 Average Function Value of Generation= 0.99780
 Maximum Function Value
                                    -0.99976
  Number of Crossovers
                                91
%%%%%% Restart micro-population at generation 113 %%%%%%
                   ##################
                                    Paraml Param2 Fitness
         Binary Code
  <del>1 000100010001011000100010100000 0.0667 0.0674 0.99976</del>
                                    0.0385 0.3847 0.00088
  <del>2 000010011101100011000100111100</del>
  3 110110111010100101011011011011 0.8581 0.6786 0.00816
```

```
http://www.cuaerospace.com/carroll/ga/ga.out
```

Average Values: 0.3474 0.4058 0.20231

Average Function Value of Generation= 0.20231
Maximum Function Value = 0.99976

Number of Crossovers = 64 Elitist Reproduction on Individual 4

Average Values: 0.3580 0.4142 0.20696

Average Function Value of Generation= 0.20696
Maximum Function Value = 0.99976

Number of Crossovers = 75
Elitist Reproduction on Individual 5

Average Values: 0.0734 0.3764 0.28149

Average Function Value of Generation - 0.28149

Maximum Function Value - 0.99976

Number of Crossovers = 76
Elitist Reproduction on Individual 1

Binary Code Param1 Param2 Fitness
1 00010001000101100010010100000 0.0667 0.0674 0.99976
2 00010001000101001001010100000 0.0355 0.5674 0.00000
4 00010001100100100010100000 0.0686 0.0674 0.99724
5 00010001000100100010000000 0.0667 0.0635 0.99131

Average Values: 0.0609 0.1697 0.76059

Average Function Value of Generation= 0.76059

Maximum Function Value = 0.99976

```
81
 Number of Crossovers
 Elitist Reproduction on Individual
Paraml Param2 Fitness
       Binary Code
 \frac{1-000100010001000000101010100000}{0.0667}
 2 000100011001011000100010100000 0.0687 0.0674 0.99707
 3 000100010001011000100010100000 0.0667 0.0674 0.99976
 4-00010001000100100100001000000 \quad 0.0667 \quad 0.0635 \quad 0.99131
 5 000100010001000100010100000 0.0667 0.0674 0.99975
                               0.0671 0.0697 0.96050
Average Values:
Average Function Value of Generation - 0.96050
Maximum Function Value
                               = 0.99976
 Number of Crossovers
                           83
 Elitist Reproduction on Individual
<del>ዩዩዩዩዩዩዩ Restart micro-population at generation 118 ዩዩዩዩዩዩዩ</del>
                ################
                               Param1 Param2 Fitness
       Binary Code
 \frac{1 \cdot 000100010001011000100010100000}{1 \cdot 000100010100000} = \frac{0.0667}{0.0674} = \frac{0.99976}{0.0674}
 0.7272 0.6337 0.00011
 4 101110100010101101000100011100
 5 110010110011111001001110011101 0.7939 0.1532 0.00000
                               0.6101 0.3015 0.20242
Average Values:
Average Function Value of Generation= 0.20242
                               -0.99976
 Maximum Function Value
 Number of Crossovers
 Elitist Reproduction on Individual
                ###################
                               Paraml Param2 Fitness
       Binary Code
                               0.2237 0.0241 0.05406
 <del>1 001110010100011000001100010101</del>
                              0.4986 0.1488 0.00003
 2 011111111010011001001100001101
 4 000100010001011000100010100000 0.0667 0.0674 0.99976
                              0.8558 0.2117 0.00608
 5 110110110001011001101100011001
                               0.3929 0.2064 0.21199
 Average Values:
 Average Function Value of Generation= 0.21199
                                -0.99976
 Maximum Function Value
```

2

Elitist Reproduction on Individual

Number of Crossovers

```
################
Paraml Param2 Fitness
       Binary Code
                             0.2240 0.0201 0.03914
 1 001110010101011000001010010001
 2 00010001001011000100010100000 0.0667 0.0674 0.99976
 3 001100010001011000101000000001 0.1917 0.0782 0.00447
 4 001100010101011000100000110100 0.1927 0.0641 0.00600
 0.2812 0.0508 0.20989
Average Values:
Average Function Value of Generation = 0.20989
Maximum Function Value
 Number of Crossovers
                          68
 Elitist Reproduction on Individual
Param1 Param2 Fitness
       Binary Code
                             0.2240 0.0201 0.03946
 \frac{1001110010101011000001010010100}{100000101001001000}
 2 00110001001011000100010110100 0.1917 0.0680 0.00494
 0.0677 0.0674 0.99915
 4 000100010101011000100010100000
                             0.0667 0.0674 0.99976
 5-000100010001011000100010100000
                             0.1546 0.0581 0.45667
Average Values:
Average Function Value of Generation= 0.45667
Maximum Function Value
                              -0.99976
 Number of Crossovers
                          62
                             ###################
################## Generation 123
                             Paraml Param2 Fitness
       Binary Code
 2-000100010101011000100010100000 0.0677 0.0674 0.99915
 3 001110010101011000100010100000 0.2240 0.0674 0.25678
 4 000100010001011000100010100000 0.0667 0.0674 0.99976
 5 - 000100010101010100101010010100 0.0677 0.0826 0.82173
                             0.0986 0.0704 0.81543
Average Values:
Average Function Value of Generation = 0.81543
                              -0.99976
Maximum Function Value
 Number of Crossovers
                          65
* የተመሰው Restart micro-population at generation 123 የተየትዩት
Binary Code
                             Paraml Param2 Fitness
 1 000100010001011000100010100000
                             0.0667 0.0674 0.99976
```

2 110100101000000001011101000011 0.8223 0.1817 0.00001

```
http://www.cuaerospace.com/carroll/ga/ga.out
```

 3 0001101111010001010111000011111
 0.1086
 0.6728
 0.03662

 4 01010010001000110001101010
 0.3208
 0.5345
 0.00003

 5 011100110100111100010111
 0.4504
 0.0905
 0.31949

Average Values: 0.3538 0.3094 0.27118

Average Function Value of Generation - 0.27118
Maximum Function Value - 0.99976

Number of Crossovers = 82 Elitist Reproduction on Individual 1

Binary Code 1 0001000101010101001010100000 0 0.0667 0.0674 0.99976 0.011001111001111010111111 0 0.2024 0.6533 0.00677 0.01100110101010101010101010001 0 0.2003 0.0826 0.01840 0.00110110101011110000101011110 0.1068 0.5210 0.00288 0.00100010001111000101110000011 0 0.0669 0.0899 0.65492

Average Values: 0.1286 0.2828 0.33655

Average Function Value of Generation= 0.33655
Maximum Function Value = 0.99976

Number of Crossovers = 64
Elitist Reproduction on Individual 5

Binary Code Param1 Param2 Fitness
1 0001000101111000101010100000 0.0669 0.0830 0.81464
2 000100110101100010010110001 0.0755 0.0679 0.94203
3 000100010001011000101010000010 0.0667 0.0821 0.83340
4 000100010001111000100110000011 0.0669 0.0743 0.95748
5 0001000100010110001001000000 0.0667 0.0674 0.99976

Average Values: 0.0686 0.0749 0.90946

Average Function Value of Generation= 0.90946
Maximum Function Value = 0.99976

Number of Crossovers = 70
Elitist Reproduction on Individual 2

Binary Code
1 0001000101111000100010100010
2 00010001001011100010010100000
3 0001000100010110001010100010
4 000100010001011000100110100001
5 000100010001011100010010010010
0 0.0667
0 0.0752
0 0.94670
0 0.0674
0 0.99970

Average Values: 0.0668 0.0721 0.95184

Average Function Value of Generation- 0.95184

0.2538 0.4052 0.20057

Maximum Function Value

Average Values:

Number of Crossovers - 69

ዩዩዩዩዩዩዩ Restart micro-population at generation 127 ዩዩዩዩዩዩዩ

Average Function Value of Generation= 0.20057
Maximum Function Value = 0.99976

Number of Crossovers = 80 Elitist Reproduction on Individual 4

Average Function Value of Generation= 0.42570
Maximum Function Value = 0.99976

Number of Crossovers = 72
Elitist Reproduction on Individual 4

Average Values: 0.0674 0.1579 0.35046

Average Function Value of Generation= 0.35046
Maximum Function Value = 0.99976

Number of Crossovers = 76
Elitist Reproduction on Individual 3

```
##################
################## Generation 131
                                  Paraml Param2 Fitness
        Binary Code
 1 000100010001010000100010010000
                                  0.0667 0.0669 0.99999
                                  0.0667 0.0674 0.99975
  2 000100010001010000100010100000
                                  0.0667 0.0674 0.99976
 3 000100010001011000100010100000
                                  0.0667 0.2241 0.25951
 4 000100010001011001110010110000
                                  0.0687 0.0986 0.43942
 5 000100011001011000110010100000
                                  0-0671 0-1049 0-73968
Average Values:
Average Function Value of Generation= 0.73968
                                   = 0.99999
Maximum Function Value
                              77
 Number of Crossovers
###################
        Binary Code
                                  Paraml Param2 Fitness
  #
 \frac{1 - 000100010001010000100010100000}{1 - 0001000101000000} - \frac{0.0667}{0.0674} - \frac{0.0674}{0.99975}
  <del>2 000100010001010000100010010000</del>
                                  0.0667 0.0669 0.99999
  3 000100011001011000110010000000 0.0687 0.0977 0.46276
  4 000100010001011000100010100000 0.0667 0.0674 0.99976
  5 00010001000101000100010010000 0.0667 0.0669 0.99999
                                  0.0671 0.0732 0.89245
 Average Values:
 Average Function Value of Generation - 0.89245
 Maximum Function Value
                                   = 0.99999
                              75
  Number of Crossovers
                                  ####################
Paraml Param2 Fitness
        Binary Code
  1 00010001000101000100010010000
                                  0.0667 0.0669 0.99999
                                  0.0667 0.0669 0.99999
  <del>2 000100010001010000100010010000</del>
                                  0.0667 0.0664 0.99985
  3 000100010001010000100010000000
                                  0.0667 0.0674 0.99976
  4 000100010001011000100010100000
                                  0.0667 0.0674 0.99975
  5 000100010001010000100010100000
                                  0.0667 0.0670 0.99987
 Average Values:
 Average Function Value of Generation= 0.99987
                                   -0.99999
 Maximum Function Value
                              78
  Number of Crossovers
%%%%%% Restart micro-population at generation 133 %%%%%%
                  ##################
                                  Paraml Param2 Fitness
        Binary Code
                                  0.0667 0.0669 0.99999
  1 000100010001010000100010010000
                                  0.9713 0.1344 0.00000
  2 111110001010100001000100110100
  3 010010100011110000010011011100
                                  0.2900 0.0380 0.23019
```

```
http://www.cuacrospace.com/carroll/ga/ga.out
```

Average Values: 0.3675 0.3278 0.24620

Average Function Value of Generation= 0.24620
Maximum Function Value = 0.99999

Number of Crossovers = 89 Elitist Reproduction on Individual 2

Average Values: 0.1306 0.2734 0.30219

Average Function Value of Generation= 0.30219
Maximum Function Value = 0.99999

Number of Crossovers = 74
Elitist Reproduction on Individual 2

Binary Code Param1 Param2 Fitness
1 00000010001010000100011000 0 0.0042 0.0671 0.02371
2 0001000100010100001001001000 0.0667 0.0669 0.99999
3 00010001000101000011001001000 0.0667 0.0673 0.99985
4 00000011000101000011001001000 0.0120 0.0981 0.03027
5 000100010001010000110010010100 0.0667 0.0983 0.44934

Average Values: 0.0433 0.0795 0.50063

Average Function Value of Generation = 0.50063
Maximum Function Value = 0.99999

Number of Crossovers = 72

Binary Code
1 0001000100010100010010010000
2 00010001000101000010011100
3 0001000100010100010011000
4 000100010001010001001001000
5 0001000100010100010011000
0 0.0667
0 0.0670
0 0.999985
0 0.01000100010100010011000
0 0.0667
0 0.0670
0 0.999985

Average Values: 0.0667 0.0671 0.99991

Average Function Value of Generation= 0.99991
Maximum Function Value = 0.99999

76 Number of Crossovers

```
******* Restart micro-population at generation 137 *******
```

Binary Code Param1 Param2 Fitness 1 000100010001010000100010010000 0.0667 0.0669 0.99999 3 0100001101010010100110111111100 0.2630 0.3046 0.15539 4 101101010011011111001101110100 0.7079 0.9020 0.00007 0.9963 0.9232 0.00000 5 1111111100001111111011000101100 0.5353 0.6126 0.23330 Average Values:

Average Function Value of Generation= 0.23330 - 0.99999 Maximum Function Value

Number of Crossovers Elitist Reproduction on Individual

Paraml Param2 Fitness Binary Code 1 001100000101011110110011010110 0.1888 0.8503 0.00018 2 010100010001001010000011110100 0.3167 0.2575 0.04855 $\frac{3 \cdot 0010010001110101001001001001000}{0.1424} = \frac{0.5670}{0.00000}$ 0.0667 0.0669 0.99999 4 000100010001010000100010010000 0.0677 0.0210 0.16562 5-000100010101010000001010110000 0.1565 0.3525 0.24287

Average Function Value of Generation= 0.24287 Maximum Function Value = 0.99999

75 Number of Crossovers Elitist Reproduction on Individual

Average Values:

Param1 Param2 Fitness Binary Code $\begin{smallmatrix} 1 & 000100010101010000001010110000 \end{smallmatrix} \quad \begin{smallmatrix} 0.0677 & 0.0210 \end{smallmatrix} \quad \begin{smallmatrix} 0.16562 \end{smallmatrix}$ 2.001100010101011000010010010010 0.1927 0.0357 0.002763 00010001000101000010101010000 0.0667 0.0835 0.80434 0.0667 0.0669 0.99999 4 000100010001010000100010010000 0.3168 0.2575 0.04821 5 010100010001011010000011110100

0.1421 0.0929 0.40418 Average Values:

Average Function Value of Generation= 0.40418 Maximum Function Value - 0.99999

Number of Crossovers 67

http://www.cuaerospace.com/carroll/ga/ga.out

Average Values:

```
# Binary Code 1 0001000100101010000011110100 0 0.0667 0.2575 0.83477 0.001000100010101000101010000 0.0667 0.0835 0.80434 0.0010001000101000010010000 0.0667 0.0669 0.99999 0.0010001000101000010010000 0.0667 0.0669 0.99999 0.001000100010101010101000 0.0667 0.0835 0.80434
```

0.0667 0.1116 0.88868

Average Function Value of Generation - 0.88868
Maximum Function Value - 0.99999

NAXIMAM-Parecton value

Number of Crossovers = 81

Average Values: 0.0667 0.1088 0.58217

Average Function Value of Generation - 0.58217
Maximum Function Value - 0.99999

Number of Crossovers = 65

Average Values: 0.0667 0.0709 0.95946

Average Function Value of Generation= 0.95946
Maximum Function Value = 0.99999

Number of Crossovers - 66

#################	Generation	144	######	#######	##
# Binary Co	de		Param1	Param2	Fitness
1-00010001000101	000010001001	0000	0.0667	0.0669	0.99999
2 11000100110100	001101101101	0101	0.7688	0.4284	0.0001
3 10011000010111	101000101110	1101	0.5952	0.2729	0.00823
4-10100011011100	110111010001	1000	0.6385	0.7273	0.00012
5 01101111101101	110110110100	0011	0.4364	0.7130	0.00280

```
Average Values:
```

0.5011 0.4417 0.20223

Average Function Value of Generation = 0.20223
Maximum Function Value = 0.99999

Number of Crossovers = 80 Elitist Reproduction on Individual 1

#	Binary Code	Param1	Param2	Fitness
1	000100010001010000100010010000	0.0667	0.0669	0.99999
2	010011110001010100100011000010	0.3089	0.5684	0.0000
3	100100010101111010001011001001	0.5679	0.2718	0.0001
4	000110010001011000100010110101	0.0980	0.0680	0.45542
5-	01001100001101101000100100101	0.2977	0.2677	0.24427

Average Values: 0.2678 0.2486 0.33994

Average Function Value of Generation - 0.33994
Maximum Function Value - 0.99999

Number of Crossovers = 66
Elitist Reproduction on Individual 1

#	Binary Code	Param1	Param2	Fitness
1	-000100010001010000100010010000	0.0667	0.0669	0.99999
2	000011010011011010000010000001	0.0516	0.2539	0.67346
3-	010111000011011000001011010101	0.3602	0.0221	0.0000
4	000100010001010000100010010101	0.0667	0.0670	0.99995
5	010100000011011010001011000000	0.3133	0.2715	0.06591

Average Values: 0.1717 0.1363 0.54786

Average Function Value of Generation - 0.54786
Maximum Function Value - 0.99999

Number of Crossovers = 58
Elitist Reproduction on Individual 4

#	Binary Code	Paraml	Param2	Fitness
1	000101010011010000000010010101	0.0828	0.0045	0.02041
2	000110010011011000100010000000	0.0985	0.0664	0.44417
3	- 000100010001010000100010010001	0.0667	0.0669	0.99998
4	-000100010001010000100010010000	0.0667	0.0669	0.99999
5	-000100010011010010101011000000	0.0672	0.3340	0.00395

Average Values: 0.0764 0.1078 0.49370

Average Function Value of Generation - 0.49370
Maximum Function Value - 0.99999

Number of Crossovers - 76

Elitist Reproduction on Individual

```
################
                             Paraml Param2 Fitness
       Binary Code
 1-000101010001010000100010010101 0.0823 0.0670 0.82844
                            0.0980 0.0669 0.45592
 2 000110010001011000100010010000
 3 000100010001011000100010010000
                            0.0667 0.0669 0.99999
                            0.0667 0.0664 0.99986
 4 00010001000101100010001000000
 5 00010001000101000100010010010 0.0667 0.0669 0.99999
Average Values:
                             0.0761 0.0668 0.85684
Average Function Value of Generation= 0.85684
Maximum Function Value
                              -0.99999
                         74
 Number of Crossovers
Paraml Param2 Fitness
       Binary Code
 1 - 000100010001011000100010010000  0.0667 - 0.0669 - 0.99999
 3 111111000011101010001110101110 0.9853 0.2788 0.00047
                            0.0786 0.4318 0.27929
 4 000101000010001011011101000100
 0.3638 0.4879 0.25595
Average Values:
Average Function Value of Generation = 0.25595
                             <del>- 0.99999</del>
Maximum Function Value
 Number of Crossovers
                         74
 Elitist Reproduction on Individual
Paraml Param2 Fitness
       Binary Code
 \frac{1-100011010011011100101010010100}{0.5516} \quad \frac{0.5827}{0.00000}
 2 000101000000001001100011000100 0.0782 0.1935 0.00634
 3 00010000000011000101011010000 0.0626 0.0845 0.77239
\hbox{-4.100100000011001000001010100100} \quad \hbox{0.5633} \quad \hbox{0.0206} \quad \hbox{0.00000}
 5 00010001001011000100010010000 0.0667 0.0669 0.99999
                             0.2645 0.1896 0.35574
Average Values:
Average Function Value of Generation= 0.35574
                             <del>- 0.99999</del>
Maximum Function Value
 Number of Crossovers
 Elitist Reproduction on Individual
```

Binary Code

Paraml Param2 Fitness

```
http://www.cuaerospace.com/carroll/ga/ga.out
```

 1
 0001000100101100010010010000
 0.0667
 0.0669
 0.99999

 2
 0001000000101100010010010100
 0.0628
 0.0670
 0.98769

 3
 00010100000011000101101010000
 0.0782
 0.0845
 0.70799

 4
 0001010000011001100010010000
 0.0821
 0.1919
 0.00425

 5
 1001000000101100010001000100
 0.5629
 0.0665
 0.00000

Average Values: 0.1706 0.0954 0.53998

Average Function Value of Generation= 0.53998
Maximum Function Value = 0.99999

Number of Crossovers = 77
Elitist Reproduction on Individual 2

Binary Code Param1 Param2 Fitness
1 00010001000011001100010010000 0.0665 0.1919 0.00510
2 0001000100010110001001001000 0.0667 0.0669 0.99999
3 000100010001011000100100100 0.0667 0.0670 0.99997
4 000100010010110001001001000 0.0667 0.0670 0.99997
5 00010101000101100010010010000 0.0824 0.1919 0.00422

Average Values: 0.0698 0.1169 0.60185

Average Function Value of Generation=-0.60185
Maximum Function Value =-0.99999

Number of Crossovers = 75

ዩዩዩዩዩዩዩ Restart micro-population at generation 152 ዩዩዩዩዩዩ

Binary Code 1 0001000100101100010010010000 0 0.0667 0.0669 0.99999 0 0.01110101010010010011111110 0 0.2914 0.3143 0.03167 0 0.01010101010101101101000001 0 0.5716 0.2129 0.00001 0 0.101010101010010101111111 0 0.8341 0.2929 0.02422

Average Values: 0.4443 0.2474 0.21118

Average Function Value of Generation= 0.21118
Maximum Function Value = 0.99999

Number of Crossovers = 74
Elitist Reproduction on Individual 4

#	Binary Code	Paraml	Param2	Fitness
1	110100010001001000010111011100	0.8167	0.0458	0.02350
2	0100101100011110001000101110000	0.2934	0.0679	0.37844
3-	01010001000001000110011000001	0.3164	0.0996	0.02493
4	000100010001011000100010010000	0.0667	0.0669	0.99999
5_	110001101001100010110000111100	0.7758	0.3456	0.00000

```
Average Values:
```

0.4538 0.1252 0.28537

Average Function Value of Generation= 0.28537
Maximum Function Value = 0.99999

Number of Crossovers = 68
Elitist Reproduction on Individual 2

# Binary Co	o de	Param1	Param2	Fitness
	1000110011000000	0.0667	0.0996	0.41756
2 00010001000101	1000100010010000	0.0667	0.0669	0.99999
3 11011011000100	10000011011100	0.8558	0.0136	0.00528
	100010001001000	0.3480	0.0669	0.00005
=	1000100011010000	0.2541	0.0688	0.80658

Average Values: 0.3183 0.0632 0.44589

Average Function Value of Generation= 0.44589
Maximum Function Value = 0.99999

Number of Crossovers = 70
Elitist Reproduction on Individual 1

# Binary Code	Param1	Param2	Fitness
1 000100010001011000100010010000	0.0667	0.0669	0.99999
2-010000100000100000110010100	0.2539	0.0123	0.05599
3-000100010001011000110010000000	0.0667	0.0977	0.46401
4 01011011000100100100110111000	0.3558	0.0759	0.0000
5 000100010001011000110010010000	0.0667	0.0981	0.45226
Average Values:	0.1620	0.0702	0.39445

Average Function Value of Generation= 0.39445
Maximum Function Value = 0.99999

Number of Crossovers 76
Elitist Reproduction on Individual

#################	Generation	157	#######	########	##
# Binary Co	de		Param1	Param2	Fitness
1 00010001000100		0100	0.0667	0.1061	0.27783
2 0000001000101	100010011001	0000	0.0042	0.0747	0.02270
3 00010001000101			0.0667	0.0977	0.46401
4-0000001000101			0.0042	0.0670	0.02382
5-00010001000101	100010001001	0000	0.0667	0.0669	0.99999

Average Values: 0.0417 0.0825 0.35767

Average Function Value of Generation = 0.35767

Maximum Function Value = 0.99999

```
73
Number of Crossovers
Elitist Reproduction on Individual
```

Paraml Param2 Fitness Binary Code 1 000100010001011000110010010000 0.0667 0.0981 0.45226 2 000100010001001000110010000000 0.0667 0.0977 0.46400 3 000100010001011000100010010000 0.0667 0.0669 0.99999 0.0042 0.0669 0.02382 4 0000001001011000100010010000 5 000100010001011000110010000000 0.0667 0.0977 0.46401 0.0542 0.0855 0.48082 Average Values: Average Function Value of Generation= 0.48082

-0.99999Maximum Function Value

Number of Crossovers 78

* የተመሰው Restart micro-population at generation 158 የተያዩተናት

################### Param1 Param2 Fitness Binary Code 1 000100010001011000100010010000 0.0667 0.0669 0.99999 0.4098 0.4180 0.01066 2 011010001110011011010110000001 3 1010110000101001111110000000111 0.6725 0.9690 0.00000 4 001010010100110001100110100000 0.1613 0.2002 0.00000 5 101101101010110101011101010000 0.7136 0.6821 0.00076 0.4048 0.4673 0.20228 Average Values:

Average Function Value of Generation - 0.20228 Maximum Function Value -0.99999

Number of Crossovers 79 Elitist Reproduction on Individual

Param1 Param2 Fitness Binary Code 0.0863 0.0767 0.68880 1 000101100001011000100111010000 0.2232 0.1992 0.00463 2 001110010010011001100110000000 0.4420 0.0039 0.00986 3 011100010010011000000010000001 0.7018 0.6275 0.00377 4 101100111010011101000001010000 0.0667 0.0669 0.99999 5 000100010001011000100010010000 0.3040 0.1948 0.34141 Average Values:

Average Function Value of Generation- 0.34141 Maximum Function Value -0.99999

75 Number of Crossovers Elitist Reproduction on Individual

http://www.cuaerospace.com/carroll/ga/ga.out

Average Values:

Paraml Param2 Fitness Binary Code 0.0672 0.1914 0.00461 1 000100010011011001100010000000 2 000101100001011000100010010000 0.0863 0.0669 0.74257 4 000100010001011000100010010000 0.0667 0.0669 0.99999 0.0665 0.0039 0.02263 5 000100010000011000000010000000 0.1503 0.0683 0.36065

Average Function Value of Generation= 0.36065 = 0.99999Maximum Function Value

67 Number of Crossovers

###################

Param1 Param2 Fitness Binary Code 1 000100100001011000100010010000 0.0707 0.0669 0.98876 2 000101100001011000100010010000 0.0863 0.0669 0.74257 $\frac{3 \cdot 000100010001011000100010010000}{0.0667} \cdot \frac{0.0669}{0.99999}$ 4 011101100001011000000110010000 0.4613 0.0122 0.03469

0.1503 0.0434 0.55773 Average Values:

Average Function Value of Generation= 0.55773 Maximum Function Value -0.99999

Number of Crossovers Elitist Reproduction on Individual 5

################

Binary Code Paraml Param2 Fitness 1 00010000001011000100010010000 0.0628 0.0669 0.98771 $\frac{2\ 00010011000101100010010010010000}{0.0746}$ 5-000100010001011000100010010000 0.0667 0.0669 0.99999

0.1222 0.0560 0.78627 Average Values:

Average Function Value of Generation= 0.78627 -0.99999Maximum Function Value

Number of Crossovers 84

ዩዩዩዩዩዩዩ Restart micro-population at generation 163 ዩዩዩዩዩዩ

Param1 Param2 Fitness Binary Code 3 110111101110101010110110101111 0.8708 0.3503 0.00000 4 100011110000011110111000101110 0.5587 0.8608 0.00000

```
Average Values:
```

Average Values:

0.6343 0.6478 0.20001

Average Function Value of Generation - 0.20001 -0.99999Maximum Function Value

Number of Crossovers = 82 Elitist Reproduction on Individual

raramz	<u>Fitness</u>
0.9751	0.0000
0.0924	0.03626
0.0981	0.02402
0.3189	0.04426
0.0669	0.99999
	0.9751 0.0924 0.0981 0.3189

0.5103 0.3103 0.22091 Average Values:

Average Function Value of Generation= 0.22091 Maximum Function Value -0.99999

Number of Crossovers 67 Elitist Reproduction on Individual

# Binary Code	Param1	Param2	Fitness
1-000100010000011010100010010001	0.0665	0.3169	0.05655
2-000100010001011000100010010000	0.0667	0.0669	0.99999
3 000100010000111010100011010000	0.0666	0.3189	0.04501
4-001100010000111000100111010001	0.1916	0.0767	0.00447
5-000100111001011000100010010000	0.0765	0.0669	0.92975
Average Values:	0.0936	0.1693	0.40715

Average Function Value of Generation = 0.40715 - 0.99999 Maximum Function Value

Number of Crossovers 74 Elitist Reproduction on Individual

H A H II I	** ** ** ** ** **		
# Binary Code	Param1	Param2	Fitness
1-00010011000101100010001001000	0.0746	0.0669	0.95472
2-00010001000001101010001001000	1 0.0665	0.3169	0.05655
3 00010011000101100010001001000	0 0.0746	0.0669	0.95472
4 00010001000011100010001001000	0.0666	0.0669	0.99996
5 00010001000101100010001001000	0 0.0667	0.0669	0.99999

0.0698 0.1169 0.79319 Average Values:

Average Function Value of Generation - 0.79319 Maximum Function Value -0.99999

ዩዩዩዩዩዩዩ Restart micro-population at generation 167 ዩዩዩዩዩዩዩ

Average Function Value of Generation= 0.37306
Maximum Function Value = 0.99999

Number of Crossovers = 80
Elitist Reproduction on Individual 5

0.2445 0.1584 0.48967

Average Function Value of Generation- 0.48967

Maximum-Function Value = 0.99999

Number of Crossovers = 88
Elitist Reproduction on Individual 3

Average Values:

Average Function Value of Generation= 0.35776
Maximum Function Value = 0.99999

Number of Crossovers - 70
Elitist Reproduction on Individual 1

http://www.cuaerospace.com/carroll/ga/ga.out

```
# Binary Code
1 0001000101010010010010000 0.0667 0.0669 0.99999
2 001100010010110001001001000 0.1917 0.0669 0.00494
3 01010001111101100010011110000 0.3202 0.0698 0.03793
4 01010001101010100100100100 0.3187 0.0669 0.04586
5 0111000101000000010010111000 0.4424 0.0681 0.43721

Average Values:

0.2680 0.0677 0.30519
```

Average Function Value of Generation= 0.30519
Maximum Function Value = 0.99999

Number of Crossovers = 80 Elitist Reproduction on Individual 4

# Binary Code	Param1	Param2	Fitness
1 00110001000001000100010111000	0.1915	0.0681	0.00466
2 01110001100000000100010110000	0.4434	0.0679	0.44695
3 000100010111011000100011110000	0.0682	0.0698	0.99162
4 000100010001011000100010010000	0.0667	0.0669	0.99999
5 000100011011011000100010110000	0.0692	0.0679	0.99488

Average Values: 0.1678 0.0681 0.68762

Average Function Value of Generation= 0.68762
Maximum Function Value = 0.99999

Number of Crossovers = 72 Elitist Reproduction on Individual 4

#	Binary Code	Param1	Param2	Fitness
1	0001000101110110001000101110000	0.0682	0.0679	0.99769
2	000100010111011000100011010000	0.0682	0.0688	0.99539
3	000100011001011000100010110000	0.0687	0.0679	0.99647
	000100010001011000100010010000	0.0667	0.0669	0.99999
5-	000100010111011000100010010000	0.0682	0.0669	0.99853
_				

Average Values: 0.0680 0.0677 0.99761

Average Function Value of Generation= 0.99761
Maximum Function Value = 0.99999

Number of Crossovers = 73

[[] [] [] [] [] [] [] [] [] [
Binary Code	Param1	Param2	Fitness
000100010011011000100010010000	0.0672	0.0669	0.99987
000100010001011000100010010000	0.0667	0.0669	0.99999
-000100010011011000100010010000	0.0672	0.0669	0.99987
000100011111011000100010110000	0.0702	0.0679	0.99061
-000100011001011000100010010000	0.0687	0.0669	0.99730
	_	Binary Code Param1 -000100010011011000100010010000 0.0672 -000100010011011000100010010000 0.0667 -000100011111011000100010110000 0.0672 -000100011111011000100010110000 0.0702	Binary Code Param1 Param2 0001000100110110100010010010000 0.0672 0.0669 -00010001001101100010010010000 0.0667 0.0669 -000100011111011000100010010000 0.0672 0.0669 -000100011111011001000100110000 0.0702 0.0679

Average Values: 0.0680 0.0671 0.99753

```
Average Function Value of Generation- 0.99753
                                   - 0.99999
Maximum Function Value
                              74
 Number of Crossovers
 Elitist Reproduction on Individual
<del>የዩዩዩዩዩዩ</del> Restart micro-population at generation 174  ዩዩዩዩዩዩዩ
Paraml Param2 Fitness
        Binary Code
 \frac{1-00010001001011000100010010000}{1-000100010010000} = \frac{0.0667}{0.0669} = \frac{0.99999}{0.999999}
 \frac{2}{100100000010001101100111100111} 0.5630 0.7024 0.00000
 \frac{3-000001100000010010000110001010}{0.0235} \frac{0.2620}{0.17312}
 4-1011110011011100010010101010101 0.7378 0.1458 0.00000
 \frac{5-01010011110010000001000101111}{5-01010011111} = \frac{0.3273}{0.0171} = \frac{0.00157}{0.00157}
                                  0.3437 0.2388 0.23494
 Average Values:
 Average Function Value of Generation= 0.23494
                                   <del>- 0.99999</del>
 Maximum Function Value
  Number of Crossovers
  Elitist Reproduction on Individual
Paraml Param2 Fitness
        Binary Code
  \frac{1-101101000001011000001010010001}{0.7035} \frac{0.0201}{0.00348}
  2-000010000001000000110011000 0.0157 0.0125 0.00703
  \frac{3-010001100100110010001000101011}{0.2746}
  4 \cdot 0101001111011110000000000010110 \cdot 0.3276 \cdot 0.0007 \cdot 0.00017
  5 000100010001011000100010010000 0.0667 0.0669 0.99999
                                  0.2776 0.0734 0.32596
 Average Values:
 Average Function Value of Generation= 0.32596
 Maximum Function Value
                                   <del>- 0.99999</del>
                               78
  Number of Crossovers
  Elitist Reproduction on Individual
Paraml Param2 Fitness
        Binary Code
  2 000101010001010000100110010000 0.0823 0.0747 0.78949
  3 000001000000110010001000001011 0.0158 0.2660 0.08468
  4 000100010001011000100010010000 0.0667 0.0669 0.99999
  5-00000100000010000001110101011 0.0157 0.0287 0.02993
                                   0.0916 0.1537 0.38160
 Average Values:
```

- 0.99999

Average Function-Value of Generation- 0.38160

Maximum Function Value

Number of Crossovers 79 Elitist Reproduction on Individual Paraml Param2 Fitness Binary Code 0.0667 0.0669 0.99999 1-000100010001011000100010010000 2 000101010001011000100110010000 0.0824 0.0747 0.78890 $\frac{300010101000101100010010010000}{0.0824}$ 4 - 000100010001011000100110010000 0.0667 0.0747 0.952950.0198 0.0750 0.14202 5 00000101000101000100110011000 0.0636 0.0716 0.74234 Average Values: Average Function Value of Generation 0.74234 - 0.99999 Maximum Function Value 90 Number of Crossovers ዩዩዩዩዩዩዩ Restart micro-population at generation 178 ዩዩዩዩዩዩዩ ################ Generation 179 ################# Paraml Param2 Fitness Binary Code $\frac{1000100010001011000100010010000}{1000010010000}$ 0.7311 0.5870 0.00000 2 101110110010011100101100100010 3 11110001111110101101111101111101 0.9452 0.4355 0.00000 0.5247 0.4458 0.20065 Average Values: Average Function Value of Generation- 0.20065 - 0.99999 Maximum Function Value Number of Crossovers Elitist Reproduction on Individual 1 Param1 Param2 Fitness Binary Code 0.0667 0.0669 0.99999 1 000100010001011000100010010000 2 000110011000011001101000010101 0.0997 0.2038 0.01514 0.6837 0.0875 0.07134 3 101011110000011000101100110010 0.1948 0.6231 0.00103 4 0011000111011101001111111000010 0.5985 0.5899 0.00008 5 100110010011011100101110000000 0.3287 0.3142 0.21752 Average Values: Average Function Value of Generation- 0.21752 -0.99999 Maximum Function Value

Number of Crossovers

Elitist Reproduction on Individual

```
Paraml Param2 Fitness
       Binary Code
 \tfrac{1-101110110000011000100110010000}{0.7306} \ \tfrac{0.0747}{0.00027}
 2 101111010000011000101100010101 0.7384 0.0866 0.00002
 3 101100110001011000100110010000 0.6996 0.0747 0.03146
 4 000100010001011000100010010000 0.0667 0.0669 0.99999
 0.4842 0.1029 0.20637
Average Values:
Average Function Value of Generation- 0.20637
                                <del>- 0.99999</del>
Maximum Function Value
 Number of Crossovers
                            75
 Elitist Reproduction on Individual
                ################
                               Param1 Param2 Fitness
       Binary Code
 1 10011011000001100010010010000 0.6056 0.0669 0.03395
 <del>2 000100010001011000100010010000 0.0667 0.0669 0.99999</del>
 3 001110010001011000100110010000 0.2230 0.0747 0.22881
 4 10110001001011000100110010000 0.6918 0.0747 0.05821
 5 001100010001011000100110010000 0.1917 0.0747 0.00471
                               0.3558 0.0716 0.26513
 Average Values:
 Average Function Value of Generation- 0.26513
                                -0.99999
 Maximum Function Value
                            66
 Number of Crossovers
 Elitist Reproduction on Individual
                #################
                               Paraml Param2 Fitness
       Binary Code
 \tfrac{1-100100010001011000100010010000}{0.5668} \ \ \tfrac{0.0669}{0.0000}
 <del>2-101100010001011000100010010000 0.6918 0.0669 0.06108</del>
 3 00010001001011000100110010000 0.0667 0.0747 0.95295
 4 100110010000011000100010010000 0.5978 0.0669 0.01479
 \frac{5 \cdot 0001000100101100010010010000}{0.0667} \cdot \frac{0.0669}{0.0669} \cdot \frac{0.99999}{0.99999}
                               0.3980 0.0685 0.40576
 Average Values:
 Average Function Value of Generation - 0.40576
                                -0.99999
 Maximum Function Value
 Number of Crossovers
                            87
*** Restart micro-population at generation 183 *******
Paraml Param2 Fitness
       Binary Code
 1 000100010001011000100010010000 0.0667 0.0669 0.99999
 2-0100110100100100110000011000011 0.3013 0.3780 0.00006
```

```
http://www.cuaerospace.com/carroll/ga/ga.out
```

Average Values: 0.5107 0.2489 0.25982

Average Function Value of Generation= 0.25982
Maximum Function Value = 0.99999

Number of Crossovers = 75
Elitist Reproduction on Individual 3

Binary Code Param1 Param2 Fitness
1 0001000101111000100011100011 0.0669 0.0694 0.99478
2 00010001011111000100011010010 0.0678 0.0689 0.99587
3 00010001001011000100100100 0.0667 0.0669 0.99999
4 0001000111111111000101111010010 0.0703 0.0455 0.69099
5 001100011111111100010011000000 0.1953 0.0684 0.00980

Average Values: 0.0934 0.0638 0.73829

Average Function Value of Generation= 0.73829
Maximum Function Value = 0.99999

Number of Crossovers = 73
Elitist Reproduction on Individual

Average Values: 0.0670 0.0679 0.99835

Average Function Value of Generation= 0.99835
Maximum Function Value = 0.99999

Number of Crossovers = 76

Binary Code Param1 Param2 Fitness
1 000100010111100010001001001 0 0.0669 0.0670 0.99999
2 000100010001111000100010010 0.0669 0.0670 0.99999
3 000100010001111000100010010 0.0669 0.0670 0.99999
4 00010001000101110001000100100 0.0667 0.0669 0.99999
5 000100010001111000100010010000 0.0669 0.0669 1.00000

Average Values: 0.0668 0.0669 0.99999

Average Function Value of Generation= 0.99999
Maximum Function Value = 1.00000

Number of Crossovers - 66

%%%%%%% Restart micro population at generation 187 %%%%%%

Average Values: 0.4546 0.2303 0.21639

Average Function Value of Generation = 0.21639
Maximum Function Value = 1.00000

Number of Crossovers = 74
Elitist Reproduction on Individual 5

Average Values: 0.2858 0.2034 0.32621

Average Function Value of Generation = 0.32621
Maximum Function Value = 1.00000

Number of Crossovers = 91 Elitist Reproduction on Individual 2

Average Values: 0.0762 0.0916 0.48945

Average Function Value of Generation= 0.48945
Maximum Function Value = 1.00000

Number of Crossovers = 57
Elitist Reproduction on Individual 4

```
Paraml Param2 Fitness
       Binary Code
                             0.0669 0.0991 0.42903
 1 000100010001111000110010110000
 2 000110010001110000101010010000 0.0981 0.0825 0.37420
 3-000100010001111000110010110000 0.0669 0.0991 0.42903
 4 000100010001111000100010010000 0.0669 0.0669 1.00000
 5 000100010001111000110000110000 0.0669 0.0952 0.52378
                             0.0731 0.0886 0.55121
Average Values:
Average Function Value of Generation= 0.55121
Maximum Function Value
                              -1.00000
                          67
 Number of Crossovers
###################
                             Param1 Param2 Fitness
       Binary Code
 \frac{1.000100010001111000110010010000}{0.00669} \quad \frac{0.0981}{0.45226}
 2 000100010001111000110000010000 0.0669 0.0942 0.54802
 3 000100010001111000100010010000 0.0669 0.0669 1.00000
 4 000100010001111000110010110000 0.0669 0.0991 0.42903
 5 000100010001111000110010110000 0.0669 0.0991 0.42903
                             0.0669 0.0915 0.57167
Average Values:
Average Function Value of Generation - 0.57167
Maximum Function Value
                              -1.00000
                          76
 Number of Crossovers
Paraml Param2 Fitness
 #
       Binary Code
 1 000100010001111000100010010000 0.0669 0.0669 1.00000
 2 111111110011001000011000101011 0.9969 0.0482 0.00197
 3 111111111011010100001010001101 0.9989 0.5199 0.00004
 4 1100010101101010000101111100111 0.7712 0.0461 0.00004
 0.6089 0.1405 0.20319
Average Values:
Average Function Value of Generation - 0.20319
                              -1.00000
Maximum Function Value
                          66
 Number of Crossovers
 Elitist Reproduction on Individual
Paraml Param2 Fitness
       Binary Code
                             0.2714 0.0772 0.72539
 1 010001010111101000100111100010
 2 000100010001111000100010010000 0.0669 0.0669 1.00000
 3 101001011110101000010111101011 0.6481 0.0462 0.15940
 4 000100110011001000101000101001 0.0750 0.0794 0.83999
```

```
http://www.cuaerospace.com/carroll/ga/ga.out
```

 $\frac{5001111110011101000010010100001}{5001111110011101000010100001} = \frac{0.2470}{0.0362} = \frac{0.33361}{0.0001010100001}$

Average Values: 0.2617 0.0612 0.61168

Average Function Value of Generation= 0.61168
Maximum Function Value = 1.00000

Number of Crossovers = 81 Elitist Reproduction on Individual 1

Binary Code Param1 Param2 Fitness
1 00010001000111100010010010000 0.0669 0.0669 1.00000
2 00010001011101001011010000 0.0667 0.0833 0.80951
3 00010101011101000101100000000 0.0829 0.0743 0.78211
4 00010001001111000101000000001 0.0672 0.0782 0.90482
5 00111011000111100010010110000 0.2309 0.0366 0.18684

Average Values: 0.1029 0.0678 0.73665

Average Function Value of Generation= 0.73665
Maximum Function Value = 1.00000

Number of Crossovers = 61
Elitist Reproduction on Individual 3

Average Values: 0.0670 0.0717 0.94342

Average Function Value of Generation= 0.94342
Maximum Function Value = 1.00000

Number of Crossovers = 82

****** Restart micro-population at generation 196 ******

Average Values: 0.3854 0.5106 0.20097

Average Function Value of Generation= 0.20097

-1.00000

77 Number of Crossovers Elitist Reproduction on Individual

Binary Code Param1 Param2 Fitness 2 111001000011110101111110100111 0.8916 0.7473 0.00000 0.3169 0.1998 0.00118 3 010100010001111001100110010010

0.5903 0.9424 0.00000 4 1001011100011111111100010100000 5 000100010001111000100010010000 0.0669 0.0669 1.00000

0.4646 0.4094 0.26662 Average Values:

Average Function Value of Generation= 0.26662 Maximum Function Value -1.00000

Number of Crossovers 79 Elitist Reproduction on Individual

################ Generation 199 ################

Paraml Param2 Fitness Binary Code 1-010101010101111000100010010001 0.3325 0.0669 0.00536 2 001101010001111000100010010000 0.2075 0.0669 0.05796 3 010100010001111000100010010010 0.3169 0.0670 0.05695 4 011101010001111000101010010000 0.4575 0.0825 0.42484 5 000100010001111000100010010000 0.0669 0.0669 1.00000

0.2762 0.0700 0.30902 Average Values:

Average Function Value of Generation- 0.30902 Maximum-Function Value -1.00000

74 Number of Crossovers Elitist Reproduction on Individual

Param1 Param2 Fitness Binary Code $\frac{1000101010001111000100010010000}{0.0825}$ 2.000100010001111000101010010000 0.0669 0.0825 0.824733 000100010001111000100010010000 0.0669 0.0669 1.00000 4 001100010001111000100010010000 0.1919 0.0669 0.00507 0.3325 0.0825 0.00442 5 010101010001111000101010010000

0.1481 0.0731 0.53192

Average Function Value of Generation = 0.53192 Maximum Function Value -1.00000

Number of Crossovers

Average Values:

ዩዩዩዩዩዩዩ Restart micro-population at generation 200 ዩዩዩዩዩዩዩ

map.//www.cauchospaco.com/canom/ga/garear					
Summary of Output					
Generation	Evaluations	Avg.Fitness	Best Fitness		
0.1000E+01	0.5000E+01	0.2047E-01	0.10147E+00		
0.1000E+01	0.1000E+02	0.4206E-01	0.10147E+00		
0.2000E+01	0.1500E+02	0.1302E+00	0.22471E+00		
0.4000E+01	0.2000E+02	0.4967E-01	0.22471E+00		
0.5000E+01	0.2500E+02	0.4622E-01	0.22471E+00		
0.5000E+01	0.3000E+02	0.6616E-01	0.22471E+00		
0.7000E+01	0.3500E+02	0.6470E-01	0.22471E+00		
0.8000E+01	0.4000E+02	0.6744E-01	0.22471E+00		
0.9000E+01	0.4500E+02	0.6783E-01	0.22471E+00		
0.3000E+02	0.5000E+02	0.4531E-01	0.22471E+00		
0.1000E+02	0.5500E+02	0.5091E-01	0.22471E+00		
0.1200E+02	0.6000E+02	0.9019E-01	0.22492E+00		
0.1200E+02	0.6500E+02	0.9066E-01	0.22492E+00		
0.1400E+02	0.7000E+02	0.9173E-01	0.22492E+00		
0.1500E+02	0.7500E+02	0.1355E+00	0.29078E+00		
0.1600E+02	0.8000E+02	0.1002E+00	0.29078E+00		
0.1700E+02	0.8500E+02	0.2308E+00	0.57101E+00		
0.1800E+02	0.9000E+02	0.4515E+00	0.57101E+00		
0.1900E+02	0.9500E+02	0.1247E+00	0.57101E+00		
0.2000E+02	0.1000E+03	0.1201E+00	0.57101E+00		
0.2100E+02	0.1050E+03	0.1733E+00	0.57101E+00		
0.2200E+02	0.1100E+03	0.2699E+00	0.57101E+00		
0.2300E+02	0.1150E+03	0.3930E+00	0.57101E+00		
0.2400E+02	0.1200E+03	0.1192E+00	0.57101E+00		
0.2500E+02	0.1250E+03	0.2650E+00	0.57101E+00		
0.2600E+02	0.1300E+03	0.4157E+00	0.57101E+00		
0.2700E+02	0.1350E+03	0.4508E+00	0.57370E+00		
0.2800E+02	0.1400E+03	0.1211E+00	0.57370E+00		
0.2900E+02	0.1450E+03	0.1256E+00	0.57370E+00		
0.3000E+02	0.1500E+03	0.1260E+00	0.57370E+00		
0.3100E+02	0.1550E+03	0.1215E+00	0.57370E+00		
0.3200E+02	0.1600E+03	0.3631E+00	0.65745E+00		
0.3300E+02	0.1650E+03	0.3706E+00	0.65745E+00		
0.3400E+02	0.1700E+03	0.1362E+00	0.65745E+00		
0.3500E+02	0.1750E+03	0.1739E+00	0.65745E+00		
0.3600E+02	0.1800E+03	0.2188E+00	0.65745E+00		
0.3700E+02	0.1850E+03	0.4179E+00	0.66297E+00		
0.3800E+02	0.1900E+03	0.5469E+00	0.66297E+00		
0.3900E+02	0.1950E+03	0.6606E+00	0.66672E+00		
0.4000E+02	0.2000E+03	0.6645E+00	0.66797E+00		
0.4100E+02	0.2050E+03	0.1348E+00	0.66797E+00		
0.4200E+02	0.2100E+03	0.1927E+00	0.66797E+00		
0.4300E+02	0.2150E+03	0.2034E+00	0.66797E+00		
0.4400E+02	0.2200E+03	0.3022E+00	0.66797E+00		
		0 40110.00	0 (741) 77.00		

0.2250E+03

0.2300E+03

0.2500E+03

0.2550E+03

0.2600E+03

0.2650E+03

0.2700E+03

0.2750E+03

0.2800E+03

0.2850E+03

0.2350E+03

0.2450E+03

0.4800E+02 0.2400E+03

0.4500E+02

0.4600E+02

0.4700E+02

0.4900E+02

0.5000E+02

0.5100E+02

0.5200E+02

0.5300E+02

0.5400E+02

0.5500E+02

0.5600E+02

0.5700E+02

0.4311E+00

0.1356E+00

0.1629E+00

0.1847E+00

0.1774E+00

0.6680E+00

0.7734E+00

0.1970E+00

0.2277E+00

0.1970E+00

0.3150E+00

0.3750E+00

0.3008E+00

0.67412E+00

0.67412E+00

0.67412E+00

0.67412E+00

0.67412E+00

0.98354E+00

0.98354E+00

0.98354E+00

0.98354E+00

0.98354E+00

0.98354E+00

0.98354E+00

0.98354E+00

•			
0.5800E+02	0.2900E+03	0.2011E+00	0.98354E+00
0.5900E+02	0.2950E+03	0.3842E+00	0.98354E+00
0.6000E+02	0.3000E+03	0.3195E+00	0.98354E+00
0.6100E+02	0.3050E+03	0.5175E+00	0.98414E+00
0.6200E+02	0.3100E+03	0.6032E+00	0.99008E+00
0.6300E+02	0.3150E+03	0.1982E+00	0.99008E+00
0.6400E+02	0.3200E+03	0.2733E+00	0.99008E+00
0.6500E+02	0-3250E+03	0.3861E+00	0.99008E+00
••••	0.3250E+03	0.6052E+00	0.99929E+00
0.6600E+02	• • • • • • • • • • • • • • • • • • • •	0.0052E+00	0.99929E+00
0.6700E+02	0.3350E+03	• • • • • • • • • • • • • • • • • • • •	0.99929E+00
0.6800E+02	0.3400E+03	0.3533E+00	0.99929E+00
0.6900E+02	0.3450E+03	0.2072E+00	• • • • • • • • • • • • • • • • • • • •
0.7000E+02	0.3500E+03	0.2748E+00	0.99929E+00
0.7100E+02	0.3550E+03	0.4527E+00	0.99929E+00
0.7200E+02	0.3600E+03	0.6767E+00	0.99929E+00
0.7300E+02	0.3650E+03	0.7503E+00	0.99929E+00
0.7400E+02	0.3700E+03	0.9653E+00	0.99929E+00
0.7500E+02	0.3750E+03	0.9653E+00	0.99929E+00
0.7600E+02	0.3800E+03	0.2080E+00	0.99929E+00
0.7700E+02	0.3850E+03	0.3159E+00	0.99929E+00
0.7800E+02	0.3900E+03	0.4895E+00	0.99929E+00
0.7900E+02	0.3950E+03	0.9026E+00	0.99936E+00
0.8000E+02	0.4000E+03	0.9606E+00	0.99940E+00
0.8100E+02	0.4050E+03	0.2003E+00	0.99940E+00
0.8200E+02	0.4100E+03	0.2131E+00	0.99940E+00
0.8300E+02	0-4150E+03	0.2240E+00	0.99940E+00
0.8400E+02	0.1200E+03	0.4382E+00	0.99940E+00
0.8500E+02	0.4250E+03	0.7995E+00	0.99940E+00
0.8600E+02	0.4300E+03	0.7999E+00	0.99940E+00
	0.4350E+03	0.2002E+00	0.99940E+00
0.8700E+02	0.4330E+03	0.2034E+00	0.99940E+00
0.8800E+02	0.1100-	0.2054B+00	0.99940E+00
0.8900E+02	0.4450E+03	0.2130E+00	0.99940E+00
0.9000E+02	0.4500E+03	•	0.99940E+00
0.9100E+02	0.4550E+03	0.2754E+00	
0.9200E+02	0.4600E+03	0.3286E+00	0.99940E+00
0.9300E+02	0.4650E+03	0.6486E+00	0.99948E+00
0.9400E+02	0.4700E+03	0.5697E+00	0.99948E+00
0.9500E+02	0.4750E+03	0.2615E+00	0.99948E+00
0.9600E+02	0.4800E+03	0.2865E+00	0.99948E+00
0.9700E+02	0.4850E+03	0.4980E+00	0.99967E+00
0.9800E+02	0.4900E+03	0.8079E+00	0.99967E+00
0.9900E+02	0.4950E+03	0.2000E+00	0.99967E+00
0.1000E+03	0.5000E+03	0.2000E+00	0.99967E+00
0.1010E+03	0.5050E+03	0.2233E+00	0.99967E+00
0.1020E+03	0.5100E+03	0.5961E+00	0.99967E+00
0.1030E+03	0.5150E+03	0.7979E+00	0.99967E+00
0.1040E+03	0.5200E+03	0.2023E+00	0.99967E+00
0.1050E+03	0.5250E+03	0.2029E+00	0.99967E+00
0.1060E+03	0.5300E+03	0.4054E+00	0.99967E+00
0-1070E+03	0.5350E+03	0.4018E+00	0.99967E+00
0.1080E+03	0.5400E+03	0.2025E+00	0.99967E+00
0.1090E+03	0.5450E+03	0.2005E+00	0.99967E+00
0.1100E+03	0.5500E+03	0.4374E+00	0.99967E+00
0.1100E+03	0.5550E+03	0.4084E+00	0.99967E+00
0.1120E+03	0.5550E+03	0.8017E+00	0.99976E+00
0.11205+03	0.5650E+03	0.9978E+00	0.99976E+00
0.1130E+03	0.5090E+03	0.3370E+00	0.99976E+00
0.1140E+03	0.5750E+03	0.2029B+00	0.99976E+00
0.1150E+03	0.5750E+03	0.2815E+00	0.99976E+00
•	0.5850E+03	0.7606E+00	0.99976E+00
0.1170E+03	0.5850E+03	0.9605E+00	0.99976E+00
0.1180E+03	U.53UUE+U3	v.50035100	0.99970B100

0.1190E+03	0.5950E+03	0.2024E+00	0.99976E+00
0.1200E+03	0.6000E+03	0.2120E+00	0.99976E+00
0.1210E+03	0.6050E+03	0.2099E+00	0.99976E+00
0.1220E+03	0.6100E+03	0.4567E+00	0.99976E+00
0.1230E+03	0.6150E+03	0.8154E+00	0.99976E+00
0.1230E+03	0.6200E+03	0.2712E+00	0.99976E+00
*		0.2712B+00	0:99976E+00
0.1250E+03	0.6250E+03		
0.1260E+03	0.6300E+03	0.9095E+00	0.99976E+00
0.1270E+03	0.6350E+03	0.9518E+00	0.99976E+00
0.1280E+03	0.6400E+03	0.2006E+00	0.99976E+00
0.1290E+03	0.6450E+03	0.4257E+00	0.99976E+00
0.1300E+03	0.6500E+03	0.3505E+00	0.99976E+00
0.1310E+03	0.6550E+03	0.7397E+00	0.9999E+00
0.1320E+03	0.6600E+03	0.8924E+00	0.9999E+00
0.1330E+03	0.6650E+03	0.9999E+00	0.9999E+00
0.1340E+03	0.6700E+03	0.2462E+00	0.9999E+00
0.1350E+03	0.6750E+03	0.3022E+00	0.99999E+00
0.1360E+03	0.6800E+03	0.5006E+00	0.9999E+00
0.1370E+03	0.6850E+03	0.9999E+00	0:9999E+00
0.1370E+03	0.6900E+03	0.2333E+00	0.99999E+00
0.1390E+03	0.6950E+03	0.2333E+00 0.2429E+00	0.99999E+00
0.1400E+03	0.0990E+03	0.2123E+00	0.99999E+00
	• • • • • • • • •	• • • • • • • •	0.99999E+00
0.1410E+03	0.7050E+03	0.8887E+00	***********
0.1420E+03	0.7100E+03	0.5822E+00	0.9999E+00
0.1430E+03	0.7150E+03	0.9595E+00	0.99999E+00
0.1440E+03	0.7200E+03	0.2022E+00	0.9999E+00
0.1450E+03	0.7250E+03	0.3399E+00	0.9999E+00
0.1460E+03	0.7300E+03	0.5479E+00	0.99999E+00
0.1470E+03	0.7350E+03	0.4937E+00	0.9999E+00
0.1480E+03	0.7400E+03	0.8568E+00	0.9999E+00
0.1490E+03	0.7450E+03	0.2559E+00	0.9999E+00
0.1500E+03	0.7500E+03	0.3557E+00	0.9999E+00
0.1510E+03	0.7550E+03	0.5400E+00	0.99999E+00
0.1520E+03	0.7600E+03	0.6019E+00	0.9999E+00
0.1520E+03	0.7650E+03	0.2112E+00	0.9999E+00
0.1540E+03	0.7700E+03	0.2854E+00	0.99999E+00
0.1510E+03	0.7750E+03	0.2051B+00	0.99999E+00
0.1560E+03	0.7730E+03	0.3944E+00	0.99999E+00
*	0000	0.3577E+00	0.99999E+00
0.1570E+03	0.7850E+03	0.3577E+00	0.99999E+00
0.1580E+03	0.7900E+03	***************************************	<u>.</u>
0.1590E+03	0.7950E+03	0.2023E+00	0.9999E+00
0.1600E+03	0.8000E+03	0.3414E+00	0.9999E+00
0.1610E+03	0.8050E+03	0.3607E+00	0.99999E+00
0.1620E+03	0.8100E+03	0.5577E+00	0.9999E+00
0.1630E+03	0.8150E+03	0.7863E+00	0.9999E+00
0.1640E+03	0.8200E+03	0.2000E+00	0.9999E+00
0.1650E+03	0.8250E+03	0.2209E+00	0.9999E+00
0.1660E+03	0.8300E+03	0.4072E+00	0.9999E+00
0.1670E+03	0.8350E+03	0.7932E+00	0.9999E+00
0.1680E+03	0.8400E+03	0.3731E+00	0.9999E+00
0.1690E+03	0.8450E+03	0.4897E+00	0.9999E+00
0.1700E+03	0.8500E+03	0.3578E+00	0.9999E+00
0.1700E+03	0.8550E+03	0.3052E+00	0.99999E+00
0.1710E+03	0.8600E+03	0.6876E+00	0.99999E+00
0.1720E+03	0.8650E+03	0.9976E+00	0.99999E+00
0.1730E+03		0.9975E+00	0.99999E+00
	0.8700E+03		
0.1750E+03	0.8750E+03	0.2349E+00	0.99999E+00
0.1760E+03	0.8800E+03	0.3260E+00	0.99999E+00
0.1770E+03	0.8850E+03	0.3816E+00	0.9999E+00
0.1780E+03	0.8900E+03	0.7423E+00	0.9999E+00
0.1790E+03	0.8950E+03	0.2007E+00	0.9999E+00

http://www.cuacrospace.com/carroll/ga/ga.out

0.1800E+03	0.9000E+03	0.2175E+00	0.9999E+00
0.1810E+03	0.9050E+03	0.2064E+00	0.99999E+00
0.1820E+03	0.9100E+03	0.2651E+00	0.9999E+00
0.1830E+03	0.9150E+03	0.4058E+00	0.9999E+00
0.1840E+03	0.9200E+03	0.2598E+00	0.99999E+00
0.1850E+03	0.9250E+03	0.7383E+00	0.9999E+00
0.1860E+03	0.9300E+03	0.9983E+00	0.99999E+00
0.1870E+03	0.9350E+03	0.1000E+01	0.10000E+01
0.1880E+03	0.9400E+03	0.2164E+00	0.10000E+01
0.1890E+03	0.9450E+03	0.3262E+00	0.10000E+01
0.1900E+03	0.9500E+03	0.4894E+00	0.10000E+01
0.1910E+03	0.9550E+03	0.5512E+00	0.10000E+01
0.1920E+03	0.9600E+03	0.5717E+00	0.10000E+01
0.1930E+03	0.9650E+03	0.2032E+00	0.10000E+01
0.1940E+03	0.9700E+03	0.6117E+00	0.10000E+01
0.1950E+03	0.9750E+03	0.7367E+00	0.10000E+01
0.1960E+03	0.9800E+03	0.9434E+00	0.10000E+01
0.1970E+03	0.9850E+03	0.2010E+00	0.10000E+01
0.1980E+03	0.9900E+03	0.2666E+00	0.10000E+01
0.1990E+03	0.9950E+03	0.3090E+00	0.10000E+01
U 3000E+03	0 1000E+04	0.5319E+00	0.10000E+01

```
parameter (indmax=200,nchrmax=30,nparmax=2)
```

- e indmax = maximum # of individuals, i.e. max population size
- e nchrmax maximum # of chromosomes (binary bits) per individual
 - nparmax maximum # of parameters which the chromosomes make up

This is version 1.7a, last updated on 4/2/2001.

Download from: http://cuaerospace.com/carroll/ga.html>

Copyright David L. Carroll; this code may not be reproduced for sale or for use in part of another code for sale without the express written permission of David L. Carroll.

This genetic algorithm (GA) driver is free for public use. My only request is that the user reference and/or acknowledge the use of this driver in any papers/reports/articles which have results obtained from the use of this driver. I would also appreciate a copy of such papers/articles/reports, or at least an e-mail message with the reference so I can get a copy. Thanks.

This program is a FORTRAN version of a genetic algorithm driver. This code initializes a random sample of individuals with different parameters to be optimized using the genetic algorithm approach, i.e. evolution via survival of the fittest. The selection scheme used is tournament selection with a shuffling technique for choosing random pairs for mating. The routine includes binary coding for the individuals, jump mutation, creep mutation, and the option for single-point or uniform crossover. Niching (sharing) and an option for the number of children per pair of parents has been added. More recently, an option for the use of a micro-GA has been added.

For companies wishing to link this GA driver with an existing code, I am available for some consulting work. Regardless, I suggest altering this code as little as possible to make future updates easier to incorporate.

Any users new to the GA world are encouraged to read David Goldberg's "Genetic Algorithms in Search, Optimization and Machine Learning," Addison-Wesley, 1989.

The seven FORTRAN GA files are:

gal70.f
ga.inp
ga2.inp (w/ different namelist identifier)
ga.out
ga.restart
params.f
ReadMe (this file!)

I have provided a sample subroutine "func", but ultimately the user must supply this subroutine "func" which should be your cost function. You should be able to run the code with the sample subroutine "func" and the provided ga.inp file and obtain the optimal function value of 1.0000 at generation 187 with the uniform crossover micro-GA enabled (this is 935 function evaluations). Note that because different computers may treat precision and truncation differently, I have seen cases where two computers using the same input produce different evolution histories (but still converge to the optimal).

I-still recommend using the micro-GA technique (microga=1) with uniform crossover (iunifrm=1). However, if possible, I strongly suggest that you use values of nposibl of 2**n (2, 4, 8, 16, 32, 64, etc.). While my test function works fine for other values of nposibl, I have encountered problems where the uniform crossover micro-GA has

difficulty with parameters having long bit strings and a non-2**n value of nposibl, e.g. nposibl=1000, will have 10 bits assigned (for this case I would suggest running nposibl=1024 rather than 1000); I am presently investigating possible fixes for this situation.

Updates:

Version 1.7 includes several improvements:

- (i) The coding and input files are cleaned up to provide identical output across a wider range of computers.
- (ii) The arrays have been rearranged to enable a more efficient caching of system memory. For cases with very large population sizes, run time improvements of as much as a factor of 4-6 were observed!

 For population sizes less than 1000 you will not see much change.
- (iii) A summary of the results has been added to the end of the output file.
- (iv) An alternate input file "ga2.inp" has been included. Some compilers require an '&' and a '/' in the namelist input file, rather than '\$' signs.
- (v) For those wishing to try ever harder test functions, the included function is now N-dimensional, where N is simply determined by the number of parameters specified (nparam).

Version 1.6.5 of the code allowed creep mutations to be implemented with the micro-GA technique. (This version was never officially released.)

Version 1.6.4 of the code has a minor modification to the niching routine and another minor modification which would only affect a user having a single parameter with more than 2**30 possibilities (probably noone has used this large a number).

Version 1.6.3 of the code fixes a bug in the niching routine. Niching should now work much better than in previous versions. A few other minor changes have been made (not worth mentioning). The sample function has been changed to something a bit more challenging.

Version 1.6.2 of the code has had major restructuring in the form of converting all of the operators (crossover, mutation, etc.) into subroutines. The code logic should be a little more understandable now and it lends itself to more easily modifying parts of the code. The counter kountmx (see v1.6.1 comments below) was added to the namelist input. Otherwise, code performance should be the same.

Version 1.6.1 of the code has very minor modifications. If you are already successfully using the code, then you will not need this update.

- Added a little documentation about changing format statements 1050, 1075, 1275, and 1500 when you change nparam or the total number of chromosomes (see below).
- (ii) I have commented out all of the lines of code dealing with cputime. The Macintosh specific SECNDS call was causing more questions than I had anticipated. However, other than commenting the lines out, I have left them in their location for reference in case the user wants a cputime added.
- (iii) I have included a sample output file.
- (iv) Added counter (kountmx) to control how frequently the restart file is written. This saves I/O time and wear and tear on storage device. Presently set to write every fifth generation.

Version 1.6 of the code has incorporated the ability to use a micro-GA approach; this significantly reduced the number of function evaluations to find the global maximum of my test function.

Version 1.5 of the code has added some more flexibility to your available options:

- You now specify the minimum and maximum values of the parameters rather than the minimum and the increment.
- You now specify the number of possibilities you want for each parameter, not the number of bits. This modification has two features: first, the program automatically calculates the number of bits per parameter, second, you are no longer forced to have a number of possibilities equal to 2**n. While the code is more efficient when there 2**n possibilities per parameter, it will run quite well with a lesser number; e.g. a colleague has 25 specific airfoil families he wants to investigate, greater than 16, less than 32.
- (iii) You can now specify specific parameters for niching. Earlier versions of the code forced you to niche on all parameters. Now, the input array 'nichflg' permits you to choose the parameters for niching.
- (iv) You have an input flag to prevent the printing of specific jump. and creep mutation information
- You now specify the maximum values of population size, number of parameters and number of chromosomes in an include file (params.f). This sets the maximum array sizes in the code. When running, the code only uses the array size up to npopsiz and nparam (from ga.inp) and nchrome (computed internally from the nposibl input array).

The code is presently set for a maximum population size of 200, 30 chromosomes (binary bits) and 2 parameters. These values can be changed in params f as appropriate for your problem. Correspondingly you will have to change a few 'write' and 'format' statements if you change nchrmax and/or nparmax. In particular, if you change nchrome and/or nparam, then you should change the 'format' statement numbers 1050, 1075, 1275, and 1500. For example, if you have a problem with 4 parameters and 16 chromosomes (bits), then you should change these format statements to be:

The CPU time related lines of code reference a Macintosh specific time function (SECNDS). To avoid compiler errors with other computers, I have commented out these lines of code. If you wish to have cputime output, then you will have to change the time functions for the specific computer you are running on. Most modern Unix machines will recognize the 'etime' function; these lines are added to the code along with the variable 'tarray' and 'cpu...again, to avoid compiler errors with different computers, these lines of code are also commented out.

A common problem arises with the Microsoft PowerStation compiler, i.e., PowerStation does not recognize the abbreviation NML for NAMELIST. If you are using PowerStation, you will likely have to substitute NAMELIST for all instances of NML.

Please feel free to contact me with questions, comments, or errors (hopefully none of latter).

Enjoy!

David L. Carroll
CU Aerospace
2004 South Wright Street Extended
Urbana, IL 61802

e-mail: carroll@cuaerospace.com

Phone: 217-333-8274 fax: 217-244-7757

micro-GA Tip:

My favorite GA technique is still the micro-GA. At this point, I recommend using the micro-GA with uniform crossover and a small population size. The following inputs gave me excellent performance:

microga - 1
npopsiz - 5
maxgen - 100
iunifrm - 1

I have also gotten good performance with the single-point crossover (iunifrm=0), micro-GA.

If you decide to use the micro-GA, you will not need to worry about the population sizing or creep mutation tips below.

See-the Krishnakumar reference below for more information-about micro-GA's.

Population Sizing Tip:

I've had a lot of people ask me about population sizing, especially people who are attempting large problems where 100 individuals is probably not enough. The true authority on the subject is David Goldberg, but here is a crude population scaling law in my paper (based on Goldberg & Deb, 1992):

npopsiz = order[(1/k)(2**k)] for binary coding

where I - nchrome and k is the average size of the schema of interest (effectively the average number of bits per parameter, i.e. approximately equal to nchrome/nparam, rounded to the nearest integer). I find that when I have uniform crossover and niching turned on (which I recommend doing), that this scaling law is usually overkill, i.e. you can most likely get by with populations at least twice as small.

Remember to make the parameter 'indmax' (in 'params.f') greater than or equal to 'npopsiz'.

Creep Mutation Probability Tip:

I generally like to have approximately the same number of creep mutations and jump mutations per generation. Using basic probabilistic arguments, it can be shown that you will get approximately the same number of creep and jump

pcreep - (nchrome/nparam) * pmutate

where pmutate (the jump mutation probability) is 1/npopsiz.

Suggested reading that I have found to be of use:

Goldberg, D. E., and Richardson, J., "Genetic Algorithms with Sharing for Multimodal Function Optimization," Genetic Algorithms and their Applications: Proceedings of the Second International Conference on Genetic Algorithms, 1987, pp. 41-49.

Goldberg, D. E., "Genetic Algorithms in Search, Optimization and Machine Learning," Addison-Wesley, 1989.

Goldberg, D. E., "A Note on Boltzmann Tournament Selection for Genetic Algorithms and Population-Oriented Simulated Annealing, "-in: Complex Systems, Vol. 4, Complex Systems Publications, Inc., 1990, pp. 445-460.

Goldberg, D. E., "Real-coded Genetic Algorithms, Virtual Alphabets, and Blocking," in: Complex Systems, Vol. 5, Complex Systems Publications, Inc., 1991, pp. 139-167.

Goldberg, D. E., and Deb, K., "A Comparitive Analysis of Selection Schemes Used in Genetic Algorithms," in: Foundations of Genetic Algorithms, ed. by Rawlins, G.J.E., Morgan Kaufmann Publishers, San Mateo, CA, pp. 69-93, 1991.

Goldberg, D. E., Deb, K., and Clark, J. H., "Genetic Algorithms, Noise, and the Sizing of Populations," in: Complex Systems, Vol. 6, Complex Systems Pub., Inc., 1992, pp. 333-362.

Krishnakumar, K., "Micro-Genetic Algorithms for Stationary and Non-Stationary Function Optimization," SPIE: Intelligent Control and Adaptive Systems, Vol. 1196, Philadelphia, PA, 1989.

Syswerda, G., "Uniform Crossover in Genetic Algorithms," in:
Proceedings of the Third International Conference on Genetic Algorithms,
Schaffer, J. (Ed.), Morgan Kaufmann Publishers, Los Altos, CA, pp. 2-9,
1989.

If you are interested in my work (which may give some insights into how and why I coded some aspects of my GA), I can mail copies of three papers of mine.

G. Yang, L.E. Reinstein, S. Pai, Z. Xu, and D.L. Carroll, "A new genetic algorithm technique in optimization of permanent 125-I prostate implants," Medical Physics, Vol. 25, No. 12, 1998, pp. 2308-2315.

Carroll, D. L., "Chemical Laser Modeling with Genetic Algorithms," AIAA J., Vol. 34, 2, 1996, pp.338-346.

(A preprint version of this paper can now be downloaded in PDF format via my website:

<http://cuaerospace.com/carroll/gatips.html> look for AIAA1996.pdf)

Carroll, D. L., "Genetic Algorithms and Optimizing Chemical Oxygen-Iodine

Lasers," Developments in Theoretical and Applied Mechanics, Vol. XVIII, eds. H.B. Wilson, R.C. Batra, C.W. Bert, A.M.J. Davis, R.A. Schapery, D.S. Stewart, and F.F. Swinson, School of Engineering, The University of Alabama, 1996, pp.411-424.

(This paper can now be downloaded in PDF format via my website:
http://cuaerospace.com/carroll/gatips.html look for SECTAM18.pdf)

Disclaimer: this program is not guaranteed to be free of error (although it is believed to be free of error), therefore it should not be relied on for solving problems where an error could result in injury or loss. If this code is used for such solutions, it is entirely at the user's risk and the author disclaims all liability.

The following portion of this disclosure was created in *Powerpoint* for purposes of further describing the present invention. It the specification, especially with reference to FIGS. 37-47C, respectively, particularly concerns bandwidth enhanced normal mode helical antennas. It begins by setting forth the objectives, considerations, and questions addressed in the beginning stages of development of the present invention. The aeffects of different physical antenna parameters on antenna performance are addressed by showing the aeffect in the VSWR by these variations.

5

10

15

20

25


30


The remainder of the <u>following disclosure portion discussion</u> with respect to FIGS. <u>37-47C</u>, respectively, shows several different antenna designs and in graphical form illustrates the respective performance of each. A straight wire antenna, a simple helix, and a triple helix are all examined. Each antenna is modified by the addition of various parasitic elements. The characteristics of each of these antennas are then illustrated. The VSWR, directivity, and input impedance are shown so that the different antennas having different combinations of parasitic elements can be analyzed effectively.

This portion of the disclosure concludes by summarizing the results obtained from the different combinations. The conclusions drawn from these results are then set forth. Results obtained from the different antenna combinations are then summarized and conclusions drawn from these results are set forth. It illustrates Such results illustrate the initial indications that bandwidth improvements could be made by the addition of these parasitic elements.

Objectives for the subject antenna include it being low-profile, omnidirectional and broadband. Design considerations include: (a) the helix can be made shorter by adjusting the pitch, (b) normal mode helix has narrow bandwidth, and (c) parasitic elements increase the bandwidth of straight wires. Questions addressed in the subject analysis include determination of whether the bandwidth of the normal mode helix can be improved with parasitic elements and if so, what are suitable structures for the parasites.

FIG. 37 presents numerical results of the effect of pitch angle on helix VSWR for a helical antenna having a total wire length of 75cm and a wire radius of 0.5cm. The different curves plotted in the graph of FIG. 37 are for antennas having a helix pitch (θ) of 30, 40, 50, 60 and 70 degrees. For an antenna having a pitch of 30 degrees, a height reduction of 45.0% and a total height of 41.3cm is achievable. For an antenna having a





triple helix antenna having four straight wire parasites, such as depicted in FIG. 47B, a triple helix antenna and a single helix antenna. For the triple helix antenna having four parasites, a VSWR less than 3.5 is achieved on a frequency range from 110 MHz to 380 MHz for a bandwidth ratio of 3.45:1. FIG. 47C provides a graphical representation of antenna directivity versus frequency for the triple helix antenna with different values for the helix pitch angles (θ). FIG. 47D provides a graphical representation of antenna directivity versus frequency for the triple helix antenna with parasites (such as in FIG. 47B) with different values for the helix pitch angles (θ).

A summary of the results determined from the numerical data provided in FIGS. 40A through 47D, respectively, is now presented in Table 8 below. These results show that parasitic straight wires and helices are useful for improving the bandwidth of helical antennas. Also, the triple helix has reduced VSWR over the frequency band which makes the structure more amenable to improvement by parasites.

Driven Element	Number of Parasites	Types of Parasites	Bandwidth Ratio
Straight Wire	2	Straight wire	1.90:1
Straight Wire	4	Straight wire	<u>2.05:1</u>
Helix	2	Straight wire	<u>1.86:1</u>
Helix	4	Straight wire	<u>2.23:1</u>
Helix	2	Helix (same cylinder)	<u>1.86:1</u>
Helix	2	Helix (different cylinders)	<u>1.81:1</u>
Triple Helix	4	Straight wire	<u>3.45:1</u>

15 <u>Table 8</u>

5

10

The following further portion of this disclosure was also created in Powerpoint for purposes of further describing the present invention. It particularly concerns the sleeve-cage monopole and sleeve helix for wide band operation. It sets forth the objectives, considerations, and questions addressed in the development of the present invention, and presents relevant background information and illustrations of the antennas discussed within. The VSWR, input impedance, and directivity are given for each antenna with and without the addition of parasitic elements. Illustrations and graphical data for the cage monopole, the sleeve-cage monopole, the quadrifilar helix, and the sleeve-helix are presented. The relevant data for each is then shown in a table so that a side-by-side comparison can be made to more clearly illustrate the improvements made in the antenna characteristics by the optimal placement of parasitic elements. The physical measurements and characterization values of various antennas optimized for various VSWR values are presented. This data is then presented in a comparison to several background antennas to illustrate the improvements in antenna performance made by the present invention.

5

10

15

Overview

- Introduction
- Helix geometry considerations
- Procedure for efficient optimization of helix with parasitic elements
- Numerical results for open sleeve monopole
- Numerical results for bandwidthimprovement of normal mode helix
- Conclusions

Introduction

Objectives for Antenna

- Low-profile
- Omnidirectional
- Broadband















- Helix can be made shorter by adjusting the pitch
- Normal mode helix has narfow bandwidth
- Parasitic elements increase the bandwidthof straight wires

Questions addressed

- Can the bardwidth of the normal mode helix be improved with parasitic elements?
- If 86, what are suitable structures for the parasites?





References on Reduced-Rank Matrices

Propagation Society (APS) Symposium, Montreal, Canada, S.D. Rogers and C.M. Butler, "Reduced Rank Matrices for Curved Wire Structures," Digest of 1997 Antennas and vol. 1, pp. 68-71, July N997. S.D. Rogers, "Efficient Numerical Techniques for Curved Wires," Masters Thesis, Clemson University, August 1997.

Website for above liturature and copies of these slides www.epg.clemson.edu/~sdroger

Reference


Genetic algorithm driver:


Carroll, D.L., "A FORTRAN Genetic Algorithm Code",


Univ. of Illinois, Urbana L.


http://www.staff.uiuc.edu/~carroll/ga.html


The above genetic algorithm driver was used to search for optimum parameter values for the geometry.
































Summary of Results

Driven Element	Number of Parasites	Type of Parasites	BandwidtkRatio
Straight wire	2	Straight wire	1.90:1
Straight wire	4	Straight wire	2.05:1
Helix	2	Straight wire	1.86:1
Helix	4	Straight wire	2.23:1
Helix	7/	Helix (same cylinder)	1.86:1
Helix	7	Helix (different cylinders)	1.81:1
Triple helfx	4	Straight wire	3.45.4

Conclusions

Parasitic straight wires and helices are useful for improving the bandwidth of holical antennas.

The triple helix has a reduced VSWR over the frequency band which makes the structure more amenable to improvement by parasites.

ABSTRACT OF THE DISCLOSURE

5

10

15

20

25

30

A method for applying an algorithm to facilitate the design of wideband omnidirectional antennas, and the design of sleeve cage monopole and sleeve helix units includes rapid resolution of a complex relationship among antenna components to yield an optimal system. A genetic algorithm is used with fitness values for design factors expressed in terms to yield optimum combinations. Cage antennas are optimized via a genetic algorithm for operation over a wide band with low VSWR. Genetic algorithms and an integral equation solver are employed to determine the position and lengths of parasitic wires around a cage antenna in order to minimize VSWR over a band. The cage may be replaced by a normal mode quadrifilar helix for height reduction and with reoptimized parasites. This technology provides a method (application) of an algorithm to facilitate the design of wideband operations of antennas, and the design of sleeve cage monopole and sleeve helix, units. The technology is of interest/commercial potential throughout the audio communications community. Omnidirectional capabilities and enhanced wideband capabilities are two desirable features for the design of many antenna applications. Designing omnidirectional antennas with wideband capabilities requires rapid resolution of complex relationship among antenna components to yield an optimal system. The invention comprises the use of a genetic algorithm with fitness values for design factors expressed in terms to yield optimum combinations of at least two types of antennas. Cage antennas are optimized via a genetic algorithm (GA) for operation over a wide band with low voltage standing wave ratio (VSWR). Numerical results are compared to those of other dual band and broadband antennas from the literature. Measured results for one cage antenna are presented. Genetic algorithms and an integral equation solver are employed to determine the position and lengths of parasitie wires around a cage antenna in order to minimize voltage standing wave ratio (VSWR) over a band. The cage is replaced by a normal mode quadrifilar helix for height reduction and the parasites are re-optimized. Measurements of the input characteristics of these optimized structures are presented along with data obtained from solving the electric field integral equation.

Genetic algorithms (Y. Rahmat-Samii and E. Michielssen, Electromagnetic Optimizations by Genetic Algorithms, New York: John Wiley and Sons, Inc., 1999) are used here in conjunction with an integral equation solution technique to determine the placement of the parasitic wires around a driven cage. The cage may be replaced by a quadrifilar helix operating in the normal mode in order to shorten the antenna. Measurements of these optimized structures are included for verification of the bandwidth improvements.